



US010165912B2

(12) **United States Patent**
Conrad

(10) **Patent No.:** **US 10,165,912 B2**

(45) **Date of Patent:** **Jan. 1, 2019**

(54) **SURFACE CLEANING APPARATUS**

(71) Applicant: **Omachron Intellectual Property Inc.**,
Hampton (CA)

(72) Inventor: **Wayne Ernest Conrad**, Hampton (CA)

(73) Assignee: **Omachron Intellectual Property Inc.**,
Hampton, Ontario (CA)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 466 days.

(21) Appl. No.: **15/076,060**

(22) Filed: **Mar. 21, 2016**

(65) **Prior Publication Data**

US 2016/0198914 A1 Jul. 14, 2016

Related U.S. Application Data

(60) Continuation-in-part of application No. 14/822,211,
filed on Aug. 10, 2015, now Pat. No. 9,888,817, and
(Continued)

(51) **Int. Cl.**
A47L 5/24 (2006.01)
A47L 5/22 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *A47L 5/225* (2013.01); *A47L 5/24*
(2013.01); *A47L 5/28* (2013.01); *A47L 9/1625*
(2013.01);
(Continued)

(58) **Field of Classification Search**

CPC ... *A47L 5/24*; *A47L 5/28*; *A47L 5/225*; *A47L*
9/1625; *A47L 9/1683*; *A47L 9/1691*;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

911,258 A 2/1909 Neumann
1,600,762 A 9/1926 Hawley
(Continued)

FOREIGN PATENT DOCUMENTS

AU 112778 4/1940
CA 1077412 A1 5/1980
(Continued)

OTHER PUBLICATIONS

International Preliminary Examination Report on International appli-
cation No. PCT/CA2015/051332, dated Mar. 7, 2016.
(Continued)


Primary Examiner — David Redding

(74) *Attorney, Agent, or Firm* — Philip C. Mendes da
Costa; Bereskin & Parr LLP/S.E.N.C.R.L., s.r.l.

(57) **ABSTRACT**

A surface cleaning apparatus comprises a surface cleaning
head, an upright section moveably mounted to the surface
cleaning head, and a portable cleaning unit removably
mounted to the upright section and comprising an energy
storage member and a portable cleaning unit suction motor.
The energy storage member provides the portable cleaning
unit suction motor with power at least when the portable
cleaning unit is switched on and when the portable cleaning
unit is removed from the upright section.

8 Claims, 28 Drawing Sheets



Related U.S. Application Data

a continuation-in-part of application No. 14/875,381, filed on Oct. 5, 2015, now Pat. No. 9,545,181, which is a continuation of application No. 13/782,217, filed on Mar. 1, 2013, now Pat. No. 9,192,269, which is a continuation-in-part of application No. 13/720,754, filed on Dec. 19, 2012, now Pat. No. 8,752,239, which is a division of application No. 11/954,331, filed on Dec. 12, 2007, now Pat. No. 8,359,705.

(60) Provisional application No. 62/093,189, filed on Dec. 17, 2014, provisional application No. 60/884,767, filed on Jan. 12, 2007, provisional application No. 60/870,175, filed on Dec. 15, 2006.

(51) **Int. Cl.**

A47L 9/28 (2006.01)
A47L 5/28 (2006.01)
A47L 9/16 (2006.01)
A47L 9/32 (2006.01)

(52) **U.S. Cl.**

CPC *A47L 9/1683* (2013.01); *A47L 9/1691* (2013.01); *A47L 9/2868* (2013.01); *A47L 9/2878* (2013.01); *A47L 9/2884* (2013.01); *A47L 9/325* (2013.01)

(58) **Field of Classification Search**

CPC *A47L 9/325*; *A47L 9/2884*; *A47L 9/2868*; *A47L 9/2878*
 USPC 15/329, 331, DIG. 1
 IPC *A47L 5/24*
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,797,812 A 3/1931 Waring
 1,898,608 A 2/1933 Alexander
 1,937,765 A 12/1933 Leathers
 2,015,464 A 9/1935 Saint-Jacques
 2,152,114 A 3/1939 Tongeren
 2,542,634 A 2/1951 Davis
 2,678,110 A 5/1954 Madsen
 2,731,102 A 1/1956 James
 2,811,219 A 10/1957 Wenzl
 2,846,024 A 8/1958 Bremi
 2,913,111 A 11/1959 Rogers
 2,917,131 A 12/1959 Evans
 2,937,713 A 5/1960 Stephenson et al.
 2,942,691 A 6/1960 Dillon
 2,942,692 A 6/1960 Benz
 2,946,451 A 7/1960 Culleton
 2,952,330 A 9/1960 Winslow
 2,981,369 A 4/1961 Yellott et al.
 3,032,954 A 5/1962 Racklyeft
 3,085,221 A 4/1963 Francis
 3,130,157 A 4/1964 Kelsall et al.
 3,200,568 A 8/1965 McNeil
 3,204,772 A 9/1965 Ruxton
 3,217,469 A 11/1965 Eckert
 3,269,097 A 8/1966 German
 3,320,727 A 5/1967 Farley
 3,372,532 A 3/1968 Campbell
 3,426,513 A 2/1969 Bauer
 3,518,815 A 7/1970 Peterson et al.
 3,530,649 A 9/1970 Porsch et al.
 3,543,325 A 12/1970 Hamrick
 3,561,824 A 2/1971 Homan
 3,582,616 A 6/1971 Wrob
 3,684,093 A 5/1972 Kono
 3,675,401 A 7/1972 Cordes
 3,822,533 A 7/1974 Oranje

3,898,068 A 8/1975 McNeil et al.
 3,933,450 A 1/1976 Percevaut
 3,988,132 A 10/1976 Oranje
 3,988,133 A 10/1976 Schady
 4,097,381 A 6/1978 Ritzler
 4,187,088 A 2/1980 Hodgson
 4,218,805 A 8/1980 Brazier
 4,236,903 A 12/1980 Malmsten
 4,307,485 A 12/1981 Dessig
 4,373,228 A 2/1983 Dyson
 4,382,804 A 5/1983 Mellor
 4,409,008 A 10/1983 Solymes
 4,486,207 A 12/1984 Baillie
 4,494,270 A 1/1985 Ritzau et al.
 4,523,936 A 6/1985 Disanza, Jr.
 4,678,588 A 7/1987 Shortt
 4,700,429 A 10/1987 Martin et al.
 4,744,958 A 5/1988 Pircon
 4,778,494 A 10/1988 Patterson
 4,826,515 A 5/1989 Dyson
 D303,173 S 8/1989 Miyamoto et al.
 4,853,008 A 8/1989 Dyson
 4,853,011 A 8/1989 Dyson
 4,853,111 A 8/1989 MacArthur et al.
 4,900,270 A 2/1990 Edwards et al.
 4,905,342 A 3/1990 Ataka
 4,944,780 A 7/1990 Usmani
 4,980,945 A 1/1991 Bewley
 5,054,157 A 10/1991 Werner et al.
 5,080,697 A 1/1992 Finke
 5,090,976 A 2/1992 Dyson
 5,129,125 A 7/1992 Gamou et al.
 5,224,238 A 7/1993 Barlett
 5,230,722 A 7/1993 Yonkers
 5,254,019 A 10/1993 Noschese
 5,267,371 A 12/1993 Soler et al.
 5,287,591 A 2/1994 Rench et al.
 5,307,538 A 5/1994 Rench et al.
 5,309,600 A 5/1994 Weaver et al.
 5,309,601 A 5/1994 Hampton et al.
 5,347,679 A 9/1994 Saunders et al.
 5,363,535 A 11/1994 Rench et al.
 5,466,172 A 11/1995 Carstens et al.
 5,481,780 A 1/1996 Daneshvar
 5,515,573 A 5/1996 Frey
 5,599,365 A 2/1997 Alday et al.
 D380,033 S 6/1997 Theiss et al.
 5,704,400 A 1/1998 Eldridge
 5,709,007 A 1/1998 Chiang
 5,755,096 A 5/1998 Holleyman
 5,815,878 A 10/1998 Murakami et al.
 5,815,881 A 10/1998 Sjogreen
 5,858,038 A 1/1999 Dyson et al.
 5,858,043 A 1/1999 Geise
 5,893,938 A 4/1999 Dyson et al.
 5,935,279 A 8/1999 Kilstrom
 5,941,729 A 8/1999 Sri-Jayantha
 5,950,274 A 9/1999 Kilstrom
 5,970,572 A 10/1999 Homas
 6,071,095 A 6/2000 Verkaart
 6,071,321 A 6/2000 Trapp et al.
 6,080,022 A 6/2000 Shaberman et al.
 6,094,775 A 8/2000 Behmer
 6,122,796 A 9/2000 Downham et al.
 6,210,469 B1 4/2001 Tokar
 6,221,134 B1 4/2001 Conrad et al.
 6,228,260 B1 5/2001 Conrad et al.
 6,231,645 B1 5/2001 Conrad et al.
 6,251,296 B1 6/2001 Conrad et al.
 6,260,234 B1 7/2001 Wright et al.
 6,295,692 B1 10/2001 Shideler
 6,345,408 B1 2/2002 Nagai et al.
 6,406,505 B1 6/2002 Oh et al.
 6,434,785 B1 8/2002 Vandenbelt et al.
 6,440,197 B1 8/2002 Conrad et al.
 D466,867 S 12/2002 Krobusek
 6,500,025 B1 12/2002 Moenkhaus et al.
 6,502,278 B2 1/2003 Oh et al.
 6,519,810 B2 2/2003 Kim

(56)

References Cited

U.S. PATENT DOCUMENTS

6,531,066	B1	3/2003	Saunders et al.	8,117,712	B2	2/2012	Dyson et al.
6,536,072	B2	3/2003	Thur et al.	8,146,201	B2	4/2012	Conrad
6,540,549	B2	4/2003	Rupert	8,151,407	B2	4/2012	Conrad
6,553,612	B1	4/2003	Dyson et al.	8,152,877	B2	4/2012	Greene
6,553,613	B2	4/2003	Onishi et al.	8,156,609	B2	4/2012	Milne et al.
6,560,818	B1	5/2003	Hasko	8,161,599	B2	4/2012	Griffith et al.
6,581,239	B1	6/2003	Dyson et al.	8,225,456	B2	7/2012	Hakan et al.
6,599,338	B2	7/2003	Oh et al.	8,484,799	B2	7/2013	Conrad
6,599,350	B1	7/2003	Rockwell et al.	8,673,487	B2	3/2014	Churchill
6,613,316	B2	9/2003	Sun et al.	8,834,209	B2	9/2014	Conrad
6,623,539	B2	9/2003	Lee et al.	9,192,269	B2	11/2015	Conrad
6,625,845	B2	9/2003	Matsumoto et al.	2002/0011053	A1	1/2002	Oh
6,640,385	B2	11/2003	Oh et al.	2002/0062531	A1	5/2002	Oh
6,648,934	B2	11/2003	Choi et al.	2002/0088208	A1	7/2002	Lukac et al.
6,712,868	B2	3/2004	Murphy et al.	2002/0112315	A1	8/2002	Conrad
6,732,403	B2	5/2004	Moore et al.	2002/0134059	A1	9/2002	Oh
6,746,500	B1	6/2004	Park et al.	2002/0178535	A1	12/2002	Oh et al.
6,782,583	B2	8/2004	Oh	2002/0178698	A1	12/2002	Oh et al.
6,782,585	B1	8/2004	Conrad et al.	2002/0178699	A1	12/2002	Oh
6,810,558	B2	11/2004	Lee	2003/0046910	A1	3/2003	Lee
6,818,036	B1	11/2004	Seaman	2003/0066273	A1	4/2003	Choi et al.
6,833,015	B2	12/2004	Oh et al.	2003/0106180	A1	6/2003	Tsen
6,868,578	B1	3/2005	Kasper et al.	2003/0159238	A1	8/2003	Oh
6,874,197	B1	4/2005	Conrad	2003/0159411	A1	8/2003	Hansen et al.
6,896,719	B2	5/2005	Coates et al.	2003/0200736	A1	10/2003	Ni
6,929,516	B2	8/2005	Brochu et al.	2004/0010885	A1	1/2004	Hitzelberger et al.
6,962,506	B1	11/2005	Krobusek	2004/0025285	A1	2/2004	McCormick et al.
6,968,596	B2	11/2005	Oh et al.	2004/0088817	A1	5/2004	Cochran et al.
6,976,885	B2	12/2005	Lord	2004/0216263	A1	11/2004	Best et al.
7,113,847	B2	9/2006	Chmura et al.	2004/0216264	A1	11/2004	Shaver et al.
7,128,770	B2	10/2006	Oh et al.	2005/0081321	A1	4/2005	Milligan et al.
7,160,346	B2	1/2007	Park	2005/0115409	A1	6/2005	Conrad
7,162,770	B2	1/2007	Davidshofer	2005/0132528	A1	6/2005	Yau
7,175,682	B2	2/2007	Nakai et al.	2005/0198769	A1	9/2005	Lee et al.
7,188,388	B2	3/2007	Best et al.	2005/0198770	A1	9/2005	Jung et al.
7,198,656	B2	4/2007	Takemoto et al.	2005/0252179	A1	11/2005	Oh et al.
7,222,393	B2	5/2007	Kaffenberger et al.	2005/0252180	A1	11/2005	Oh et al.
7,272,872	B2	9/2007	Choi	2006/0037172	A1	2/2006	Choi
7,278,181	B2	10/2007	Harris et al.	2006/0090290	A1	5/2006	Lau
7,341,611	B2	3/2008	Greene et al.	2006/0042206	A1	6/2006	Arnold et al.
7,354,468	B2	4/2008	Arnold et al.	2006/0123590	A1	6/2006	Fester et al.
7,370,387	B2	5/2008	Walker et al.	2006/0137304	A1	6/2006	Jeong et al.
7,377,007	B2	5/2008	Best	2006/0137306	A1	6/2006	Jeong et al.
7,377,953	B2	5/2008	Oh	2006/0137309	A1	6/2006	Jeong et al.
7,386,915	B2	6/2008	Blocker et al.	2006/0137314	A1	6/2006	Conrad et al.
7,395,579	B2	7/2008	Oh	2006/0156508	A1	7/2006	Khalil
7,426,768	B2	9/2008	Peterson et al.	2006/0162298	A1	7/2006	Oh et al.
7,429,284	B2	9/2008	Oh	2006/0162299	A1	7/2006	North
7,448,363	B1	11/2008	Rasmussen et al.	2006/0168922	A1	8/2006	Oh
7,449,040	B2	11/2008	Conrad et al.	2006/0168923	A1	8/2006	Lee et al.
7,485,164	B2	2/2009	Jeong et al.	2006/0207055	A1	9/2006	Ivarsson et al.
7,488,363	B2	2/2009	Jeong et al.	2006/0207231	A1	9/2006	Arnold
7,547,337	B2	6/2009	Oh et al.	2006/0230715	A1	10/2006	Oh et al.
7,547,338	B2	6/2009	Kim et al.	2006/0230723	A1	10/2006	Kim et al.
7,563,298	B2	7/2009	Oh	2006/0230724	A1	10/2006	Han et al.
7,565,853	B2	7/2009	Arnold et al.	2006/0236663	A1	10/2006	Oh
7,588,616	B2	9/2009	Conrad et al.	2006/0254226	A1	11/2006	Jeon
7,597,730	B2	10/2009	Yoo et al.	2006/0278081	A1	12/2006	Han et al.
7,628,831	B2	12/2009	Gomiciaga-Pereda et al.	2006/0288516	A1	12/2006	Sawalski
7,740,676	B2	6/2010	Burnham et al.	2007/0077810	A1	4/2007	Gogel
7,770,256	B1	8/2010	Fester	2007/0079473	A1	4/2007	Min
7,776,120	B2	8/2010	Conrad	2007/0079585	A1	4/2007	Oh et al.
7,779,506	B2	8/2010	Kang et al.	2007/0095028	A1	5/2007	Kim
7,798,845	B1	9/2010	Buchanan	2007/0095029	A1	5/2007	Min
7,803,207	B2	9/2010	Conrad	2007/0136984	A1	6/2007	Hsu
7,805,804	B2	10/2010	Loebig	2007/0209334	A1	9/2007	Conrad
7,811,349	B2	10/2010	Nguyen	2007/0209335	A1	9/2007	Conrad
7,867,308	B2	1/2011	Conrad	2007/0271724	A1	11/2007	Hakan et al.
7,922,794	B2	4/2011	Morphey	2007/0289089	A1	12/2007	Yacobi
7,931,716	B2	4/2011	Oakham	2007/0289266	A1	12/2007	Oh
7,938,871	B2	5/2011	Llyod	2008/0040883	A1	2/2008	Beskow et al.
7,979,959	B2	7/2011	Courtney	2008/0047091	A1	2/2008	Nguyen
8,021,453	B2	9/2011	Howes	2008/0057780	A1	3/2008	O'Rourke
8,062,398	B2	11/2011	Luo et al.	2008/0134460	A1	6/2008	Conrad
8,078,761	B2	12/2011	Cardina et al.	2008/0134462	A1	6/2008	Jansen et al.
				2008/0178416	A1	7/2008	Conrad
				2008/0178420	A1	7/2008	Conrad
				2008/0190080	A1	8/2008	Conrad
				2008/0196194	A1	8/2008	Conrad

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0301903 A1 12/2008 Cunningham et al.
 2009/0067944 A1 3/2009 Motta et al.
 2009/0100633 A1 4/2009 Jeon
 2009/0113659 A1 5/2009 Jeon
 2009/0144932 A1 6/2009 Yoo
 2009/0165431 A1 7/2009 Oh
 2009/0205160 A1 8/2009 Conrad
 2009/0205161 A1 8/2009 Conrad
 2009/0205298 A1 8/2009 Hyun et al.
 2009/0209666 A1 8/2009 Hellberg et al.
 2009/0265877 A1 10/2009 Dyson et al.
 2009/0282639 A1 11/2009 Dyson et al.
 2009/0300874 A1 12/2009 Tran et al.
 2009/0300875 A1 12/2009 Inge et al.
 2009/0307564 A1 12/2009 Vedantham et al.
 2009/0307863 A1 12/2009 Milne et al.
 2009/0307864 A1 12/2009 Dyson
 2009/0308254 A1 12/2009 Oakham
 2009/0313958 A1 12/2009 Gomiciaga-Pereda et al.
 2009/0313959 A1 12/2009 Gomiciaga-Pereda et al.
 2010/0083459 A1 4/2010 Beskow et al.
 2010/0132319 A1 6/2010 Ashbee et al.
 2010/0154150 A1 6/2010 Mcleod
 2010/0175217 A1 7/2010 Conrad
 2010/0197157 A1 8/2010 Wang
 2010/0212104 A1 8/2010 Conrad
 2010/0224073 A1 9/2010 Oh et al.
 2010/0229321 A1 9/2010 Dyson et al.
 2010/0229328 A1 9/2010 Conrad
 2010/0242210 A1 9/2010 Conrad
 2010/0243158 A1 9/2010 Conrad
 2010/0293745 A1 11/2010 Coburn
 2010/0299865 A1 12/2010 Conrad
 2010/0299866 A1 12/2010 Conrad
 2011/0023261 A1 2/2011 Proffitt, II et al.
 2011/0146024 A1 6/2011 Conrad
 2011/0168332 A1 7/2011 Bowe et al.
 2012/0060322 A1 3/2012 Simonelli et al.
 2012/0216361 A1 8/2012 Millington et al.
 2012/0222245 A1 9/2012 Conrad
 2012/0222260 A1 9/2012 Conrad
 2012/0222262 A1 9/2012 Conrad
 2014/0137362 A1 5/2014 Smith
 2014/0137363 A1 5/2014 Wilson
 2014/0137364 A1 5/2014 Stickney et al.
 2014/0182080 A1 7/2014 Lee et al.
 2014/0208538 A1 7/2014 Visel et al.

FOREIGN PATENT DOCUMENTS

CA 1218962 A 3/1987
 CA 2450450 A1 12/2004
 CA 2484587 A1 4/2005
 CA 2438079 C 8/2009
 CA 2659212 A1 9/2010
 CN 1493244 A 5/2004
 CN 1887437 A 1/2007
 CN 202932850 U 5/2013
 DE 875134 C 4/1953
 DE 9216071 U1 2/1993
 DE 4232382 C1 3/1994
 EP 493950 A2 7/1992
 EP 1200196 B1 6/2005
 EP 1779761 A2 5/2007
 EP 1815777 A1 8/2007
 EP 1594386 B1 4/2009
 EP 1676516 B1 1/2010
 EP 2308360 A2 4/2011
 EP 1629758 B1 10/2013
 EP 2848173 A1 3/2015
 FR 2812531 B1 11/2004
 GB 100791 A 12/1953
 GB 1111074 A 4/1968
 GB 2035787 B 10/1982
 GB 2126471 * 3/1984

GB 2163703 B 1/1988
 GB 2268875 A 1/1994
 GB 2307849 A 6/1997
 GB 2282979 B 10/1997
 GB 2365324 B 7/2002
 GB 2441962 B 3/2011
 GB 2466290 B 10/2012
 GB 2508035 A 5/2014
 JP 61131720 A 6/1986
 JP 2000140533 A 5/2000
 JP 2010178773 A 8/2010
 JP 2010220632 A 10/2010
 JP 2011189132 A 9/2011
 JP 2011189133 A 9/2011
 WO 1980002561 A1 11/1980
 WO 9627446 A1 9/1996
 WO 9720492 A1 6/1997
 WO 9809121 A1 3/1998
 WO 9843721 A1 10/1998
 WO 0107168 A1 2/2001
 WO 2004069021 A1 8/2004
 WO 2006026414 A3 8/2007
 WO 2008009883 A1 1/2008
 WO 2008009888 A1 1/2008
 WO 2008009890 A1 1/2008
 WO 2008009891 A1 1/2008
 WO 2008088278 A2 7/2008
 WO 2009026709 A1 3/2009
 WO 2010102396 A1 9/2010
 WO 2010142968 A1 12/2010
 WO 2010142969 A1 12/2010
 WO 2010142970 A1 12/2010
 WO 2010142971 A 12/2010
 WO 2011054106 A1 5/2011
 WO 2012042240 A1 4/2012
 WO 2012117231 A1 9/2012

OTHER PUBLICATIONS

International Search Report and Written Opinion received in connection to International Patent Application No. PCT/CA2007/002211, dated Apr. 21, 2008.
 Euro-Pro Shark Cordless Hand Vac Owner's Manual, Published in 2002.
 United States Office Action, dated Jul. 22, 2010, for U.S. Appl. No. 11/953,292.
 United States Office Action, dated Feb. 16, 2011, for U.S. Appl. No. 11/953,292.
 International Search Report and Written Opinion received in connection to International Patent Application No. PCT/CA2015/050661, dated Oct. 19, 2015.
 Office Action dated Jul. 7, 2010, for Canadian Patent Application No. 2,675,714.
 International Preliminary Examination Report on International Application No. PCT/CA00/00873, dated Oct. 26, 2001.
 European Communication pursuant to Article 94(3) on European Patent Application No. 04078261.7, dated Feb. 26, 2010.
 European Communication pursuant to Article 94(3) on European Patent Application No. 04078261.7, dated Apr. 24, 2012.
 Makita BCL180 User Manual.
 Makita 4071 Handy Vac II Cordless Cleaner.
 Handbook of Air Pollution Prevention and Control, pp. 397-404, 2002.
 The Office Action received in connection to the related Chinese Patent Application No. 00813438.3 dated Jul. 11, 2003.
 The Office Action received in connection to the corresponding U.S. Appl. No. 12/720,901 dated Jun. 10, 2011.
 The Office Action Received in connection to the Ccorresponding Chinese Patent Application No. 200880126486.6 dated Mar. 23, 2012.
 Supplementary European Search Report, dated Jun. 16, 2009, as received on the corresponding EP Application No. 07719394.4.
 International Preliminary Report on International Application No. PCY/CA2007/000380, dated Jul. 24, 2007.

(56)



References Cited

OTHER PUBLICATIONS

Office Action, issued in U.S. Appl. No. 12/720,901, dated Nov. 26, 2010.

International Search Report and Written Opinion received in connection to International Patent Application No. PCT/CA2014/00133, dated May 26, 2014.

* cited by examiner






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 22A




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 27A




Fig. 28




Fig. 29

SURFACE CLEANING APPARATUS

CROSS-REFERENCES TO RELATED APPLICATIONS

This application claims the benefit under 35 USC 120 as:
 (a) a continuation-in-part of U.S. patent application Ser. No. 14/822,211, which was filed on Aug. 10, 2015 and which itself claims priority from U.S. Provisional Patent Application 62/093,189 which was filed on Dec. 17, 2014;
 (b) as continuation-in-part of U.S. patent application Ser. No. 14/875,381, which was filed on Oct. 5, 2015 and which itself is continuation of U.S. patent application Ser. No. 13/782,217 which was filed on Mar. 1, 2013 and which issued as U.S. Pat. No. 9,192,269 on Nov. 24, 2015, which itself is a continuation-in-part of U.S. patent application Ser. No. 13/720,754 which was filed on Dec. 19, 2012 and which issued as U.S. Pat. No. 8,752,239 on May 2, 2013, which itself is a divisional application of U.S. patent application Ser. No. 11/954,331 which was filed on Dec. 12, 2007 which issued as U.S. Pat. No. 8,359,705 on Jan. 29, 2013, which itself claims priority from U.S. Provisional Patent applications 60/870,175 (filed on Dec. 15, 2006), and 60/884,767 (filed on Jan. 12, 2007), all of which are incorporated herein by reference in their entirety.

FIELD

This specification relates to a surface cleaning apparatus comprising a base with a removable portable surface cleaning unit such as a pod or other hand carryable surface cleaning apparatus wherein the portable surface cleaning apparatus is usable when mounted on the base or when removed therefrom.

INTRODUCTION

The following is not an admission that anything discussed below is part of the prior art or part of the common general knowledge of a person skilled in the art.

Various types of surface cleaning apparatuses are known in the art. Such surface cleaning apparatuses include vacuum cleaners, including upright vacuum cleaners, hand carryable vacuum cleaners, canister type vacuum cleaners, and Shop-Vac™ type vacuum cleaners. Some such vacuum cleaners are provided with wheels. For example, typical upright vacuum cleaners are provided with a surface cleaning head that includes wheels mounted to a bottom surface thereof. Upright vacuum cleaners are easy for a consumer to use since the consumer does not have to carry the vacuum cleaner but merely push it over a surface. However, depending on the size of the surface cleaning head, an upright vacuum cleaner may not be useable in smaller or crowded areas. Canister vacuum cleaners have a flexibly hose extending between a surface cleaning head and the canister body, thereby improving mobility of the cleaning head. However, consumers must separately move a canister body, which can add an extra step during the cleaning process.

SUMMARY

This summary is intended to introduce the reader to the more detailed description that follows and not to limit or define any claimed or as yet unclaimed invention. One or more inventions may reside in any combination or sub-combination of the elements or process steps disclosed in any part of this document including its claims and figures.

According to one broad aspect of this invention, a surface cleaning apparatus comprises a portable cleaning unit, which may be carried by hand or a shoulder strap such as a pod or handvac (hand vacuum cleaner), which is removably mounted on an upright section that is moveably mounted to a surface cleaning head between a storage position and a reclined in use position. The upright section may be an up flow duct or conduit which is rigid and suitable to support the pod or handvac. The portable cleaning unit may be provided with a suction motor (a portable cleaning unit suction motor) and an energy storage member (such as one or more battery). Accordingly, the suction motor of the portable cleaning unit may be operable on DC current. However, in accordance with this embodiment, the surface cleaning head or the upright section, and preferably the surface cleaning head, may include a second or upstream suction motor (e.g. an AC powered suction motor). Accordingly, when the portable cleaning unit is provided on the upright section and the surface cleaning head and/or the upright section is connected to a source of current, the upstream suction motor may be operated, e.g. on AC current, and used to cause air to travel through an airflow path (e.g., push the air in the case of a dirty air motor) to the air treatment member in the portable cleaning unit. An advantage of this design is that the upstream suction motor may provide more air watts than a smaller motor provided in the portable cleaning unit so as to produce a higher airflow and therefore increase cleanability when the portable cleaning unit is provided on the upright section. Alternately, or in addition, the upstream suction motor, when combined with the portable cleaning unit suction motor, may provide more air flow and air watts than the portable cleaning unit suction motor alone and therefore provide increased cleanability. However, when the portable cleaning unit is removed from the upright section, a smaller and lighter suction motor is utilized. While the velocity of the airflow through the portable cleaning unit when removed from the upright section may be decreased, the reduced weight of the suction motor may be beneficial. In addition, a smaller airflow path may be provided when the portable cleaning unit is removed from the upright section, and, accordingly, a smaller AC or DC power suction motor may provide substantially similar airflow in the hand carryable mode.

The portable cleaning unit may comprise at least one air treatment member and a suction motor. The air treatment member may be a cyclonic separation stage, a swirl chamber, a filter bag or any other means known in the vacuum cleaner arts. Accordingly, the portable cleaning unit is useable, e.g., as a vacuum cleaner or the like, when removed from the base. The cyclonic separation stage comprises a cyclone chamber and a material collection chamber. The portable cleaning unit is configured such that the material collection chamber is removable for emptying when the portable cleaning unit is mounted on the base. For example, the material collection chamber may be removed by itself when the portable cleaning unit is mounted on the base. Alternately, the material collection chamber and the cyclone chamber may be removable as a unit (e.g. a cyclone bin assembly). It will be appreciated that the material collection chamber, either by itself or in conjunction with the cyclone chamber and possibly other elements, may be removable from the portable cleaning unit when the portable cleaning unit has been removed from the base. An advantage of this design is that the usability of the surface cleaning apparatus is increased. In particular, when it is needed to empty the dirt collection chamber, all that is needed is to remove the dirt collection chamber either by itself, or, for example, together

with the cyclone chamber for emptying. Accordingly, a user did not carry the weight of the motor when the user is emptying the dirt collection chamber.

Preferably, in accordance with this embodiment, the dirt collection chamber and, optionally, the cyclone chamber may be provided on an upper portion of the portable cleaning unit so as to be removable upwardly therefrom.

It will be appreciated by a skilled person in the art that any of the features of the configuration of a portable cleaning unit to permit a dirt collection chamber to be removed from the portable cleaning unit when the portable cleaning unit is mounted on the base as discussed herein may not be utilized with dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with another embodiment, the portable cleaning unit may be provided with a pod hose which is removable with the portable cleaning unit from the base. The pod hose may have a smaller diameter and, accordingly, may be used only when the portable cleaning unit has been removed from the base. Accordingly, when the portable cleaning unit is on a base, the pod hose does not form part of the fluid flow path. Accordingly, the smaller diameter of the pod hose does not restrict the airflow path when the portable cleaning unit is placed on a base. An advantage of this design is that the portable cleaning unit may carry a longer hose without increasing the volume taken by the pod hose. In addition, the pod hose, being a smaller diameter, may be more flexible and enhance the usability of the portable cleaning unit in a hand carryable mode. For example, the pod hose may have a greater stretch ratio, for example, of 4:1 to 7:1 or more.

In accordance with this embodiment, a valve may be provided on the portable cleaning unit whereby the pod hose is not in airflow communication with the suction motor when the portable cleaning unit is mounted on the base. However, when the portable cleaning unit is removed from the base, the valve may be actuated (e.g. automatically upon removal of the portable cleaning unit from the base, manually by the user or automatically when the hose is deployed for use) such that pod hose form part of the air flow path.

It will be appreciated by a person skilled in the art that any of the features of the pod hose which are discussed herein may not be utilized with the dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with another embodiment, the portable cleaning unit may be operable by AC power supplied to the base when the portable cleaning unit is mounted on the base and may be operable on DC power when the portable cleaning unit is removed from the base. Accordingly, the portable cleaning unit may include an energy storage member (e.g. one or more batteries) which may power the suction motor when the portable cleaning unit is removed from the base. Accordingly, the suction motor may be operable on DC current. When the pod is mounted on the base, and the base is connected to a source of current by an electrical cord, then the suction motor may be in electrical communication with the base so as to be powered by AC current supplied through the electrical cord. For example, the suction motor could have dual winding so as to be operable on both AC and DC current. Alternately, the base may include a power supply to convert the AC current to DC current which is then supplied to the suction motor when the portable cleaning unit is placed on the base. For example, the power supply may comprise an inverter.

In this particular embodiment, it will be appreciated that the batteries in the portable cleaning unit may be charged while the portable cleaning unit is mounted on the base and the base is plugged into an electrical outlet.

In a further alternate embodiment, instead of utilizing electricity from an electrical outlet, the base may include a fuel cell or an alcohol powered internal or external combustion engine. In such an embodiment, the base may produce AC current or DC current, which is then supplied to the suction motor when the portable cleaning unit is mounted on the base and actuated.

It will be appreciated by a person skilled in the art that any of the features of a portable cleaning unit which is operable on AC and DC current as disclosed herein may not be utilized with the dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with the further embodiment, the portable cleaning unit may comprise both an energy storage member and a power supply. Accordingly, when the portable cleaning unit is connected to a power source (e.g. a cord extends from the portable cleaning unit to an electrical outlet), AC power may be supplied to the power supply (e.g. an inverter) to convert the AC current to DC which is then utilized to power the suction motor. When a user is unable to or does not want to plug the portable cleaning unit into a wall outlet, the portable cleaning unit may be powered by the energy storage member (e.g. batteries), which provide DC current to a suction motor. Accordingly, the portable cleaning unit may be powered by both AC current from a wall outlet and DC current supplied by batteries as may be desired. In a further alternate embodiment, the suction motor may be provided with two windings. In such a case, the power supply is not required and the suction motor may be powered by both DC current from the batteries and AC current from a wall outlet.

It will be appreciated by a person skilled in the art that any of the features of a pod operable with both AC and DC current as discussed herein may not be utilized with dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In one embodiment, there is provided a surface cleaning apparatus comprising:

- (a) a surface cleaning head having a first dirty fluid inlet;
- (b) an upright section moveably mounted to the surface cleaning head between an storage position and a reclined in use position;
- (c) a portable cleaning unit removably mounted to the upright section and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor;
- (d) a fluid flow path extending from the first dirty fluid inlet to the portable cleaning unit; and,
- (e) an upstream suction motor provided on one of the surface cleaning head and the upright section,

wherein the upstream suction motor is operable to provide motive power to move fluid through the fluid flow path to the portable cleaning unit when the surface cleaning apparatus is switched on and when the portable cleaning unit is mounted to the upright section, and

wherein the portable cleaning unit suction motor is operable to provide motive power to move fluid through the portable cleaning unit when the portable cleaning unit is switched on and when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or be connectable to a power cord and the portable cleaning unit may be

5

powered solely by the first energy storage member when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or be connectable to a power cord, the first energy storage member comprises one or more batteries and the one or more batteries may be charged when the portable cleaning unit is mounted on the upright section.

In some embodiments, the portable cleaning unit suction motor may not be used to provide motive power to move fluid through the fluid flow path when the surface cleaning apparatus is switched on and when the portable cleaning unit is mounted on the upright section.

In some embodiments, the upstream suction motor may be in the fluid flow path and is a dirty air motor.

In some embodiments, the surface cleaning apparatus may further comprise a downstream fluid flow path extending from an inlet of the portable cleaning unit to a clean air outlet and the portable cleaning unit suction motor may be in the downstream fluid flow path.

In some embodiments, the portable cleaning unit may further comprise or be connectable to a power cord.

In some embodiments, the power cord may provide power to the portable cleaning unit suction motor and provide power to the upstream suction motor.

In some embodiments, one of the surface cleaning head and the upright section may further comprise a second energy storage member.

In some embodiments, the second energy storage member may charge the first energy storage member when the portable cleaning unit is mounted on the upright section.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power and the upstream suction motor may be operable on AC power.

In some embodiments, the upright section may be an up flow duct.

In another embodiment, there is provided a surface cleaning apparatus comprising:

- (a) a surface cleaning head having a first dirty fluid inlet;
- (b) an upright section moveably mounted to the surface cleaning head between an storage position and a reclined in use position;
- (c) a portable cleaning unit removably mounted to the upright section and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor; and,
- (d) a fluid flow path extending from the first dirty fluid inlet to the portable cleaning unit,

wherein at least one of the surface cleaning head, the upright section and the portable cleaning unit is connectable to an external source of power, the portable cleaning unit suction motor is operable on power provided by the first energy storage member when removed from the upright section and is operable on power provided by the external source of power when mounted to the upright section.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or be connectable to a power cord and the portable cleaning unit may be powered solely by the first energy storage member when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or be connectable to a power cord, the first energy storage member comprises one or more batteries and the one or more

6

batteries may be charged when the portable cleaning unit is mounted on the upright section.

In some embodiments, the upright section may be an up flow duct.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power and the upstream suction motor may be operable on AC power.

In some embodiments, the portable cleaning unit suction motor may be a dirty air motor and the upstream suction motor may be a clean air motor.

In some embodiments, the portable cleaning unit may further comprise or be connectable to a power cord and the portable cleaning unit suction motor may also be operable on power provided by the external source of power when removed from to the upright section.

In another embodiment, there is provided a surface cleaning apparatus comprising

- (a) a wheeled base comprising an AC suction motor;
- (b) a portable cleaning unit removably mounted on the wheeled base and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor that is operable on DC power; and,

- (c) a fluid flow path extending from a first dirty fluid inlet to a clean air outlet of the surface cleaning apparatus, wherein the AC suction motor provides motive power to move fluid through the fluid flow path when the surface cleaning unit is switched on and when the portable cleaning unit is mounted on the wheeled base, and wherein the portable cleaning unit suction motor provides motive power to move fluid through the fluid flow path when the portable cleaning unit is switched on and when the portable cleaning unit is removed from the wheeled base

In some embodiments, the wheeled base may further comprise or is connectable to a power cord and the portable cleaning unit is powered solely by the first energy storage member when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the first energy storage member comprises batteries and the batteries are charged when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the suction motor in the portable cleaning unit may not be used to provide motive power to move fluid through the fluid flow path when the surface cleaning unit is switched on and when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the fluid flow path may comprise an upstream portion that extends from the first dirty fluid inlet to the portable cleaning unit and the AC suction motor is in the fluid flow path.

In some embodiments, the fluid flow path may comprise a downstream fluid flow path extending through the portable cleaning unit to the clean air outlet and the portable cleaning unit suction motor is in the downstream fluid flow path.

In some embodiments, the portable cleaning unit may comprise a flexible hose having a second dirty fluid inlet and the flexible hose is part of the downstream fluid flow path when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the flexible hose may be an electrified flexible hose.

In some embodiments, the wheeled base may further comprise a second energy storage member.

In some embodiments, the second energy storage member may charge the first energy storage member when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the portable cleaning unit suction motor may be a DC motor.

In one embodiment, there is provided a surface cleaning apparatus comprising

- (a) a wheeled based connectable to a source of current;
- (b) a portable cleaning unit removably mounted on the wheeled base and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor that is operable on DC power; and,
- (c) a fluid flow path extending from a first dirty fluid inlet to a clean air outlet of the surface cleaning apparatus, wherein the portable cleaning unit suction motor is operable on DC power when removed from the wheeled base and is operable on power provided by the wheeled base when mounted on the wheeled base.

In some embodiments, the portable cleaning unit suction motor may be a DC motor.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord and the portable cleaning unit is powered solely by the first energy storage member when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the first energy storage member comprises batteries and the batteries are charged when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the wheeled base further comprises a circuit that receives AC current and outputs DC current and the portable cleaning unit is powered the DC current when the portable cleaning unit is mounted on the wheeled base.

In some embodiments the portable cleaning unit suction motor may operate at a first power level when removed from the wheeled base and at a second power level when is mounted on the wheeled base.

In some embodiments the first power level may be less than the second power.

In accordance with another aspect, a surface cleaning apparatus, preferably a canister or Shop-Vac™ style vacuum cleaner is provided which comprises a portable cleaning unit and a wheeled base. Preferably, the cleaning unit is removably mounted to the wheeled base. Alternately, or in addition, the wheeled base has wheels mounted outward of the wheeled base, and which are preferably of a larger diameter (e.g., 1-3 inches in diameter, preferably 1.5-2.5 inches in diameter).

According to this aspect, the surface cleaning apparatus may comprise a member having a dirty fluid inlet. A fluid flow path extends from the dirty fluid inlet to a clean air outlet of the surface cleaning apparatus. The surface cleaning apparatus further comprises a wheeled based. A portable cleaning unit is removably mounted on the wheeled base and comprising at least one cyclonic separation stage and a suction motor positioned in the fluid flow path.

Embodiments in accordance with this broad aspect may be advantageous because the surface cleaning apparatus may have increased maneuverability. That is, the surface cleaning apparatus may be used as a wheel mounted surface cleaning apparatus when convenient for a user since the user need not carry the surface cleaning apparatus, or as a hand or strap

carriable surface cleaning apparatus, such as when a stairs or a smaller or crowded area is to be cleaned, according to the user's preference.

In some embodiments, the at least one cyclonic separation stage may comprise a cyclone chamber having at least one material outlet, a divider plate associated with the material outlet and an associated material collection chamber in flow communication with the material outlet.

In some embodiments, the material collection chamber may be positioned below the material outlet. In a further embodiment, the divider plate may be positioned in the material outlet.

In some embodiments, the material collection chamber may be moveable relative to the cyclone chamber. In a further embodiment the material collection chamber may be removable from the at least one cyclone chamber.

In some embodiments, the material collection chamber may have a portion that is openable. In a further embodiment, the portion that is openable may be a bottom wall. Such embodiments may be advantageous because the wheeled base may prevent accidental opening of the material collection chamber.

In some embodiments, the suction motor may be positioned laterally spaced from the at least one cyclonic separation stage. Accordingly, the surface cleaning apparatus may have a relatively wide stance and low center of mass, and therefore may have increased stability.

In some embodiments, the cleaning unit has a front end having the dirty fluid inlet and the front end of the cleaning unit is positioned at a front end of the wheeled base and the suction motor is positioned rearward of the at least one cyclonic separation stage.

In some embodiments, the wheeled base may have a length greater than its width. In further embodiments, the wheeled base may be generally polygonal, and preferably generally triangular in shape. Such embodiments may be advantageous because the surface cleaning apparatus may have both increased maneuverability and increased stability.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels, the rear wheels may have a larger diameter than the at least one front wheel and the at least one front wheel may be steerable. Such embodiments may be advantageous because the larger rear wheels may provide the wheeled base with increased stability, and the steerable front wheel may provide the wheeled base with increased maneuverability. Alternately, the front wheels may have a larger diameter or essentially the same diameter as the rear wheels.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels and the rear wheels may have a larger diameter than the at least one front wheel.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels and the rear wheels may have a smaller diameter than the at least one front wheel.

In some embodiments, the at least one front wheel may be steerable.

In some embodiments, the wheeled base may have rear wheels that are positioned outwardly of an area occupied by the cleaning unit when the cleaning unit is mounted on the wheeled base. Alternately, or in addition, the wheeled base may have front wheels that are positioned outwardly of an area occupied by the cleaning unit when the cleaning unit is mounted on the wheeled base. Such embodiments may be advantageous because the wheeled base may have a relatively wide stance, thereby providing greater stability to the

surface cleaning apparatus. Additionally, the surface cleaning apparatus may be relatively close to the ground, and may therefore have a lower center of mass and increased stability.

In some embodiments, the cleaning unit may have a front end having a fluid inlet downstream from the dirty fluid inlet and the front end of the cleaning unit is positioned at a front end of the wheeled base.

In some embodiments, the cleaning unit may be lockably receivable on the wheeled base.

In some embodiments, the wheeled base may have at least one front wheel having a diameter of 1 to 3 inches and at least two rear wheels having a diameter of 1 to 3 inches.

In some embodiments, the cleaning unit may have a carry handle and/or a shoulder strap.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels, and the cleaning unit is receivable on an open platform.

In some embodiments, the wheeled base may have an absence of operating components.

In accordance with another aspect, a surface cleaning apparatus is operable using an on board storage member in a first mode of operation and may operable using an external power source (e.g., AC power from a wall outlet) in another mode of operation. The first mode may be used when a portable cleaning unit, such as a hand vacuum cleaner, is removed from the remainder of the surface cleaning apparatus.

In accordance with this aspect, there is provided a surface cleaning apparatus comprising:

- (a) a surface cleaning head having a first dirty fluid inlet;
- (b) an upright section moveably mounted to the surface cleaning head between a storage position and a reclined in use position;
- (c) a portable cleaning unit removably mounted to the upright section and comprising at least one air treatment member, a first energy storage member and a portable cleaning unit suction motor;
- a fluid flow path extending from the first dirty fluid inlet to the portable cleaning unit; and,
- (d) an upstream suction motor provided on one of the surface cleaning head and the upright section,

wherein the upstream suction motor is operable to provide motive power to move fluid through the fluid flow path to the portable cleaning unit when the surface cleaning apparatus is switched on and when the portable cleaning unit is mounted to the upright section, and

wherein the portable cleaning unit suction motor is operable to provide motive power to move fluid through the portable cleaning unit when the portable cleaning unit is switched on and when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or may be connectable to a power cord and the portable cleaning unit may be powered solely by the first energy storage member when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or may be connectable to a power cord, the first energy storage member may comprise one or more batteries and the one or more batteries may be charged when the portable cleaning unit is mounted on the upright section.

In some embodiments, the portable cleaning unit suction motor may not be used to provide motive power to move fluid through the fluid flow path when the surface cleaning

apparatus is switched on and when the portable cleaning unit is mounted on the upright section.

In some embodiments, the upstream suction motor may be in the fluid flow path and may be a dirty air motor.

In some embodiments, the surface cleaning apparatus may further comprise a downstream fluid flow path extending from an inlet of the portable cleaning unit to a clean air outlet and the portable cleaning unit suction motor may be in the downstream fluid flow path.

In some embodiments, the portable cleaning unit may further comprise or may be connectable to a power cord.

In some embodiments, the power cord may provide power to the portable cleaning unit suction motor and may provide power to the upstream suction motor.

In some embodiments, one of the surface cleaning head and the upright section may further comprise a second energy storage member.

In some embodiments, the second energy storage member may charge the first energy storage member when the portable cleaning unit is mounted on the upright section.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power and the upstream suction motor may be operable on AC power.

In some embodiments, the upright section may comprise an up flow duct and the portable cleaning unit may be a hand vacuum cleaner.

In accordance with this aspect, there is also provided a surface cleaning apparatus comprising:

- (a) a surface cleaning head having a first dirty fluid inlet;
- (b) an upright section moveably mounted to the surface cleaning head between an storage position and a reclined in use position;
- (c) a portable cleaning unit removably mounted to the upright section and comprising at least one air treatment member, a first energy storage member and a portable cleaning unit suction motor; and,
- (d) a fluid flow path extending from the first dirty fluid inlet to the portable cleaning unit,

wherein at least one of the surface cleaning head, the upright section and the portable cleaning unit is connectable to an external source of power, the portable cleaning unit suction motor is operable on power provided by the first energy storage member when removed from the upright section and is operable on power provided by the external source of power when mounted to the upright section.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or may be connectable to a power cord and the portable cleaning unit may be powered solely by the first energy storage member when the portable cleaning unit is removed from the upright section.

In some embodiments, one of the surface cleaning head and the upright section may further comprise or may be connectable to a power cord, the first energy storage member comprises one or more battery and the one or more battery may be charged when the portable cleaning unit is mounted on the upright section.

In some embodiments, the upright section may comprise an up flow duct and the portable cleaning unit is a hand vacuum cleaner.

In some embodiments, the portable cleaning unit suction motor may be operable on DC power and the upstream suction motor may be operable on AC power.

11

In some embodiments, the portable cleaning unit suction motor may be a dirty air motor and the upstream suction motor may be a clean air motor.

In some embodiments, the portable cleaning unit may further comprise or may be connectable to a power cord and the portable cleaning unit suction motor may be also operable on power provided by the external source of power when removed from to the upright section.

It will be appreciated by a person skilled in the art that a surface cleaning apparatus may embody any one or more of the features contained herein and that the features may be used in any particular combination or sub-combination.

DRAWINGS

The drawings included herewith are for illustrating various examples of articles, methods, and apparatuses of the teaching of the present specification and are not intended to limit the scope of what is taught in any way.

In the drawings:

FIG. 1 is a perspective view of an embodiment of a surface cleaning apparatus of the present invention;

FIG. 2 is a front view of the embodiment of FIG. 1;

FIG. 3 is a side view of the embodiment of FIG. 1;

FIG. 4 is a top view of the embodiment of FIG. 1;

FIG. 5 is a perspective view of the embodiment of FIG. 1, showing a surface cleaning unit removed from a wheeled base;

FIG. 6 is a side view of the embodiment of FIG. 1, showing a surface cleaning unit removed from a wheeled base;

FIGS. 7-9 are cross-sections taken along line 7-7 in FIG. 1, showing alternate configurations of a cleaning unit;

FIG. 10 is a perspective illustration of an alternate embodiment of a surface cleaning apparatus of the present invention, showing a lid in an open position;

FIG. 11 is a perspective view of another embodiment of a surface cleaning apparatus;

FIG. 12 is another perspective view of the surface cleaning apparatus of FIG. 11;

FIG. 13 is a perspective view of the surface cleaning apparatus of FIG. 11 with a surface cleaning unit detached;

FIG. 14 is another perspective view of the surface cleaning apparatus of FIG. 11 with a surface cleaning unit detached;

FIG. 15 is a schematic representation of another embodiment of a surface cleaning apparatus;

FIG. 16 is a schematic representation of the surface cleaning apparatus of FIG. 15 with a surface cleaning unit detached;

FIG. 17 is a schematic representation of another embodiment of a surface cleaning apparatus;

FIG. 18 is a perspective view of another embodiment of a surface cleaning apparatus;

FIG. 19 is another perspective view of the surface cleaning apparatus of FIG. 18 with a cyclone bin assembly removed;

FIG. 20 is a perspective view of the surface cleaning apparatus of FIG. 18 with a surface cleaning unit detached and a cyclone bin assembly removed from the surface cleaning unit;

FIG. 21 is a bottom perspective view of the cyclone bin assembly of the surface cleaning apparatus of FIG. 18 in the open position;

FIG. 22 is a perspective view of a surface cleaning apparatus in accordance with another embodiment;

12

FIG. 22A is a perspective view of the surface cleaning apparatus of FIG. 22 in a cordless configuration;

FIG. 23 is a perspective view of the surface cleaning apparatus of FIG. 22, with a portable cleaning unit disconnected from an upright section;

FIG. 24 is a perspective view of the portable cleaning unit of FIG. 23 connected with a DC power cord;

FIG. 25 is a perspective view of the portable cleaning unit of FIG. 23 connected with a power supply and AC power cord;

FIG. 26 is a partial side view of the portable cleaning unit of FIG. 23 disconnected from a power cord;

FIG. 27 is a schematic drawing of an embodiment of the surface cleaning apparatus of FIG. 22 showing several alternative power cord connections;

FIG. 27A is a schematic drawing of another embodiment of the surface cleaning apparatus of FIG. 22 absent a power cord connections;

FIG. 28 is a schematic drawing of the surface cleaning head of FIG. 23; and,

FIG. 29 is a schematic drawing of an embodiment of the portable cleaning unit of FIG. 23.

DESCRIPTION OF VARIOUS EMBODIMENTS

Various apparatuses or processes will be described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may cover processes or apparatuses that differ from those described below. The claimed inventions are not limited to apparatuses or processes having all of the features of any one apparatus or process described below or to features common to multiple or all of the apparatuses described below. It is possible that an apparatus or process described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus or process described below that is not claimed in this document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicants, inventors or owners do not intend to abandon, disclaim or dedicate to the public any such invention by its disclosure in this document.

It will be appreciated that technologies discussed with respect to an embodiment using a wheeled base as exemplified in FIG. 1, 12 or 18 may be used individually or jointly in the embodiment utilizing a surface cleaning head with an upright section moveably mounted thereto as exemplified in FIG. 22 wherein a handheld vacuum cleaner is provided on the downstream end of a up flow conduit 689, which may be removed from the surface cleaning head and used as an above floor cleaning wand.

Portable Cleaning Unit Construction

The following is a description of portable cleaning unit constructions that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring to FIGS. 1-4, an embodiment of a surface cleaning apparatus 10 of the present invention is shown. Surface cleaning apparatus 10 may be a canister type vacuum cleaner, a Shop-Vac™ type vacuum cleaner, or another type of vacuum cleaner that may be mounted to a wheeled base. Surface cleaning apparatus 10 comprises a dirty fluid inlet 12, a clean air outlet 14, and a fluid flow path extending therebetween. A portable cleaning unit 16 is provided in the fluid flow path. Cleaning unit 16 comprises at least one cyclonic separation stage 18 for removing dirt from air, or for removing liquid from air or to pick up liquid.

13

Cleaning unit 16 further comprises a suction motor 20 for drawing fluid from the dirty fluid inlet 12 to the clean air outlet 14.

Dirty fluid inlet 12 is provided in a member 34. In the embodiment shown in FIGS. 1-6, member 34 is a hose. In the embodiment shown in FIGS. 7-10, member 34 is a nozzle. In other embodiment, member 34 may be, for example, a surface cleaning head. It will be appreciated that a flexible hose, a rigid wand or other attachment may be affixed or removably affixed to portable cleaning unit 16.

Referring to the exemplified embodiments of FIGS. 7-9, from dirty fluid inlet 12, fluid is directed to cleaning unit 16. Cleaning unit 16 may be of a variety of configurations. In the embodiment of FIGS. 7 and 8, cleaning unit 16 comprises a single cyclonic cleaning stage 18 preferably comprising a single cyclone housed in a first housing 44, and a filter assembly 38 and motor 20 housed in a second housing 46 adjacent the first housing. Accordingly, in this embodiment, the suction motor 20 is positioned laterally adjacent and laterally spaced from the cyclonic cleaning stage 18. In the embodiment of FIG. 9, cleaning unit 16 comprises first 18 and second 48 cleaning stages housed in first housing 44, and filter assembly 38 and motor 20 housed in second housing 46 laterally adjacent the first housing. In this embodiment, motor 20 is positioned laterally spaced from and laterally adjacent both of first 18 and second 48 cleaning stages. It will be appreciated that portable cleaning unit may utilize one or more cyclonic cleaning stages, each of which may comprise a single cyclone or a plurality of cyclones in parallel. In any embodiment, one or more additional cleaning stages may be used such as one or more filters.

For example, in the embodiments exemplified, cyclonic cleaning stage 18 includes a single cyclone chamber 22. Cyclone chamber 22 comprises a dirty air inlet 24, a separated or dirty material outlet 26, and a clean air outlet 28. A dirty or separated material collection chamber 30 is mounted below dirty material outlet 26, for collecting material removed from the air in cyclone chamber 22. In the embodiment shown, a divider plate 32 is associated with dirty material outlet 26. Divider plate 32 is positioned below the dirty material outlet 26, within the material collection chamber 30. It will be appreciated that a divider plate may be used any one or more of the cyclones and it may be of any configuration and located at any position known in the art. Alternately, a divider plate may not be used and the cyclone chambers may be of any design.

Material collection chamber 30 may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIGS. 7 and 8, material collection chamber 30 has a bottom 31 that is openable by pivoting about a pivot pin 33. In this embodiment, material collection chamber further comprises a latch 35, for locking bottom 31 in place, and a button 37 for releasing the latch. In other embodiments, material collection chamber 30 may be emptied in another manner. For example, material collection chamber 30 may be movable or removable from surface cleaning apparatus 10, such that it may be emptied, or may have another portion that opens. It may be removable from portable cleaning unit with the associated cyclone or cyclones as a sealed unit. See for example the embodiments of FIGS. 14 and 19.

In some embodiments, a filter or a screen may be associated with clean air outlet 28. For example, as shown in FIG. 8, a cylindrical housing 53 may be mounted on clean air outlet 28 and may have a plurality of openings 55 which are provided with a screen (e.g. a wire mesh). Any such screen or filter known in the art may be used.

14

In the embodiment of FIGS. 7 and 8, air is directed from cyclone chamber 22 out of clean air outlet 28, and into an airflow passage 36, which extends between first housing 44 and second housing 46. From airflow passage 36, air is directed through a filter assembly 38, which, in the embodiments exemplified, comprises a pre-motor foam filter 40, and a screen filter 42. From filter assembly 38, air is drawn past motor 20, and out of clean air outlet 14.

In the exemplified embodiment of FIG. 9, from cyclone chamber 22, air is directed out of clean air outlet 28 and into second cyclonic cleaning stage 48. Second cyclonic cleaning stage 48 comprises a plurality of second stage cyclones 50 in parallel. Each second stage cyclone comprises an inlet (not shown) in fluid communication with clean air outlet 28, and an outlet 52 in fluid communication with airflow passage 36. Each second stage cyclone comprises a cyclonic cleaning region 54, and a dirt collection region 56. From outlets 28, air is directed into airflow passage 36, and into filter assembly 38. From filter assembly 38, air is drawn past motor 20, and out of clean air outlet 14.

In other embodiments, cleaning unit 16 may be otherwise configured. For example, cleaning unit 16 may not comprise a filter assembly, or may comprise a plurality of filter assemblies. Additionally, cleaning unit 16 may comprise additional cleaning stages, which may be positioned laterally adjacent each other or above each other.

In the embodiments shown, the first 44 and second 46 housings are integrally molded. In other embodiments, the first 44 and second 46 housings may be separately manufactured and then secured together, such as by a common base or by gluing, welding or mechanically securing the two housings together. In some embodiments, first 44 and/or second 46 housing may be provided with an openable lid 45, as shown in FIG. 10. When a user opens lid 45, the user may have access to components housed in first 44 and/or second housing 46. For example, as shown in FIG. 10, lid 45 may be provided with a plurality of flanges 47, which are mounted on flanges 49 provided on housings 44 and/or 46. Flanges 47 are pivotally connected together by pivot pins 51. Accordingly, lid 45 may be pivoted from the closed position, as shown in FIGS. 1-9, to the opened position, as shown in FIG. 10.

Referring to FIG. 11, another embodiment of a surface cleaning apparatus 110 is shown. Surface cleaning apparatus 110 is generally similar to surface cleaning apparatus 10, and analogous features are identified using like reference characters indexed by 100.

Surface cleaning apparatus 110 comprises a dirty fluid inlet 112, a clean air outlet 114, and a fluid flow path extending therebetween. A portable cleaning unit 116 is provided in the fluid flow path. Cleaning unit 116 comprises at least one cyclonic separation stage 118 for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit 116 further comprises a suction motor 120 for drawing fluid from the dirty fluid inlet 112 to the clean air outlet 114. Dirty fluid inlet 112 is provided in a member 134, which in this embodiment is a surface cleaning head.

In this embodiment the cleaning unit 116 is mounted to a wheeled base 158. Wheeled base 158 comprises a plurality of wheels 160, and a cradle 162, which receives cleaning unit 116. The portable cleaning unit 116 can be operated while seated in the cradle 162 (FIGS. 11 and 12) and can be lifted out of the cradle 162 and used as a hand carryable apparatus (FIG. 13).

Referring to FIG. 14, in this embodiment the cyclone cleaning stage 118 includes a cyclone chamber 122. Cyclone chamber 122 comprises a dirty air inlet 124, a separated or

15

dirty material outlet **126**, and a clean air outlet **128** (FIG. **14**). A dirty or separated material collection chamber **130** is beside the cyclone chamber **122** and in communication with the dirty material outlet **126**, for collecting material removed from the air in cyclone chamber **122**.

Material collection chamber **130** may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIG. **14**, material collection chamber **130** has a bottom **131** that is openable by pivoting about a pivot pin **133**. In this embodiment, material collection chamber further comprises a latch **135**, for locking bottom **131** in place, and a button **137** for releasing the latch. In this embodiment the material collection chamber **130** may be movable or removable from surface cleaning apparatus **110** and from the portable cleaning unit **116**, such that it may be emptied, and is removable from portable cleaning unit **116** with the associated cyclone **118** or cyclones as a sealed unit.

Referring to FIGS. **18-21**, another embodiment of a surface cleaning apparatus **510** is shown. Apparatus **510** is generally similar to surface cleaning apparatus **10**, and analogous features are identified using like reference characters indexed by **500**.

Referring to FIG. **18**, surface cleaning apparatus **510** comprises a dirty fluid inlet **512**, a clean air outlet **514**, and a fluid flow path extending therebetween. A portable cleaning unit **516** is provided in the fluid flow path. Cleaning unit **516** comprises at least one cyclonic separation stage **518** (FIG. **21**) for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit **516** further comprises a suction motor **520** (FIG. **20**) for drawing fluid from the dirty fluid inlet **512** to the clean air outlet **514**. Dirty fluid inlet **512** is provided in a member **534**, which in this embodiment is a surface cleaning head.

In this embodiment the cleaning unit **516** is mounted to a wheeled base **558**. Wheeled base **558** comprises a plurality of wheels **560**, and a cradle **562** (FIG. **20**), which receives cleaning unit **516**. The portable cleaning unit **516** can be operated while seated in the cradle **562** (FIG. **18**) and can be lifted out of the cradle **562** and used as a hand carryable apparatus (FIG. **20**).

Referring to FIG. **21**, in this embodiment the cyclone cleaning stage **518** includes a cyclone chamber **522**. Cyclone chamber **522** comprises a dirty air inlet **524** (FIG. **19**), a separated or dirty material outlet **526**, and a clean air outlet **528**. A dirty or separated material collection chamber **530** is beside the cyclone chamber **522** and in communication with the dirty material outlet **526**, for collecting material removed from the air in cyclone chamber **522**.

Material collection chamber **530** may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIG. **21**, material collection chamber **530** has a bottom **531** that is openable by pivoting about a pivot pin **533**. In this embodiment, material collection chamber further comprises a latch **535**, for locking bottom **531** in place, and a button **537** for releasing the latch.

Referring to FIGS. **22-23**, and **27**, another embodiment of a surface cleaning apparatus **610** is shown. Apparatus **610** is generally similar to surface cleaning apparatus **10**, and analogous features are identified using like reference characters indexed by **600**. As shown, apparatus **610** may be a handheld surface cleaning apparatus ("handvac"), which is mountable to a base **658** comprising a surface cleaning head **634** and an upright section **689**, which may also function as an above floor cleaning wand.

16

Referring to FIG. **22**, surface cleaning apparatus **610** comprises a dirty fluid inlet **612**, a clean air outlet **614**, and a fluid flow path extending therebetween. A portable cleaning unit **616** is provided in the fluid flow path. Portable cleaning unit **616** comprises at least one cyclonic separation stage **618** (FIG. **27**) for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit **616** further comprises a portable cleaning unit suction motor **620** (FIG. **27**) for drawing fluid through the portable cleaning unit (e.g., from the dirty fluid inlet **612** to the clean air outlet **614**). Dirty fluid inlet **612** is provided in a member **634**, which in this embodiment is a surface cleaning head.

In this embodiment, the cleaning unit **616** is mounted to upright section **689** which is moveably mounted to surface cleaning head **634** between a storage position and a reclined in use position, and may use any connection member (e.g., a pivot) as is known in the art. Surface cleaning head **634** may be a wheeled base comprising a plurality of wheels **660** (e.g. two rear wheels **660**). Alternatively, surface cleaning head **634** may not include any wheels **660** (e.g. surface cleaning head **634** may slide over surfaces to be cleaned). Cleaning unit **616** may be connected to surface cleaning head **634** by an up flow conduit **689**. An up flow conduit **689** may be pivotally connected to surface cleaning head **634** by a pivot joint **635**. For example, up flow conduit **689** may be formed by or in pivot joint **635**, or up flow conduit **689** may comprise a rigid extension conduit (e.g. wand) extending upwardly from pivot joint **635** as shown. The portable cleaning unit **616** can be operated while mounted to the conduit **689** (e.g. as a stick vac or stair cleaner) and can be disconnected from air flow communication with surface cleaning head **634** and used as a hand carryable apparatus (e.g. handvac, see FIG. **23**) (e.g., it may be removed by itself from up flow conduit **689** (the upright section as exemplified) or it may be removed with up flow conduit **689**).

Referring to FIG. **27**, in this embodiment the cyclone cleaning stage **618** includes a cyclone chamber **622**. Cyclone chamber **622** comprises a dirty air inlet **624**, a separated or dirty material outlet **626**, and a clean air outlet **628**. A dirty or separated material collection chamber **630** is adjacent the cyclone chamber **622** and in communication with the dirty material outlet **626**, for collecting material removed from the air in cyclone chamber **622**. It will be appreciated that the cyclone cleaning stage may be of any design

Material collection chamber **630** may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIG. **22**, material collection chamber **630** has an openable bottom **631**.
Wheeled Base Construction

The following is a description of a wheeled base construction that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring again to FIGS. **1-4**, portable cleaning unit **16** is mounted to a wheeled base **58**. Wheeled base **58** comprises a plurality of wheels **60**, and a cradle **62**, which receives cleaning unit **16**.

In some embodiments, cleaning unit **16** may be permanently mounted to wheeled base **58**, for example via one or more bolts. In other embodiments, cleaning unit **16** may be removably mounted to wheeled base **58**. For example, a user may remove cleaning unit **16** from wheeled base in order to maneuver cleaning unit **16**, or to empty material collection chamber **30**. In such embodiments, cleaning unit **16** is portable. For example, as shown in FIGS. **5** and **6**, cleaning unit **16** may be removed from wheeled base **58** by lifting cleaning unit **16** off of wheeled base **58**.

17

In any embodiment, surface cleaning apparatus **10** may comprise a handle **64**, and/or a shoulder strap **65** (shown in FIG. **8**) for maneuvering cleaning unit **16** when it is removed from wheeled base **58**. In some embodiments, handle **64** may be integrally formed with one or both of first **44** and second **46** housings.

Surface cleaning apparatus **10** may further comprise a locking member (not shown), such that cleaning unit **16** may be lockably received on wheeled base **58**. The locking member may comprise any suitable locking member known in the art, such as, for example, a quick release latch, a friction or snap fit, a set screw, a tie down strap (e.g., a strap which may be wrapped around cleaning unit **16**) or the like. The lock may be actuatable by a foot pedal. Alternately wheeled base **58** may have side wall extending up around cradle **62** within which portable cleaning unit **16** is received. It will be appreciated that cradle **64** may be any member on which portable cleaning unit **16** may be received or secured, such as a flat base with or without side walls.

In the embodiments exemplified, wheeled base **58** comprises a front wheel **66**, and two rear wheels **68a**, **68b**. Accordingly, cradle **62** is a platform that is generally polygonal and, preferably, generally triangular in configuration. This configuration may provide increased maneuverability to surface cleaning apparatus **10**. In other embodiments, wheeled base **58** may comprise another number of wheels. For example, in some embodiments, wheeled base **58** may comprise two front wheels and two rear wheels. It will be appreciated that, as exemplified, housings **44**, **46** may be oriented on cradle **62** with the suction motor at the rearward end of portable cleaning unit **16** and the inlet to portable cleaning unit **16** at the forward end of the front housing. In alternate configurations, housings **44**, **46** may be positioned side by side. Further, if more than two housings **44**, **46** are provided, then the housings may be arranged linearly, in a triangular configuration or any other desired configuration.

In some embodiments, front wheel **66** is rotatably mounted about a vertical axis to cradle **62** (e.g., is a caster wheel), and rear wheels are non-rotatably mounted about a vertical axis. Accordingly, front wheel **66** may be steerable. In other embodiments, all of front wheel **66** and rear wheels **68** may be caster wheels, or may be non-rotatably mounted wheels.

In some embodiments, wheeled base **58** has a length greater than its width. That is, the distance L between front wheel **66** and axis **67** extending between rear wheels **68a**, **68b**, is greater than the distance W between rear wheels **68a**, **68b**, along axis **67**. In other embodiments, wheeled base **58** may have a width W greater than its length L , or may have width W equal to its length L .

In the embodiments shown, front wheel **66** is of a smaller diameter than rear wheels **68a**, **68b**. Alternately, rear wheels **68a**, **68b** may be smaller than front wheel **66**. Preferably, both the front and rear wheels are each relatively large. For example, in some embodiments, front wheel(s) may have a diameter of between about 0.5-4 inches, preferably 1-3 inches and more preferably 1.5-2.5 inches. In some embodiments, rear wheels may have a diameter of between about 0.5-4 inches, preferably 1-3 inches and more preferably 1.5-2.5 inches. In one particular embodiment, both front wheel(s) **66** and rear wheels **68a**, **68b** have a diameter in the same range. Such embodiments may be advantageous to provide surface cleaning apparatus **10** with increased maneuverability and with increased stability.

In the embodiments shown, wheeled base **58** is configured such that, when cleaning unit **16** is mounted on cradle **62**, rear wheels **58** are positioned outwardly of cleaning unit **16**.

18

That is, rear wheels **58** are separated by a distance W that is greater than the width W' of cleaning unit **16**. Such embodiments may provide surface cleaning apparatus **10** with a wider stance, and accordingly with increased stability. Additionally, because rear wheels **68** are positioned outwardly of cleaning unit **16**, rear wheels **68** may be provided with an increased diameter, as previously mentioned, without increasing the distance between cleaning unit **16** and a surface such as a floor. Accordingly, the center of mass of cleaning unit **16** may remain low, which further increases the stability of surface cleaning apparatus **10**.

In some embodiments, wheeled base **58** may comprise operating components of surface cleaning apparatus **10**, such as a suction motor (see FIG. **17**). For example, wheeled base may comprise a portion that is provided in the fluid flow path, and includes a filter assembly (not shown). In other embodiments, as exemplified, wheeled base **58** may not comprise any operating components (i.e. wheeled base has an absence of operating components).

In the embodiments shown, cleaning unit **16** is oriented such that dirty fluid inlet **12** is provided at a front end **70** of surface cleaning apparatus **10**, adjacent front wheel **66**, and suction motor **20** is provided at a rear end **72** of surface cleaning apparatus **10**, adjacent rear wheels **68**. In other embodiments, cleaning unit **16** may be otherwise oriented. For example, suction motor **20** may be provided at front end **70**, and dirty fluid inlet **12** may be provided at rear end **72**. Alternately, cleaning unit **16** may be oriented such that suction motor **20** and dirty fluid inlet **12** are equally spaced from front wheel **66** and rear wheels **68**. That is, cleaning unit **16** may be positioned substantially sideways in wheeled base **58**.

In some embodiments, portable cleaning unit **16** may be connected to a remote surface cleaning head by connected in air flow communication with the wheeled base, wherein the remote surface cleaning head may be connected or removably connected in air flow communication with the wheeled base. Accordingly, when portable cleaning unit **16** is placed on the wheeled base, it may be automatically connected in air flow communication with the wheeled base (see for example FIGS. **15**, **17** and **19**) or the user may have to connect portable cleaning unit **16** in air flow communication with the wheeled base, such as by connecting a hose of portable cleaning unit **16** in air flow communication with an air outlet of the wheeled base (see for example FIGS. **5** and **6**).

As exemplified in FIGS. **5** and **6**, wheeled base **62** may comprise a floor cleaning mount **82** coupled to cradle **62**. A first end **84** of mount **82** is configured for receiving member **34**, which, in the embodiments exemplified in FIGS. **1-6**, is a hose. A second end **86** of mount **82** is configured for receiving another member, for example a remote surface cleaning head that is preferably at the distal end of a wand and a flexible hose extends between the wand and mount **82** (not shown). It will be appreciated that portable cleaning unit **16** may be designed such that the inlet of the portable cleaning unit automatically is connected in flow communication with mount **82** when portable cleaning unit **16** is positioned on wheeled base **58**, such as by use of an inlet port aligned with first end **84** or a rigid pipe that is fittable thereon. Alternately, as exemplified, a flexible hose **34** that is manually insertable may be used. An advantage of this design is that the attachment member for a wand or the like is provided on the platform and not the portable cleaning unit. Therefore, the wand may be used to pull wheeled base **58** without risk of pulling portable cleaning unit **16** off of wheeled base **58**. Further, preferably the attachment point is

close to the floor, preferably at the level of cradle **62**, thereby lowering the point at which wheeled base **58** may be pulled and increasing the stability of wheeled base **58** when it is being pulled.

It will be appreciated that in the portable mode, a wand or flexible hose and wand, or other member known in the art may be attached to hose **34** or hose **34** may be removed and the wand or flexible hose and wand, or other member known in the art may be attached directly to the inlet to housing **44**.

In some embodiments, one or more accessories, such as cleaning brush **74** and wand extension **76** may be secured to the upper surface of lid **45**, such as by means of mounts **78**. Accordingly, extension **76** may be configured to function as a handle (e.g. central section **76** may be arcuate in shape or be spaced from lid **45**), to define an opening **80** between the upper surface of lid **34** such that extension **76** of brush **74** may be a carry handle **64** for the vacuum cleaner. Alternately, extension **76** may be configured to seat on handle **64** and permit handle **64** to be used when brush **74** is mounted on portable cleaning unit **16**. In other embodiments, one or more accessories may be provided in a recess in the lower surface of portable cleaning unit **16** or in an upper surface of wheeled base **58**.

Referring to FIGS. **22** and **28**, portable cleaning unit **616** is mountable to base **658**. base **658** comprises a surface cleaning head **634**, and an up flow conduit **689** to which cleaning unit **616** is mountable. As exemplified, cleaning unit **616** is removably mounted to base **658**. For example, a user may remove cleaning unit **616** from base **658** in order to use cleaning unit **616** as a handvac, or to empty material collection chamber **630**.

As shown, cleaning unit **616** may have a handle **664** for maneuvering cleaning unit **616** when it is connected to base **658** and when it is removed from base **658** (FIG. **23**). Surface cleaning apparatus **610** may further comprise a locking member **625**, such that cleaning unit **616** may be lockably mounted to base **658**.

Referring to FIGS. **27** and **28**, base **658** may comprise operating components of surface cleaning apparatus **610**, such as an upstream suction motor **620b**. Suction motor **620b** may be a dirty air suction motor that is positioned in the airflow path downstream of dirty fluid inlet **612** and upstream of clean air outlet **614**, such as upstream of up flow conduit **689**. In other embodiments (e.g., in the surface cleaning head or on the up flow conduit).

As exemplified in FIGS. **23** and **27**, portable cleaning unit **616** may include an inlet end **623**, which may be formed as a nozzle as shown. Inlet end **623** may be fluidly connected to a downstream end **690** of up flow conduit **689** in a suitable manner (including any suitable manner known in the art) for mounting portable cleaning unit **616** to base **658**.

Removable Dirt Chamber

The following is a description of a portable cleaning unit having a removable dirt chamber that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

As exemplified in FIG. **14**, the cyclone chamber **118** and material collection chamber **130** may be constructed as a one piece assembly and are referred to collectively as a cyclone bin assembly **188**. In accordance with this aspect, cyclone bin assembly **188** may be removed from the portable surface cleaning unit **116** when the portable surface cleaning unit **116** is seated on the base **158** (FIGS. **14** and **19**) and when the portable surface cleaning unit **116** is separated from the base **158** (FIG. **13**). This may allow a user to remove only

the cyclone bin assembly **188**, for example for emptying, regardless of whether the surface cleaning unit **116** is docked on the base **158**.

As exemplified in FIGS. **18-21**, the material collection chamber **530** may be movable or removable from surface cleaning apparatus **510** and from the portable cleaning unit **516**, such that it may be emptied, and is removable from portable cleaning unit **516** with the associated cyclone **518** or cyclones as a sealed unit.

In the illustrated embodiment, the cyclone chamber **518** and material collection chamber **530**, referred to collectively as a cyclone bin assembly **588**, can be removed from the portable surface cleaning unit **516** when the portable surface cleaning unit **516** is seated on the base **558** (FIG. **19**) and when the portable surface cleaning unit **516** is separated from the base **558** (FIG. **20**). This may allow a user to remove only the cyclone bin assembly **588**, for example for emptying, regardless of whether the surface cleaning unit **516** is docked on the base **558**.

Referring to FIG. **18**, in the illustrated embodiment, when the surface cleaning unit **516** is mounted on the base **558** the air flow path between the surface cleaning head **534** and the suction motor in the surface cleaning unit **516** includes a rigid conduit **589**, a flexible hose **590a**.

In this embodiment, the first hose **190a** is connected to the surface cleaning unit **516** and extends between a downstream end **592a** (with reference to the direction of airflow through the hose **590a**) that is connected to the surface cleaning unit **516** and the rigid conduit **589**. In this configuration, when the surface cleaning unit **516** is removed from the base **558** the hose **590a** comes with the surface cleaning unit **516** (FIG. **20**).

It will be appreciated that, in alternate embodiments, material collection chamber **130** may be a separate unit and may be removable without the cyclone chamber. Alternately, or in addition, material collection chamber **130** may be removed with the handle of the portable cleaning unit. An advantage of this design is that the handle of the portable cleaning unit may be useable to manipulate the material collection chamber **130** or cyclone bin assembly when removed for emptying.

Automatic Portable Cleaning Unit Hose Connection

The following is a description of automatically connecting a hose of the portable cleaning unit in air flow communication with the base when the portable cleaning unit is placed on the base that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring to FIG. **12**, in the illustrated embodiment, when the surface cleaning unit **116** is mounted on the base **158**, the air flow path between the remote surface cleaning head **134** and the suction motor in the surface cleaning unit **116** includes a rigid conduit or wand **189**, a first flexible hose **190a** and a second flexible hose **190b** (see also FIG. **14**) positioned downstream from the first hose **190a**.

The first hose **190a** extends from its upstream that is connected to rigid conduit **189** to its downstream end **192a** (with reference to the direction of airflow through the hose **190a**) that is connected to the base **158**. The first hose **190a** has a diameter **191a**. While the first hose **190a** may be removably connectable to the base **158**, first hose **109a** remains attached to the base **158** regardless of the position of the surface cleaning unit **116** (FIGS. **12** and **14**).

Referring to FIG. **13**, the second hose **190b** is attached to and is removable with the surface cleaning unit **116**. A downstream end **192b** of the hose **190b** is attached to the air inlet **124** of the cyclone chamber **118** and the upstream end

193b is removably connectable in air flow communication with the air outlet of the base 158 (e.g., opening 195 of coupling 194). When the surface cleaning unit 116 is removed from the base 158, the upstream or inlet end 193b of the hose 190b can be used as a second or auxiliary dirty air inlet for drawing fluid and debris into the air flow path. Optionally, auxiliary cleaning tools may be attached to the inlet end 193b of the hose 190b. In this configuration, the first hose 190a does not form part of the airflow path to the surface cleaning unit 116.

The second hose 190b is shown in a wrapped or storage position in FIG. 13 in which it is wrapped around part of the surface cleaning unit 116. When the surface cleaning unit 116 is in use as a portable cleaning unit the second hose 190b can be unwound and extended. Preferably, the second hose 190b is extensible to increase its cleaning range. The second hose 190b has a diameter 191b, which optionally may be smaller than diameter 191a. This may help reduce the overall size of the surface cleaning unit 116 and may help it nest on the base 158. However, it is preferred that they have the same or similar diameters so as to provide an air flow path that has a generally constant diameter. The hoses 190a and 190b may be generally similar. Alternatively, they may have different properties. For example, the first hose 190a may be non-extensible and relatively stiff (to allow a user to pull the hose 190a to advance the base 158 across the surface) and the second hose 190b may be extensible and less stiff.

Referring to FIG. 12, when the surface cleaning unit 116 is seated on the base 158, the inlet end 193b of the second hose 190b is connected in air flow communication with the downstream end 192a of the first hose 190a, using coupling 194, thereby re-establishing air flow communication between the cleaning head 134 and the surface cleaning unit 116.

Referring to FIG. 13, the coupling 194 may be any suitable connector, and in the example illustrated, is an elbow-type connector with a downstream opening 195 surrounded by a sealing face 196. The surface cleaning unit 116 may be configured such that the upstream end 193b of the second hose 190b is aligned with the opening 195 and seals against seal face 196 to establish the air flow path when the surface cleaning unit 116 is placed on base 158. Accordingly, sealing face 196 is sealed by the inlet end 193b automatically when the surface cleaning unit 116 is inserted vertically onto the base 158.

In order to provide a seal, one or both of base 158 and surface cleaning unit 116 may be configured to provide sufficient abutment therebetween so that an air tight seal is created. As exemplified in FIG. 13, the rear face of coupling 194 is angled and a mating angled surface may be provided on portable cleaning unit 116. Accordingly, when portable cleaning unit is placed on base 158, portable cleaning unit is urged rearwardly and the rear end of portable cleaning unit 116 may abut the rear wall of base 158 thereby pressing the upstream end 193b of the second hose 190b against the opening 195 and optionally compressing a gasket or the like to create an air tight seal.

If the cyclone bin assembly is removable, then the remaining body of portable cleaning unit 116 may also or alternately be angled to press the cyclone inlet 524 against opening 195 (see for example FIG. 19).

Valve to Switch Between Hoses

The following is a description of alternate air flow paths that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

In accordance with this aspect, the portable cleaning unit may incorporate a hose which is different to first hose 190a. For example, it may have a smaller diameter. Accordingly, it may be preferred not to use such a hose in the air flow path when portable cleaning unit 116 is mounted on the base since the smaller diameter hose would reduce air flow and increase the back pressure. However, the smaller diameter hose may be lighter and easier to use in a portable mode (i.e., when surface cleaning unit 116 is removed from base 158). In such a case, a valve may be provided to selectively connect the cyclone air inlet with the different hoses or air flow paths. The valve may be manually operable or automatically operable. For example, the valve may be actuated automatically when the surface cleaning unit 116 is removed from the base or when the smaller diameter hose is deployed from a storage position for use.

Accordingly, if second hose 190b has a smaller diameter into the air flow path when the surface cleaning unit 116 is docked, a user may optionally detach the downstream end 192b of the second hose 190a from the air inlet 124 (thereby removing the second hose 190b from the air flow circuit) and can reposition the downstream end 192a of the hose 190a to be connected directly to the inlet 124. Alternately, inlet 124 could be automatically connected in air flow communication with opening 195 when surface cleaning unit 116 is placed on base 158.

Optionally, instead requiring a user to reconfigure a hose, the surface cleaning apparatus may include a valve positioned in the air flow path that allows the air flow to be switched between the first and second hoses. In this configuration, both hoses can remain attached to their respective components, and the air flow path to the surface cleaning unit 116 can include either of the first and second hoses. Optionally, one of the hoses may be detachable and connectable to the other of the hoses, such that one large hose is created and forms the air flow path to the surface cleaning unit.

Referring to FIGS. 15 and 16, a schematic representation of another embodiment of a surface cleaning apparatus 210 is illustrated. Surface cleaning apparatus 210 is generally similar to apparatus 10, and analogous features are identified using like reference characters indexed by 200.

In this embodiment, the surface cleaning unit 216 includes a valve 297 provided in the air flow path, upstream from the air inlet of the cyclone chamber 218. The valve is connected to the downstream end 292b of the second hose 290b, and the valve 297 and second hose 290b are removable with the surface cleaning unit 216 (FIG. 16). When the surface cleaning unit 216 is seated on base 258, the valve can connect to coupling 294 automatically or manually. An actuating lever 298 allows a user to change to position of the valve 297 so that, when the surface cleaning unit 216 is docked, the first hose 290a is connected in air flow communication with the surface cleaning unit 216 and the second hose 290b is sealed (but remains attached and does not require re-configuration). Optionally, the valve 297 can be automatically actuated when the surface cleaning unit 216 is placed on or removed from the base 258 to adjust the air flow path accordingly.

Use of Dual Suction Motors

The following is a description of the use of dual suction motors that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Optionally, the base of the surface cleaning apparatus may include some operating components of the surface cleaning apparatus, including, for example a suction motor, the power

cord and a cord reel. Providing components in the base may help reduce the weight and/or overall size of the portable surface cleaning unit.

Referring to FIG. 17, a schematic representation of another embodiment of a surface cleaning apparatus **310** is shown. The surface cleaning apparatus **310** is generally similar to surface cleaning apparatus **10**, and analogous features are identified using like reference characters indexed by **300**.

In the illustrated embodiment, the surface cleaning apparatus **310** includes a base **358** and a surface cleaning unit **316** that can be mounted on the base **358** (as illustrated), and can be detached to be used separately from the base **358**.

The surface cleaning unit **316** includes a cyclone bin assembly **388** that has a cyclone chamber **318** and a dirt collection chamber **330**. The cyclone chamber **318** has an air inlet **324** and an air outlet **328**. A dirt outlet in the form of a slot **326** provides communication between the cyclone chamber **318** and the dirt collection chamber **330**.

A first suction motor **320a** is provided in the surface cleaning unit **316**. An air flow conduit **400** provides an air flow path between the air outlet of the pre-motor filter housing and the suction motor **320a**. Accordingly, a pre-motor filter **338** is provided in the air flow path between the air outlet **328** of the cyclone chamber **318** and the motor **320a**.

In the illustrated embodiment the electrical cord **401** is wound around a cord reel **402** that is provided in the base **358**. In addition, a second suction motor **320b** is provided in the base **358** and is in electrical communication with the power cord **401** such that the second suction motor **358** can be powered by an external power supply (e.g. a wall socket). A base conduit **403** provides air flow communication between the second suction motor **320b** and a port **404** on the upper surface of the base **358**.

When the surface cleaning unit **316** is mounted on the base **358**, a mating port **406** on the surface cleaning unit **316** may connect to and seal the port **404**. Preferably, a valve **407** (e.g. any suitable valve such as a two position valve and a ball valve) is provided, e.g., in the air flow path between the filter **338** and the motor **320a**. The valve **407** is also in air flow communication with the port **406**, and is operable to selectively connect either port **406** or conduit **400** in airflow communication with the cyclone bin assembly **388**. When conduit **400** is connected, suction motor **320a** may be used draw air through the surface cleaning unit **316** (and preferably motor **320b** is not). When port **406** is connected, suction motor **320b** may be used to draw air through the surface cleaning unit **316** (and preferably motor **320a** is not). Preferably, the valve **407** is configured (for example via a biasing member or linkage member) so that when the surface cleaning unit **316** is lifted off the base **358** the valve **407** automatically seals port **406** and connects conduit **400**.

It will be appreciated that valve may be actuatable by other means, such as a member that is drivingly connected to the valve and the member is operable as the surface cleaning unit is paced and or removed from base **358**. It will be appreciated that motor **320b** may be connected in air flow communication at an alternate location. For example, it could be downstream of motor **320a**. Alternately, it could be a dirty air motor and located upstream of cyclone chamber **318**.

Because the electrical cord **401** is provided in the base **358**, when the surface cleaning unit **316** is detached from the base **358**, it may no longer be connected to the external power source (e.g. wall socket). To provide power to the surface cleaning unit **316** when it is detached, the surface

cleaning unit **316** includes an on-board energy storage member, e.g., one or more batteries **405**. Alternatively, any other suitable energy storage member or power source can be used (fuel cell, combustion engine, solar cells, etc.). In the illustrated example, the batteries **405** provide DC power. In this configuration, when the surface cleaning unit **316** is detached from base **358**, the suction motor **320a** may operate using DC power, and may operate solely on the power supplied by batteries **405**.

Optionally, when the surface cleaning unit **316** is re-attached to the base **358**, power from the base **358** can be transferred to the surface cleaning unit **316**, for example via detachable electrical connector **408**. Preferably, if an electrical connector **408** is provided the power received from the base **358** can be used to charge the batteries **405** to help ensure the batteries **405** are charged when the surface cleaning unit **316** is removed.

Alternatively, there need not be an electrical connection between the base **358** and the surface cleaning unit **316**. In such a configuration the batteries **405** may be charged via an alternate power source, or may be replaced with fresh batteries as needed. For example, the surface cleaning unit **116** may be provided with its own power cord, or the power cord **401** may be removable from base **358** and may be plugged into surface cleaning unit **116**.

Optionally, the suction motor **320a** may be smaller and/or less powerful than the suction motor **320b**. Making the suction motor **320a** smaller and lighter than suction motor **320b** may help reduce the overall size and weight of the surface cleaning unit **316**. For example, the suction motor **320b** may be a 1000 watt motor, and the suction motor **320a** may be a 600 watt motor. Reducing the power consumption of the suction motor **320a** may also help prolong the amount of cleaning time that can be achieved using the batteries **405**, before they need to be replaced and/or recharged.

In the illustrated embodiment, because suction motor **320b** is in the base **358** with the electrical cord, it may be an AC motor that can run on AC power received from a wall socket. Motor **320a** may be operated on DC power supplied by the batteries **405**.

In this configuration, a user may be able to select which suction motor **320a** or **320b** is to be used when the surface cleaning unit **316** is docked. For example, if performing a small job or if it is desirable to keep the noise level low a user may activate the smaller suction motor **320a**. Alternatively, if performing a large job a user may select to use the suction motor **320b** by activating the motor **320b** and positioning the valve **407** as appropriate.

Dual Operational Mode for a Portable Surface Cleaning Unit

The following is a description of the use of a dual operational mode for a portable surface cleaning unit that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

In accordance with this aspect, a surface cleaning apparatus may have a single suction motor (e.g., a suction motor **320a** that is provided in the portable cleaning unit **616** which may be as shown in FIG. 23 or surface cleaning unit **116** shown in FIG. 13). which may be operable on current supplied by an on board energy storage member (e.g., batteries **405**) when removed from base **358** and may be operable on current supplied from base **358** when mounted thereon. Alternately, or in addition, the base may be provided with a suction motor **320b** and suction motor **320b** may also be operable by an on board energy storage member.

Accordingly, when removed from the base **358**, motor **320a** may be operable on DC current supplied from batteries

405. However, when mounted on the base 358 and electrical cord 401 is plugged into an electrical outlet, current may be supplied from base 358 to motor 320a. The current may be AC, in which case, motor 320a may be operable on both AC and DC current (e.g., it has dual windings) or the AC current may be converted to DC current (such as by providing a power supply in one or both of the base 358 and the surface cleaning unit 116).

Accordingly, for example, as shown in FIG. 17, an electrical connector 408 may be used to connect the portable cleaning unit 616 to the rest of the surface cleaning apparatus such as the base to thereby provide power to the suction motor 320a when the surface cleaning apparatus is docked on the base 358. When mounted on the base as exemplified in FIGS. 17 and 22, the suction motor 320a may be operable to also run on AC power or a power supply in or on the base. A converter module 409 may be provided to convert the incoming AC power to DC power. The converter module 409 may be provided in or on the base or in the portable cleaning unit 616. Optionally, the converter module 409 may be in the base 358 so that the connector 408 is with a DC connector.

It will be appreciated that the suction motor of the portable cleaning unit may be operable on different power levels. It may be operable on a first or higher power level when mounted to the base and operable on power supplied from the base (which may be AC or DC). It may be operable on a lower power level when removed from the base.

Reference is now made to FIGS. 22 and 27. In a first operating mode of surface cleaning apparatus 610, portable cleaning unit 616 is mounted to base 658, which includes removable up flow duct 689. As shown, a power cord 701 may be connected to base 658 for delivering power (e.g. AC or DC power) to base 658 for powering upstream suction motor 620b, for powering energy storage members 694b, or both. Suction motor 620b may be an AC suction motor, or a dual windings AC/DC suction motor. Alternatively, upstream suction motor 620b may be a DC suction motor. In this case, surface cleaning apparatus 610 may include a power supply 692 (FIG. 25) for converting the AC power from power cord 701 to DC power. The power supply 692 may be positioned inside base 658, or exterior to and connected to base 658 (e.g. by another power cable).

Alternatively or in addition, suction motor 620b may be powered cordlessly (i.e. while power cord 701 is disconnected from base 658) by, e.g., energy storage members 694b. For example, FIG. 22A illustrates an embodiment of surface cleaning apparatus 610 in a cordless mode of operation.

In this first operating mode, the upstream suction motor 620b may operate while cleaning unit suction motor 620 is turned off (i.e. unpowered). Alternatively, both suction motors 620 and 620b may be powered (i.e. turned on), and operated in series to develop enhanced suction. In this case, suction motors 620b and/or 620 may be powered by energy storage members 694b (e.g. cordlessly), or from the AC power delivered by power cord 701, or both. For example, portable cleaning unit 616 may be electrically connected to base 658 when mounted to base 658 (e.g. by suitable electrical wiring which may be part of up flow duct 689). Base 658 may transmit AC power (e.g. from power cord 701) or DC power (e.g. from energy storage members 694b) to portable cleaning unit 616. Similar to upstream suction motor 620b, the cleaning unit suction motor 620 may be an AC suction motor, a dual windings AC/DC suction motor, or a DC suction motor. If AC power is delivered to portable cleaning unit 616 and suction motor 620 is a DC suction

motor, then portable cleaning unit 616 may include a power supply 692 (FIG. 25) which may be positioned inside portable cleaning unit 616 or exterior to portable cleaning unit 616.

Still referring to the first operating mode, portable cleaning unit 616 and/or base 658 may include energy storage members 694 or 694b for powering one or both of suction motors 620 and 620b independently of or in addition to power from power cord 701. In this case, power from power cord 701 (optionally converted to DC power by a power supply) may charge energy storage members 694, 694b in portable cleaning unit 616, base 658, or both. For example, power from power cord 701 may power suction motor(s) 620 and/or 620a, while simultaneously charging energy storage members 694, 694b in portable cleaning unit 616, base 658, or both. This may help mitigate the possibility that energy storage members 694, 694b have insufficient charge when power cord 701 is disconnected (e.g. unplugged) from the wall outlet or disconnected (e.g. unplugged) from surface cleaning apparatus 610.

FIG. 27A exemplifies a further embodiment, in which surface cleaning unit 616 is not electrically connectable to an external source of power (e.g. is free of connectors for connection to a power cord). For example, energy storage members 694 may be removable from surface cleaning unit 616 for connection to an external source of power for charging (e.g. by inserting the portable cleaning unit 616 and/or energy storage member 694 in a charging dock).

In some embodiments portable cleaning unit 616 is itself not directly electrically connectable to an external source of power (e.g. it may not have a power cord and may not have a connector to which an external power cord may be connected). In such a case, energy storage member 694 may be charged when portable cleaning unit 616 is mounted to a base and/or by inserting the portable cleaning unit 616 and/or energy storage member 694 in a charging dock.

Still referring to the first operating mode and FIGS. 22 and 27, the power cord 701 may be connected to surface cleaning apparatus 610 at a location above base 658 (e.g. on up flow duct 689 proximate portable cleaning unit 616 and/or on portable cleaning unit 616). For example, power cord 701 may be electrically connected directly to base 658, and run upwardly on up flow duct 689 and may be secured to the exterior thereof such as by one or more mounting clips (obscured from view). This may help keep power cord 701 from dragging on the floor behind base 658 during use. Alternatively or in addition, up flow duct 689 may include a power connector 691 which mates with power cord connector 698 (obscured from view in FIG. 22, but may be similar to power cord connector 698 of FIG. 26). In this case, up flow duct 689 may include suitable electrical wiring for delivering the power from power cord 701 to base 658, portable cleaning unit 616, or both.

Still referring to FIGS. 22 and 27, surface cleaning apparatus 610 may be operable in a second cleaning mode, as an alternative to or in addition to the first cleaning mode. The second cleaning mode is similar to the first cleaning mode, except that power cord 701 is directly electrically connected to portable cleaning unit 616, and power may be transmitted from portable cleaning unit 616 to base 658 if base contains an electrically operable member such as a brush motor and/or a suction motor. As in the first cleaning mode, a power supply 692 (FIG. 25) may be positioned exterior to or inside of surface cleaning apparatus 610 (e.g. inside or exterior to base 658, portable cleaning unit 616, or both) for converting the AC power to DC power. Each of suction motors 620 and 620b may be AC, DC, or dual

windings AC/DC. Upstream suction motor **620b** may be powered exclusively of suction motor **620**, or both suction motors **620** and **620b** may be powered simultaneously. Energy storage members **694**, **694b** (if present) in base **658**, portable cleaning unit **616**, or both may be charged by the power from power cord **701**. It will be appreciated that the energy storage members may be charged while power cord **701** is connected to an AC outlet and the portable cleaning unit **616**.

The second cleaning mode may permit power from power cord **701** to supply power to portable cleaning unit **616** uninterrupted by disconnection of the portable cleaning unit **616** from base **658**. This may permit uninterrupted operation when transitioning between the second cleaning mode and an above-floor or handvac cleaning mode (or vice versa), especially where the portable cleaning unit **616** has no energy storage members **694**.

Still referring to FIGS. **22** and **27**, surface cleaning apparatus **610** may be operable in a third cleaning mode, as an alternative to or in addition to any of the first and second cleaning modes. The third cleaning mode is similar to the first cleaning mode, except that upstream suction motor **620b** is not powered or is not present. That is, power from power cord **701** is delivered to base **658**, and then transmitted to portable cleaning unit **616** to power suction motor **620**. As in the first cleaning mode, a power supply **692** (FIG. **25**) may be positioned exterior to or inside of surface cleaning apparatus **610** (e.g. inside or exterior to base **658**, portable cleaning unit **616**, or both) for converting the AC power to DC power. Suction motor **620** may be AC, DC, or dual windings AC/DC. Energy storage members **694**, **694b** (if present) in base **658**, portable cleaning unit **616**, or both may be charged by the power from power cord **701**.

Referring to FIGS. **23-25** and FIG. **29**, surface cleaning apparatus **610** may be operable in a fourth cleaning mode, as an alternative to or in addition to any of the first, second, and third cleaning modes. In the fourth cleaning mode, portable cleaning unit **616** is disconnected from base **658** and operable as a hand-held cleaning apparatus (e.g. handvac). As shown, power cord **701** may be connected to portable cleaning unit **616** for powering suction motor **620**. As in the first cleaning mode, suction motor **620** may be an AC suction motor, a dual windings AC/DC suction motor, or a DC suction motor. A power supply **692** may be positioned inside or exterior to portable cleaning unit **616** for converting AC power from power cord **701** to DC power. Alternatively, power cord **701** may include a DC power connector **702** (e.g. cigarette lighter connector) for directly delivering DC power to portable cleaning unit **616**. Energy storage members **694** (FIG. **29**) (if present) in portable cleaning unit **616** may be charged by the power from power cord **701**.

Referring to FIGS. **23**, **26**, and **29**, surface cleaning apparatus **610** may be operable in a fifth cleaning mode, as an alternative to or in addition to any of the first, second, third, and fourth cleaning modes. The fifth cleaning mode is similar to the fourth cleaning mode, except that power is not provided by power cord **701**. For example, power cord **701** may be disconnected from the external power source (e.g. disconnected from an AC wall outlet or 12V DC source), and/or power cord **701** may be disconnected from portable cleaning unit **616** (FIG. **26**). Instead, suction motor **620** is powered by energy storage members **694** in portable cleaning unit **616**.

It will be appreciated that certain features of the invention, which are, for clarity, described in the context of separate

embodiments or separate aspects, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment or aspect, may also be provided separately or in any suitable sub-combination.

What has been described above has been intended to be illustrative of the invention and non-limiting and it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

What is claimed is:

1. A surface cleaning apparatus comprising:

- a) a surface cleaning head having a first dirty fluid inlet;
- b) an upright section moveably mounted to the surface cleaning head between an storage position and a reclined in use position;
- c) a portable cleaning unit removably mounted to the upright section and comprising at least one air treatment member, a first energy storage member and a portable cleaning unit suction motor; and,
- d) a fluid flow path extending from the first dirty fluid inlet to the portable cleaning unit,

wherein at least one of the surface cleaning head, the upright section and the portable cleaning unit is connectable to an external source of power, the portable cleaning unit suction motor is operable on power provided by the first energy storage member when removed from the upright section and is operable on power provided by the external source of power when mounted to the upright section.

2. The surface cleaning apparatus of claim 1 wherein the portable cleaning unit suction motor is operable on DC power.

3. The surface cleaning apparatus of claim 1 wherein one of the surface cleaning head and the upright section further comprises or is connectable to a power cord and the portable cleaning unit is powered solely by the first energy storage member when the portable cleaning unit is removed from the upright section.

4. The surface cleaning apparatus of claim 1 wherein one of the surface cleaning head and the upright section further comprises or is connectable to a power cord, the first energy storage member comprises one or more battery and the one or more battery is charged when the portable cleaning unit is mounted on the upright section.

5. The surface cleaning apparatus of claim 1 wherein the upright section is an up flow duct and the portable cleaning unit is a hand vacuum cleaner.

6. The surface cleaning apparatus of claim 1 wherein the portable cleaning unit suction motor is operable on DC power and the upstream suction motor is operable on AC power.

7. The surface cleaning apparatus of claim 6 wherein the portable cleaning unit suction motor is a dirty air motor and the upstream suction motor is a clean air motor.

8. The surface cleaning apparatus of claim 1, wherein the portable cleaning unit further comprises or is connectable to a power cord and the portable cleaning unit suction motor is also operable on power provided by the external source of power when removed from to the upright section.