



US010314447B2

(12) **United States Patent**
Conrad

(10) **Patent No.:** **US 10,314,447 B2**
(45) **Date of Patent:** **Jun. 11, 2019**

- (54) **SURFACE CLEANING APPARATUS**
- (71) Applicant: **Omachron Intellectual Property Inc.**,
Hampton (CA)
- (72) Inventor: **Wayne Ernest Conrad**, Hampton (CA)
- (73) Assignee: **Omachron Intellectual Property Inc.**,
Hampton, Ontario (CA)
- (*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 17 days.

- 9/1625* (2013.01); *A47L 9/1641* (2013.01);
A47L 9/1666 (2013.01); *A47L 9/1683*
(2013.01); *A47L 9/2868* (2013.01); *A47L*
9/2884 (2013.01); *A47L 9/322* (2013.01)
- (58) **Field of Classification Search**
USPC 15/344, 327.1, 347, 353
See application file for complete search history.

- (21) Appl. No.: **15/446,587**
- (22) Filed: **Mar. 1, 2017**

- (56) **References Cited**
U.S. PATENT DOCUMENTS

911,258 A 2/1909 Gotthilf et al.
1,600,762 A 9/1926 Hawley et al.
(Continued)

- (65) **Prior Publication Data**
US 2017/0245700 A1 Aug. 31, 2017

- FOREIGN PATENT DOCUMENTS**

AU 112778 4/1941
CA 1077412 A1 5/1980
(Continued)

- Related U.S. Application Data**
- (60) Continuation of application No. 15/076,959, filed on
Mar. 22, 2016, now Pat. No. 10,271,698, which is a
(Continued)

- OTHER PUBLICATIONS**

English machine translation of DE112007003052T5 published as of
Jan. 14, 2010.
(Continued)


- (51) **Int. Cl.**
A47L 5/24 (2006.01)
A47L 5/22 (2006.01)
A47L 9/16 (2006.01)
A47L 9/32 (2006.01)
A47L 5/36 (2006.01)
A47L 9/28 (2006.01)
(Continued)

Primary Examiner — Joseph J Hail
Assistant Examiner — Shantese L McDonald
(74) *Attorney, Agent, or Firm* — Philip C. Mendes da
Costa; Bereskin & Parr LLP/S.E.N.C.R.L., s.r.l.

- (52) **U.S. Cl.**
CPC *A47L 5/225* (2013.01); *A47L 5/24*
(2013.01); *A47L 5/36* (2013.01); *A47L 5/362*
(2013.01); *A47L 9/009* (2013.01); *A47L 9/125*
(2013.01); *A47L 9/149* (2013.01); *A47L 9/16*
(2013.01); *A47L 9/1608* (2013.01); *A47L*

- (57) **ABSTRACT**
A surface cleaning apparatus comprises an air flow path
extending from a dirty air inlet to a clean air outlet and
includes a cyclone bin assembly, a screen and a suction
motor positioned in the air flow path. The screen is axially
removable from the cyclone bin assembly.

8 Claims, 19 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 14/875,381, filed on Oct. 5, 2015, now Pat. No. 9,545,181, which is a continuation of application No. 13/782,217, filed on Mar. 1, 2013, now Pat. No. 9,192,269, which is a continuation of application No. 13/720,754, filed on Dec. 19, 2012, now Pat. No. 8,752,239, which is a division of application No. 11/954,331, filed on Dec. 12, 2007, now Pat. No. 8,359,705.
- (60) Provisional application No. 60/870,175, filed on Dec. 15, 2006, provisional application No. 60/884,767, filed on Jan. 12, 2007.
- (51) **Int. Cl.**
A47L 9/00 (2006.01)
A47L 9/12 (2006.01)
A47L 9/14 (2006.01)

- (56) **References Cited**

U.S. PATENT DOCUMENTS

1,797,812	A	3/1931	Waring et al.	4,678,588	A	7/1987	Shortt
1,898,608	A	2/1933	Alexander et al.	4,700,429	A	10/1987	Martin et al.
1,937,765	A	12/1933	Leathers et al.	4,744,958	A	5/1988	Pircon et al.
2,015,464	A	9/1935	Saint-Jacques et al.	4,778,494	A	10/1988	Patterson
2,152,114	A	3/1939	Van Hermannus	4,826,515	A	5/1989	Dyson et al.
2,542,634	A	2/1951	Davis et al.	D303,173	S	8/1989	Miyamoto et al.
2,678,110	A	5/1954	Madsen et al.	4,853,008	A	8/1989	Dyson
2,731,102	A	1/1956	James et al.	4,853,011	A	8/1989	Dyson et al.
2,811,219	A	10/1957	Wenzl et al.	4,853,111	A	8/1989	MacArthur et al.
2,846,024	A	8/1958	Bremi et al.	4,905,342	A	3/1990	Ataka
2,913,111	A	11/1959	Rogers et al.	4,944,780	A	7/1990	Usmani
2,917,131	A	12/1959	Evans et al.	5,078,761	A	1/1992	Dyson et al.
2,937,713	A	5/1960	Stephenson et al.	5,080,697	A	1/1992	Finke et al.
2,942,691	A	6/1960	Dillon et al.	5,090,976	A	2/1992	Dyson et al.
2,942,692	A	6/1960	Benz et al.	5,129,125	A	7/1992	Gamou et al.
2,946,451	A	7/1960	Culleton et al.	5,135,552	A	8/1992	Weistra et al.
2,952,330	A	9/1960	Winslow et al.	5,224,238	A	7/1993	Bartlett
2,981,369	A	4/1961	Yellott et al.	5,230,722	A	7/1993	Yonkers
3,032,954	A	5/1962	Racklyeft et al.	5,254,019	A	10/1993	Noschese
3,085,221	A	4/1963	Kelly et al.	5,267,371	A	12/1993	Soler et al.
3,130,157	A	4/1964	Kelsall et al.	5,287,591	A	2/1994	Rench et al.
3,200,568	A	8/1965	McNeil et al.	5,307,538	A	5/1994	Rench et al.
3,204,772	A	9/1965	Ruxton et al.	5,309,600	A	5/1994	Weaver et al.
3,217,469	A	11/1965	Eckert et al.	5,309,601	A	5/1994	Hampton et al.
3,269,097	A	8/1966	German et al.	5,347,679	A	9/1994	Saunders et al.
3,320,727	A	5/1967	Farley et al.	5,363,535	A	11/1994	Rench et al.
3,372,532	A	3/1968	Campbell et al.	5,481,780	A	1/1996	Daneshvar
3,426,513	A	2/1969	Bauer	5,515,573	A	5/1996	Frey
3,518,815	A	7/1970	Peterson et al.	5,599,365	A	2/1997	Alday et al.
3,530,649	A	9/1970	Porsch et al.	D380,033	S	6/1997	Theiss et al.
3,543,325	A	12/1970	Hamrick	5,709,007	A	1/1998	Chiang et al.
3,561,824	A	2/1971	Homan	5,755,096	A	5/1998	Holleyman
3,582,616	A	6/1971	Wrob	5,779,744	A	7/1998	Mueller et al.
3,675,401	A	7/1972	Cordes	5,815,878	A	10/1998	Murakami et al.
3,684,093	A	8/1972	Kono et al.	5,815,881	A	10/1998	Sjoegreen et al.
3,822,533	A	7/1974	Oranje et al.	5,858,038	A	1/1999	Dyson et al.
3,877,902	A	4/1975	Eriksson et al.	5,858,043	A	1/1999	Geise et al.
3,898,068	A	8/1975	McNeil	5,893,938	A	4/1999	Dyson et al.
3,933,450	A	1/1976	Percevaut	5,935,279	A	8/1999	Kilstrom et al.
3,988,132	A	10/1976	Oranje	5,950,274	A	9/1999	Kilstrom
3,988,133	A	10/1976	Schady	5,970,572	A	10/1999	Thomas et al.
4,097,381	A	6/1978	Ritzler et al.	6,071,095	A	6/2000	Verkaart et al.
4,187,088	A	2/1980	Hodgson et al.	6,071,321	A	6/2000	Trapp et al.
4,218,805	A	8/1980	Brazier et al.	6,080,022	A	6/2000	Shaberman et al.
4,236,903	A	12/1980	Malmsten	6,094,775	A	8/2000	Behmer
4,307,485	A	12/1981	Dessig	6,122,796	A	9/2000	Downham et al.
4,373,228	A	2/1983	Dyson et al.	6,145,160	A	11/2000	Buss et al.
4,382,804	A	5/1983	Mellor et al.	6,210,469	B1	4/2001	Tokar
4,409,008	A	10/1983	Solymes	6,221,134	B1	4/2001	Conrad et al.
4,486,207	A	12/1984	Baillie	6,228,260	B1	5/2001	Conrad et al.
4,494,270	A	1/1985	Ritzau et al.	6,231,645	B1	5/2001	Conrad et al.
4,523,936	A	6/1985	DiSanza, Jr. et al.	6,251,296	B1	6/2001	Conrad et al.
				6,260,234	B1	7/2001	Wright et al.
				6,295,692	B1	10/2001	Shideler
				6,345,408	B1	2/2002	Nagai et al.
				6,406,505	B1	6/2002	Oh et al.
				6,434,785	B1	8/2002	Vandenbelt et al.
				6,440,197	B1	8/2002	Conrad et al.
				6,502,278	B2	1/2003	Oh et al.
				6,519,810	B2	2/2003	Kim
				6,531,066	B1	3/2003	Saunders et al.
				6,536,072	B2	3/2003	Thur et al.
				6,553,612	B1	4/2003	Dyson et al.
				6,553,613	B2	4/2003	Onishi et al.
				6,560,818	B1	5/2003	Hasko
				6,581,239	B1	6/2003	Dyson et al.
				6,599,338	B2	7/2003	Oh et al.
				6,599,350	B1	7/2003	Rockwell et al.
				6,613,316	B2	9/2003	Sun et al.
				6,623,539	B2	9/2003	Lee et al.
				6,625,845	B2	9/2003	Matsumoto et al.
				6,640,385	B2	11/2003	Oh et al.
				6,648,934	B2	11/2003	Choi et al.
				6,712,868	B2	3/2004	Murphy et al.
				6,732,403	B2	5/2004	Moore et al.
				6,746,500	B1	6/2004	Park et al.
				6,782,583	B2	8/2004	Oh
				6,782,585	B1	8/2004	Conrad et al.
				6,810,558	B2	11/2004	Lee

(56)

References Cited

U.S. PATENT DOCUMENTS

6,818,036 B1	11/2004	Seaman	2002/0112315 A1	8/2002	Conrad	
6,833,015 B2	12/2004	Oh et al.	2002/0134059 A1	9/2002	Oh	
6,840,972 B1	1/2005	Kim	2002/0178535 A1	12/2002	Oh et al.	
6,868,578 B1	3/2005	Kasper et al.	2002/0178698 A1	12/2002	Oh et al.	
6,874,197 B1	4/2005	Conrad et al.	2002/0178699 A1	12/2002	Oh	
6,896,719 B2	5/2005	Coates et al.	2003/0046910 A1	3/2003	Lee et al.	
6,929,516 B2	8/2005	Brochu et al.	2003/0066273 A1	4/2003	Choi et al.	
6,968,596 B2	11/2005	Oh et al.	2003/0106180 A1	6/2003	Tsen	
6,976,885 B2	12/2005	Lord	2003/0159238 A1	8/2003	Oh	
7,113,847 B2	9/2006	Chmura et al.	2003/0159411 A1	8/2003	Hansen et al.	
7,128,770 B2	10/2006	Oh et al.	2003/0200736 A1	10/2003	Ni	
7,160,346 B2	1/2007	Park	2004/0010885 A1	1/2004	Hitzelberger et al.	
7,162,770 B2	1/2007	Davidshofer	2004/0025285 A1	2/2004	McCormick et al.	
7,175,682 B2	2/2007	Nakai et al.	2004/0083694 A1	5/2004	Choi	
7,188,388 B2	3/2007	Best et al.	2004/0088817 A1	5/2004	Cochran et al.	
7,198,656 B2	4/2007	Takemoto et al.	2004/0134022 A1	7/2004	Murphy et al.	
7,222,393 B2	5/2007	Kaffenberger et al.	2004/0216264 A1	11/2004	Shaver et al.	
7,272,872 B2	9/2007	Choi	2005/0081321 A1	4/2005	Milligan et al.	
7,278,180 B2	10/2007	Pyeong	2005/0115409 A1	6/2005	Conrad	
7,278,181 B2	10/2007	Harris et al.	2005/0132528 A1	6/2005	Yau	
7,341,611 B2	3/2008	Greene et al.	2005/0138758 A1	6/2005	Lee et al.	
7,354,468 B2	4/2008	Arnold et al.	2005/0198769 A1	9/2005	Lee et al.	
7,370,387 B2	5/2008	Walker et al.	2005/0198770 A1	9/2005	Jung et al.	
7,377,007 B2	5/2008	Best	2005/0252179 A1	11/2005	Oh et al.	
7,377,953 B2	5/2008	Oh	2005/0252180 A1	11/2005	Oh et al.	
7,386,915 B2	6/2008	Blocker et al.	2006/0013730 A1	1/2006	Pollock et al.	
7,395,579 B2	7/2008	Oh	2006/0037172 A1*	2/2006	Choi	A47L 9/1666 15/353
7,426,768 B2	9/2008	Peterson et al.	2006/0042039 A1	3/2006	McDowell et al.	
7,429,284 B2	9/2008	Oh et al.	2006/0042206 A1	3/2006	Arnold et al.	
7,448,363 B1	11/2008	Rasmussen et al.	2006/0090290 A1	5/2006	Lau	
7,449,040 B2	11/2008	Conrad et al.	2006/0090428 A1	5/2006	Park et al.	
7,485,164 B2	2/2009	Jeong et al.	2006/0101610 A1	5/2006	Oh et al.	
7,488,362 B2	2/2009	Jeong et al.	2006/0123590 A1	6/2006	Fester et al.	
7,488,363 B2	2/2009	Jeong et al.	2006/0137303 A1	6/2006	Jeong et al.	
7,547,337 B2	6/2009	Oh et al.	2006/0137304 A1	6/2006	Jeong et al.	
7,547,338 B2	6/2009	Kim et al.	2006/0137306 A1	6/2006	Jeong et al.	
7,556,661 B2	7/2009	Jeong et al.	2006/0137307 A1	6/2006	Jeong et al.	
7,563,298 B2	7/2009	Oh	2006/0137309 A1*	6/2006	Jeong	A47L 5/362 55/337
7,588,616 B2	9/2009	Conrad et al.	2006/0137314 A1	6/2006	Conrad et al.	
7,597,730 B2	10/2009	Yoo et al.	2006/0156508 A1	7/2006	Khalil	
7,604,675 B2	10/2009	Makarov et al.	2006/0162298 A1	7/2006	Oh et al.	
7,628,831 B2	12/2009	Gomiciaga-Pereda et al.	2006/0162299 A1	7/2006	North	
7,645,309 B2	1/2010	Jeong et al.	2006/0168922 A1	8/2006	Oh	
7,740,676 B2	6/2010	Burnham et al.	2006/0168923 A1	8/2006	Lee et al.	
7,770,256 B1	8/2010	Fester	2006/0207055 A1	9/2006	Ivarsson et al.	
7,776,120 B2	8/2010	Conrad	2006/0207231 A1	9/2006	Arnold	
7,779,506 B2	8/2010	Kang et al.	2006/0230715 A1	10/2006	Oh et al.	
7,803,207 B2	9/2010	Conrad	2006/0230723 A1	10/2006	Kim et al.	
7,805,804 B2	10/2010	Loebig	2006/0230724 A1	10/2006	Han et al.	
7,811,349 B2	10/2010	Nguyen	2006/0236663 A1	10/2006	Oh	
7,867,308 B2	1/2011	Conrad	2006/0254226 A1	11/2006	Jeon	
7,887,612 B2	2/2011	Conrad	2006/0277712 A1	12/2006	Kim et al.	
7,922,794 B2	4/2011	Morphey	2006/0288516 A1	12/2006	Sawalski	
7,931,716 B2	4/2011	Oakham	2007/0067944 A1	3/2007	Kitamura et al.	
7,938,871 B2	5/2011	Lloyd	2007/0077810 A1	4/2007	Gogel et al.	
7,979,959 B2	7/2011	Courtney	2007/0079473 A1	4/2007	Min et al.	
8,021,453 B2	9/2011	Howes	2007/0079585 A1	4/2007	Oh et al.	
8,062,398 B2	11/2011	Luo et al.	2007/0095028 A1	5/2007	Kim et al.	
8,100,999 B2	1/2012	Ashbee et al.	2007/0095029 A1	5/2007	Min et al.	
8,117,712 B2	2/2012	Dyson et al.	2007/0130894 A1	6/2007	Schultink et al.	
8,146,201 B2	4/2012	Conrad	2007/0143953 A1*	6/2007	Hwang	A47L 9/0081 15/353
8,151,407 B2	4/2012	Conrad	2007/0209334 A1	9/2007	Conrad	
8,152,877 B2	4/2012	Greene	2007/0209335 A1	9/2007	Conrad	
8,156,609 B2	4/2012	Milne et al.	2007/0271724 A1	11/2007	Hakan et al.	
8,161,599 B2	4/2012	Griffith et al.	2007/0278081 A1	12/2007	Thomas et al.	
8,225,456 B2	7/2012	Hkan et al.	2007/0289089 A1	12/2007	Yacobi	
8,347,455 B2	1/2013	Dyson et al.	2007/0289266 A1	12/2007	Oh	
8,444,731 B2	5/2013	Gomiciaga-Pereda et al.	2007/0289267 A1*	12/2007	Makarov	A47L 5/28 55/345
8,484,799 B2	7/2013	Conrad	2008/0040883 A1	2/2008	Beskow et al.	
8,673,487 B2	3/2014	Churchill	2008/0047091 A1	2/2008	Nguyen	
9,192,269 B2	11/2015	Conrad	2008/0134460 A1	6/2008	Conrad	
2002/0011050 A1	1/2002	Hansen et al.	2008/0134462 A1	6/2008	Jansen et al.	
2002/0011053 A1	1/2002	Oh	2008/0178416 A1	7/2008	Conrad	
2002/0062531 A1	5/2002	Oh	2008/0178420 A1	7/2008	Conrad	
2002/0088208 A1	7/2002	Lukac et al.	2008/0190080 A1	8/2008	Oh et al.	

(56)	References Cited			CN	101108110	A	1/2008
	U.S. PATENT DOCUMENTS			CN	101448447	A	6/2009
				CN	101489453	A	7/2009
				CN	101489455	A	7/2009
2008/0196194	A1	8/2008	Conrad	CN	101489457	A	7/2009
2008/0256744	A1	10/2008	Rowntree et al.	CN	101489461	A	7/2009
2008/0301903	A1	12/2008	Cunningham et al.	CN	101657133	A	2/2010
2009/0100633	A1	4/2009	Bates et al.	CN	102188208	A	9/2011
2009/0113659	A1	5/2009	Jeon et al.	CN	102256523	A	11/2011
2009/0113663	A1	5/2009	Follows et al.	CN	202173358	U	3/2012
2009/0144932	A1	6/2009	Yoo	CN	202277306	U	6/2012
2009/0165431	A1	7/2009	Oh	CN	103040412	A	4/2013
2009/0205160	A1	8/2009	Conrad	CN	103040413	A	4/2013
2009/0205161	A1	8/2009	Conrad	CN	202932850	U	5/2013
2009/0205298	A1	8/2009	Hyun et al.	CN	103169420	A	6/2013
2009/0209666	A1	8/2009	Hellberg et al.	DE	875134	C	4/1953
2009/0265877	A1	10/2009	Dyson et al.	DE	9216071	U1	2/1993
2009/0282639	A1	11/2009	Dyson et al.	DE	4232382	C1	3/1994
2009/0300874	A1	12/2009	Tran et al.	DE	112007003039	T5	10/2009
2009/0300875	A1	12/2009	Inge et al.	DE	112007003052	T5	1/2010
2009/0307564	A1	12/2009	Vedanatham et al.	EP	489468	A1	6/1992
2009/0307863	A1	12/2009	Milne et al.	EP	493950	B1	4/1998
2009/0307864	A1	12/2009	Dyson	EP	1302148	A2	4/2003
2009/0308254	A1	12/2009	Oakham	EP	1323370	A2	7/2003
2009/0313958	A1	12/2009	Gomiciaga-Pereda et al.	EP	1200196	B1	6/2005
2009/0313959	A1	12/2009	Gomiciaga-Pereda et al.	EP	1779761	A2	5/2007
2010/0045215	A1	2/2010	Hawker et al.	EP	1676519	B1	10/2008
2010/0083459	A1	4/2010	Beskow et al.	EP	1594386	B1	4/2009
2010/0132319	A1	6/2010	Ashbee et al.	EP	1629758	A3	2/2010
2010/0154150	A1	6/2010	McLeod	EP	2308360	A2	4/2011
2010/0175217	A1	7/2010	Conrad	FR	2812531	B1	11/2004
2010/0212104	A1	8/2010	Conrad	GB	700791	A	12/1953
2010/0224073	A1	9/2010	Oh et al.	GB	1111074	A	4/1968
2010/0229321	A1	9/2010	Dyson et al.	GB	2035787	B	10/1982
2010/0229328	A1	9/2010	Conrad	GB	2163703	B	1/1988
2010/0242210	A1	9/2010	Conrad	GB	2268875	A	1/1994
2010/0243158	A1	9/2010	Conrad	GB	2282979	B	10/1997
2010/0293745	A1	11/2010	Coburn	GB	2365324	B	7/2002
2010/0299865	A1	12/2010	Conrad	GB	2440111	A	1/2008
2010/0299866	A1	12/2010	Conrad	GB	2457419	A	8/2009
2011/0023261	A1	2/2011	Proffitt, II et al.	GB	2441962	B	3/2011
2011/0146024	A1	6/2011	Conrad	GB	2466290	B	10/2012
2011/0168332	A1	7/2011	Bowe et al.	GB	2508035	A	5/2014
2011/0219570	A1	9/2011	Conrad	JP	61131720	A	6/1986
2012/0060322	A1	3/2012	Simonelli et al.	JP	2000140533	A	5/2000
2012/0216361	A1	8/2012	Millington et al.	JP	2003033300	A	2/2003
2012/0222245	A1	9/2012	Conrad	JP	2010178773	A	8/2010
2012/0222260	A1	9/2012	Conrad	JP	2010220632	A	10/2010
2012/0222262	A1	9/2012	Conrad	JP	2011189132	A	9/2011
2013/0091660	A1	4/2013	Smith	JP	2011189133	A	9/2011
2013/0091661	A1	4/2013	Smith	KR	1020050091824	A	9/2005
2013/0091812	A1	4/2013	Smith	KR	1020050091826	A	9/2005
2013/0091813	A1	4/2013	Smith	KR	1020050091829	A	9/2005
2014/0137362	A1	5/2014	Smith	KR	1020050091830	A	9/2005
2014/0137363	A1	5/2014	Wilson	KR	1020050091833	A	9/2005
2014/0137364	A1	5/2014	Stickney et al.	KR	1020050091834	A	9/2005
2014/0182080	A1	7/2014	Lee et al.	KR	1020050091835	A	9/2005
2014/0182808	A1	7/2014	Choi et al.	KR	1020050091836	A	9/2005
2014/0208538	A1	7/2014	Visel et al.	KR	1020050091837	A	9/2005
2014/0237768	A1	8/2014	Conrad	KR	1020050091838	A	9/2005
2016/0367094	A1	12/2016	Conrad	KR	1020050103343	A	10/2005
				KR	1020050104613	A	11/2005
				KR	1020050104614	A	11/2005
				KR	1020060018004	A	2/2006
				WO	1980002561	A1	11/1980
CA	1218962	A1	3/1987	WO	9627446	A1	9/1996
CA	2450450	A1	12/2004	WO	9809121	A1	3/1998
CA	2484587	A1	4/2005	WO	9843721	A1	10/1998
CA	2438079	C	8/2009	WO	107168	A1	2/2001
CA	2659212	A1	9/2010	WO	0217766	A3	2/2003
CN	1336154	A	2/2002	WO	2004069021	A1	8/2004
CN	1493244	A	5/2004	WO	2005084511	A1	9/2005
CN	1875846	A	12/2006	WO	2006026414	A3	8/2007
CN	1875855	A	12/2006	WO	2008009883	A1	1/2008
CN	1887437	A	1/2007	WO	2008009888	A1	1/2008
CN	1969739	A	5/2007	WO	2008009890	A1	1/2008
CN	1981688	A	6/2007	WO	2008009891	A1	1/2008
CN	101061932	A	10/2007	WO	2008035032	A2	3/2008
CN	101108081	A	1/2008	WO	2008035032	A3	6/2008
CN	101108106	A	1/2008	WO			

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2008088278	A2	7/2008
WO	2009026709	A1	3/2009
WO	2010102396	A1	9/2010
WO	2010142968	A1	12/2010
WO	2010142969	A1	12/2010
WO	2010142970	A1	12/2010
WO	2010142971	A1	12/2010
WO	2011054106	A1	5/2011
WO	2012042240	A1	4/2012
WO	2012117231	A1	9/2012

OTHER PUBLICATIONS

English machine translation of DE112007003039T5 published as of Oct. 29, 2009.

English machine translation of JP2011189133A published as of Sep. 29, 2011.

English machine translation of JP2010220632A published as of Oct. 7, 2010.

English machine translation of JP2010178773A published as of Aug. 19, 2010.

English machine translation of CN202932850U published as of May 15, 2013.

English machine translation of CN202277306U published as of Jun. 20, 2012.

English machine translation of CN202173358U published as of Mar. 28, 2012.

English machine translation of CN103169420A published as of Jun. 26, 2013.

English machine translation of CN103040413A published as of Apr. 17, 2013.

English machine translation of CN103040412A published as of Apr. 17, 2013.

English machine translation of CN102256523A published as of Nov. 23, 2011.

English machine translation of CN102188208A published as of Sep. 21, 2011.

English machine translation of Cn101657133A published as of Feb. 24, 2010.

English machine translation of CN101489461A published as of Jul. 22, 2009.

English machine translation of CN101489457A published as of Jul. 22, 2009.

English machine translation of CN101489455A published as of Jul. 22, 2009.

English machine translation of CN101489453A published as of Jul. 22, 2009.

English machine translation of CN101448447A published as of Jun. 3, 2009.

English machine translation of CN101108110 published as of Jan. 23, 2008.

English machine translation of CN101108106A published as of Jan. 23, 2008.

English machine translation of CN101108081A published as of Jan. 23, 2008.

English machine translation of CN101061932 published as of Oct. 31, 2007.

English machine translation of CN1981688A published as of Jun. 20, 2007.

English machine translation of CN1969739 published as of May 30, 2007.

English machine translation of CN1875855 published as of Dec. 13, 2006.

English machine translation of CN1875846 published of Dec. 13, 2006.

English machine translation of CN1336154 published as of Feb. 20, 2002.

English machine translation of KR1020050091824 published as of Sep. 15, 2005.

English machine translation of KR1020050091826 published as of Sep. 15, 2005.

English machine translation of KR1020050091829 published as of Sep. 15, 2005.

Office Action, issued in U.S. Appl. No. 12/720,901 dated Jun. 10, 2011.

Office Action, issued in U.S. Appl. No. 12/720,901 dated Nov. 26, 2010.

International Search report for International Application No. PCT/CA2014/000133 dated Apr. 9, 2014.

International Preliminary Report on Patentability, dated Jun. 16, 2009 for International application No. PCT/CA2007/000380.

Office Action received in connection to the corresponding Chinese Patent Application No. 200880126486.6 dated Mar. 23, 2012.

Office Action received in connection to the corresponding Chinese Patent Application No. 00813438.3 dated Jul. 11, 2003.

Handbook of Air Pollution Prevention and Control, pp. 397-404, 2002.

Makita BCL180 User Manual.

European Communication pursuant to Article 94(3) on European Patent Application No. 04078261.7, dated Apr. 24, 2012.

European Communication pursuant to Article 94(3) on European Patent Application No. 04078261.7, dated Feb. 26, 2010.

United States Office Action, dated Feb. 26, 2011, for U.S. Appl. No. 11/953,292.

United States Office Action, dated Jul. 22, 2010, for U.S. Appl. No. 11/953,292.

Euro-Pro Shark Cordless Hand Vac Owner's Manual, published in 2002.

Makita 4071 Handy Vac.

International Preliminary Examination Report on International application No. PCT/CA00/00873, dated Oct. 26, 2001.

International Search Report and Written Opinion received in connection to the International Patent Application No. PCT/CA2007/002211, dated Apr. 21, 2008.

International Search report for International Application No. PCT/CA2014/000133 dated May 26, 2014.

English machine translation of DE4232382 published as of Mar. 24, 1994.

English machine translation of DE9216071 published as of Feb. 25, 1993.

Third party observations made of record on the repleated United Kingdom Application No. 0911652.6, mailed Jul. 14, 2010.

Office Action issued on co-pending U.S. Appl. No. 11/953,420, dated Jun. 21, 2010.

International Preliminary Report on Patentability received on the co-pending International Application No. PCT/CA2007/002205, dated Apr. 21, 2008.

International Preliminary Report on Patentability received on the corresponding International Application No. PCT/CA2007/002204, dated Apr. 24, 2008.

Supplementary European Search Report, dated Jun. 16, 2009, as received on the corresponding EP application No. 07719394.4.

International Search Report and Written Opinion received in connection to the International Patent Application No. PCT/CA2015/050661, dated Oct. 19, 2015.

English machine translation of KR1020060018004 published as of Feb. 28, 2006.

English machine translation of KR1020050104614 published as of Nov. 3, 2005.

English machine translation of KR1020050104613 published as of Nov. 3, 2005.

English machine translation of KR1020050103343 published as of Oct. 31, 2005.

English machine translation of KR1020050091838 published as of Sep. 15, 2005.

English machine translation of KR1020050091837 published as of Sep. 15, 2005.

English machine translation of KR1020050091836 published as of Sep. 15, 2005.

English machine translation of KR1020050091835 published as of Sep. 15, 2005.

(56)

References Cited

OTHER PUBLICATIONS

English machine translation of KR1020050091834 published as of Sep. 15, 2005.

English machine translation of KR1020050091833 published as of Sep. 15, 2005.

English machine translation of KR1020050091830 published as of Sep. 15, 2005.

English machine translation of JP2011189132 published as of Sep. 29, 2011.

English machine translation of JP2003033300 published as of Feb. 4, 2003.

English machine translation of JP2000140533 published as of May 23, 2000.

English machine translation of JP61131720 published as of Jun. 19, 1986.



English machine translation of FR2812531 published as of Nov. 5, 2004.



English machine translation of CN1887437 published as of Jan. 3, 2007.

English machine translation of CN1493244 published as of May 5, 2004.

English machine translation of DE875134 published as of Apr. 30, 1953.

* cited by examiner








Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10a




Fig. 10b




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21

SURFACE CLEANING APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. 120 as a continuation application of co-pending U.S. patent application Ser. No. 15/076,959 which was filed on Mar. 22, 2016, which itself is a continuation of U.S. patent application Ser. No. 14/875,381, filed on Oct. 5, 2015, now U.S. Pat. No. 9,545,181, issued on Jan. 17, 2017, which itself is a continuation of co-pending U.S. patent application Ser. No. 13/782,217, filed on Mar. 1, 2013, now U.S. Pat. No. 9,192,269, issued on Nov. 24, 2015, which itself is a continuation in part of co-pending U.S. patent application Ser. No. 13/720,754, filed on Dec. 19, 2012, which issued as U.S. Pat. No. 8,752,239 on Jun. 17, 2014, which itself is a divisional application of co-pending U.S. patent application Ser. No. 11/954,331, filed on Dec. 12, 2007, which issued as U.S. Pat. No. 8,359,705 on Jan. 29, 2013, which itself claims priority from U.S. Provisional patent applications 60/870,175 (filed on Dec. 15, 2006), and 60/884,767 (filed on Jan. 12, 2007), all of which are incorporated herein by reference in their entirety.

FIELD

This specification relates to a surface cleaning apparatus comprising a base with a removable portable surface cleaning unit such as a pod or other hand carryable surface cleaning apparatus wherein the portable surface cleaning apparatus is usable when mounted on the base or when removed therefrom.

INTRODUCTION

The following is not an admission that anything discussed below is part of the prior art or part of the common general knowledge of a person skilled in the art.

Various types of surface cleaning apparatuses are known in the art. Such surface cleaning apparatuses include vacuum cleaners, including upright vacuum cleaners, hand carryable vacuum cleaners, canister type vacuum cleaners, and Shop-Vac™ type vacuum cleaners. Some such vacuum cleaners are provided with wheels. For example, typical upright vacuum cleaners are provided with a surface cleaning head that includes wheels mounted to a bottom surface thereof. Upright vacuum cleaners are easy for a consumer to use since the consumer does not have to carry the vacuum cleaner but merely push it over a surface. However, depending on the size of the surface cleaning head, an upright vacuum cleaner may not be useable in smaller or crowded areas. Canister vacuum cleaners have a flexibly hose extending between a surface cleaning head and the canister body, thereby improving mobility of the cleaning head. However, consumers must separately move a canister body, which can add an extra step during the cleaning process.

SUMMARY

This summary is intended to introduce the reader to the more detailed description that follows and not to limit or define any claimed or as yet unclaimed invention. One or more inventions may reside in any combination or sub-combination of the elements or process steps disclosed in any part of this document including its claims and figures.

According to one broad aspect of this invention, a surface cleaning apparatus comprises a portable cleaning unit, which may be carried by hand or a shoulder strap such as a pod, which is removably mounted on a wheeled base. The portable cleaning unit may be provided with a suction motor and an energy storage member (such as batteries). Accordingly, the suction motor of the portable cleaning unit may be operable on DC current. However, in accordance with this embodiment, the wheeled base may include a second suction motor (e.g. an AC powered suction motor). Accordingly, when the portable cleaning unit is provided on the wheeled base and the wheeled base is connected to a source of current, the suction motor in the wheeled base may be operated, e.g. on AC current, and used to draw air through an airflow path to the air treatment member in the portable cleaning unit. An advantage of this design is that the suction motor provided in the wheeled base may produce a higher airflow and therefore increase cleanability when the portable cleaning unit is provided on the wheeled base. However, when the portable cleaning unit is removed from the wheeled base, a smaller and lighter suction motor is utilized. While the velocity of the airflow through the portable cleaning unit when removed from the base may be decreased, the reduced weight of the suction motor may be beneficial. In addition, a smaller airflow path may be provided when the portable cleaning unit is removed from the base, and, accordingly, a smaller DC power suction motor may provide substantially similar airflow in the hand carryable mode.

The portable cleaning unit may comprise at least one cyclonic separation stage and a suction motor. Accordingly, the portable cleaning unit is useable, e.g., as a vacuum cleaner or the like, when removed from the wheeled base. The cyclonic separation stage comprises a cyclone chamber and a material collection chamber. The portable cleaning unit is configured such that the material collection chamber is removable for emptying when the portable cleaning unit is mounted on the wheeled base. For example, the material collection chamber may be removed by itself when the portable cleaning unit is mounted on the wheel base. Alternately, the material collection chamber and the cyclone chamber may be removable as a unit (e.g. a cyclone bin assembly). It will be appreciated that the material collection chamber, either by itself or in conjunction with the cyclone chamber and possibly other elements, may be removable from the portable cleaning unit when the portable cleaning unit has been removed from the wheeled base. An advantage of this design is that the usability of the surface cleaning apparatus is increased. In particular, when it is needed to empty the dirt collection chamber, all that is needed is to remove the dirt collection chamber either by itself, or, for example, together with the cyclone chamber for emptying. Accordingly, a user did not carry the weight of the motor when the user is emptying the dirt collection chamber.

Preferably, in accordance with this embodiment, the dirt collection chamber and, optionally, the cyclone chamber may be provided on an upper portion of the portable cleaning unit so as to be removable upwardly therefrom.

It will be appreciated by a skilled person in the art that any of the features of the configuration of a portable cleaning unit to permit a dirt collection chamber to be removed from the portable cleaning unit when the portable cleaning unit is mounted on the wheeled base as discussed herein may not be utilized with dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with another embodiment, the portable cleaning unit may be provided with a pod hose which is removable with the portable cleaning unit from the wheeled base. The pod hose may have a smaller diameter and, accordingly, may be used only when the portable cleaning unit has been removed from the wheeled base. Accordingly, when the portable cleaning unit is on a wheeled base, the pod hose does not form part of the fluid flow path. Accordingly, the smaller diameter of the pod hose does not restrict the airflow path when the portable cleaning unit is placed on a wheeled base. An advantage of this design is that the portable cleaning unit may carry a longer hose without increasing the volume taken by the pod hose. In addition, the pod hose, being a smaller diameter, may be more flexible and enhance the usability of the portable cleaning unit in a hand-carriable mode. For example, the pod hose may have a greater stretch ratio, for example, of 4:1 to 7:1 or more.

In accordance with this embodiment, a valve may be provided on the portable cleaning unit whereby the pod hose is not in airflow communication with the suction motor when the portable cleaning unit is mounted on the wheeled base. However, when the portable cleaning unit is removed from the wheeled base, the valve may be actuated (e.g. automatically upon removal of the portable cleaning unit from the wheeled base, manually by the user or automatically when the hose is deployed for use) such that pod hose forms part of the air flow path.

It will be appreciated by a person skilled in the art that any of the features of the pod hose which are discussed herein may not be utilized with the dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with another embodiment, the portable cleaning unit may be operable by AC power supplied to the base when the portable cleaning unit is mounted on the base and may be operable on DC power when the portable cleaning unit is removed from the base. Accordingly, the portable cleaning unit may include an energy storage member (e.g. one or more batteries) which may power the suction motor when the portable cleaning unit is removed from the base. Accordingly, the suction motor may be operable on DC current. When the pod is mounted on the wheeled base, and the wheeled base is connected to a source of current by an electrical cord, then the suction motor may be in electrical communication with the base so as to be powered by AC current supplied through the electrical cord. For example, the suction motor could have dual winding so as to be operable on both AC and DC current. Alternately, the base may include a power supply to convert the AC current to DC current which is then supplied to the suction motor when the portable cleaning unit is placed on the base. For example, the power supply may comprise an inverter.

In this particular embodiment, it will be appreciated that the batteries in the portable cleaning unit may be charged while the portable cleaning unit is mounted on the wheeled base and the wheeled base is plugged into an electrical outlet.

In a further alternate embodiment, instead of utilizing electricity from an electrical outlet, the wheeled base may include a fuel cell or an alcohol-powered internal or external combustion engine. In such an embodiment, the wheeled base may produce AC current or DC current, which is then supplied to the suction motor when the portable cleaning unit is mounted on the wheeled base and actuated.

It will be appreciated by a person skilled in the art that any of the features of a portable cleaning unit which is operable on AC and DC current as disclosed herein may not be

utilized with the dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In accordance with the further embodiment, the portable cleaning unit may comprise both an energy storage member and a power supply. Accordingly, when the portable cleaning unit is connected to a power source (e.g. a cord extends from the portable cleaning unit to an electrical outlet), AC power may be supplied to the power supply (e.g. an inverter) to convert the AC current to DC which is then utilized to power the suction motor. When a user is unable to or does not want to plug the portable cleaning unit into a wall outlet, the portable cleaning unit may be powered by the energy storage member (e.g. batteries), which provide DC current to a suction motor. Accordingly, the portable cleaning unit may be powered by both AC current from a wall outlet and DC current supplied by batteries as may be desired. In a further alternate embodiment, the suction motor may be provided with two windings. In such a case, the power supply is not required and the suction motor may be powered by both DC current from the batteries and AC current from a wall outlet.

It will be appreciated by a person skilled in the art that any of the features of a pod operable with both AC and DC current as discussed herein may not be utilized with dual motor design disclosed herein, but may be used by itself or in combination with any other feature disclosed herein.

In one embodiment, there is provided a surface cleaning apparatus comprising

(a) a wheeled base comprising an AC suction motor;
 (b) a portable cleaning unit removably mounted on the wheeled base and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor that is operable on DC power; and,

(c) a fluid flow path extending from a first dirty fluid inlet to a clean air outlet of the surface cleaning apparatus,

wherein the AC suction motor provides motive power to move fluid through the fluid flow path when the surface cleaning unit is switched on and when the portable cleaning unit is mounted on the wheeled base, and

wherein the portable cleaning unit suction motor provides motive power to move fluid through the fluid flow path when the portable cleaning unit is switched on and when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord and the portable cleaning unit is powered solely by the first energy storage member when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the first energy storage member comprises batteries and the batteries are charged when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the suction motor in the portable cleaning unit may not be used to provide motive power to move fluid through the fluid flow path when the surface cleaning unit is switched on and when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the fluid flow path may comprise an upstream portion that extends from the first dirty fluid inlet to the portable cleaning unit and the AC suction motor is in the fluid flow path.

In some embodiments, the fluid flow path may comprise a downstream fluid flow path extending through the portable cleaning unit to the clean air outlet and the portable cleaning unit suction motor is in the downstream fluid flow path.

In some embodiments, the portable cleaning unit may comprise a flexible hose having a second dirty fluid inlet and the flexible hose is part of the downstream fluid flow path when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the flexible hose may be an electrified flexible hose.

In some embodiments, the wheeled base may further comprise a second energy storage member.

In some embodiments, the second energy storage member may charge the first energy storage member when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the portable cleaning unit suction motor may be a DC motor.

In one embodiment, there is provided a surface cleaning apparatus comprising

(a) a wheeled based connectable to a source of current;

(b) a portable cleaning unit removably mounted on the wheeled base and comprising at least one cyclonic separation stage, a first energy storage member and a portable cleaning unit suction motor that is operable on DC power; and,

(c) a fluid flow path extending from a first dirty fluid inlet to a clean air outlet of the surface cleaning apparatus,

wherein the portable cleaning unit suction motor is operable on DC power when removed from the wheeled base and is operable on power provided by the wheeled base when mounted on the wheeled base.

In some embodiments, the portable cleaning unit suction motor may be a DC motor.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord and the portable cleaning unit is powered solely by the first energy storage member when the portable cleaning unit is removed from the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the first energy storage member comprises batteries and the batteries are charged when the portable cleaning unit is mounted on the wheeled base.

In some embodiments, the wheeled base may further comprise or is connectable to a power cord, the wheeled base further comprises a circuit that receives AC current and outputs DC current and the portable cleaning unit is powered the DC current when the portable cleaning unit is mounted on the wheeled base.

In some embodiments the portable cleaning unit suction motor may operate at a first power level when removed from the wheeled base and at a second power level when is mounted on the wheeled base.

In some embodiments the first power level may be less than the second power.

In accordance with another aspect, a surface cleaning apparatus, preferably a canister or Shop-Vac™ style vacuum cleaner is provided which comprises a portable cleaning unit and a wheeled base. Preferably, the cleaning unit is removably mounted to the wheeled base. Alternately, or in addition, the wheeled base has wheels mounted outward of the wheeled base, and which are preferably of a larger diameter (e.g., 1-3 inches in diameter, preferably 1.5-2.5 inches in diameter).

According to this aspect, the surface cleaning apparatus may comprise a member having a dirty fluid inlet. A fluid flow path extends from the dirty fluid inlet to a clean air outlet of the surface cleaning apparatus. The surface cleaning apparatus further comprises a wheeled based. A portable cleaning unit is removably mounted on the wheeled base and

comprising at least one cyclonic separation stage and a suction motor positioned in the fluid flow path.

Embodiments in accordance with this broad aspect may be advantageous because the surface cleaning apparatus may have increased maneuverability. That is, the surface cleaning apparatus may be used as a wheel mounted surface cleaning apparatus when convenient for a user since the user need not carry the surface cleaning apparatus, or as a hand or strap carryable surface cleaning apparatus, such as when a stairs or a smaller or crowded area is to be cleaned, according to the user's preference.

In some embodiments, the at least one cyclonic separation stage may comprise a cyclone chamber having at least one material outlet, a divider plate associated with the material outlet and an associated material collection chamber in flow communication with the material outlet.

In some embodiments, the material collection chamber may be positioned below the material outlet. In a further embodiment, the divider plate may be positioned in the material outlet.

In some embodiments, the material collection chamber may be moveable relative to the cyclone chamber. In a further embodiment the material collection chamber may be removable from the at least one cyclone chamber.

In some embodiments, the material collection chamber may have a portion that is openable. In a further embodiment, the portion that is openable may be a bottom wall. Such embodiments may be advantageous because the wheeled base may prevent accidental opening of the material collection chamber.

In some embodiments, the suction motor may be positioned laterally spaced from the at least one cyclonic separation stage. Accordingly, the surface cleaning apparatus may have a relatively wide stance and low center of mass, and therefore may have increased stability.

In some embodiments, the cleaning unit has a front end having the dirty fluid inlet and the front end of the cleaning unit is positioned at a front end of the wheeled base and the suction motor is positioned rearward of the at least one cyclonic separation stage.

In some embodiments, the wheeled base may have a length greater than its width. In further embodiments, the wheeled base may be generally polygonal, and preferably generally triangular in shape. Such embodiments may be advantageous because the surface cleaning apparatus may have both increased maneuverability and increased stability.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels, the rear wheels may have a larger diameter than the at least one front wheel and the at least one front wheel may be steerable. Such embodiments may be advantageous because the larger rear wheels may provide the wheeled base with increased stability, and the steerable front wheel may provide the wheeled base with increased maneuverability. Alternately, the front wheels may have a larger diameter or essentially the same diameter as the rear wheels.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels and the rear wheels may have a larger diameter than the at least one front wheel.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels and the rear wheels may have a smaller diameter than the at least one front wheel.

In some embodiments, the at least one front wheel may be steerable.

In some embodiments, the wheeled base may have rear wheels that are positioned outwardly of an area occupied by the cleaning unit when the cleaning unit is mounted on the wheeled base. Alternately, or in addition, the wheeled base may have front wheels that are positioned outwardly of an area occupied by the cleaning unit when the cleaning unit is mounted on the wheeled base. Such embodiments may be advantageous because the wheeled base may have a relatively wide stance, thereby providing greater stability to the surface cleaning apparatus. Additionally, the surface cleaning apparatus may be relatively close to the ground, and may therefore have a lower center of mass and increased stability.

In some embodiments, the cleaning unit may have a front end having a fluid inlet downstream from the dirty fluid inlet and the front end of the cleaning unit is positioned at a front end of the wheeled base.

In some embodiments, the cleaning unit may be lockably receivable on the wheeled base.

In some embodiments, the wheeled base may have at least one front wheel having a diameter of 1 to 3 inches and at least two rear wheels having a diameter of 1 to 3 inches.

In some embodiments, the cleaning unit may have a carry handle and/or a shoulder strap.

In some embodiments, the wheeled base may have at least one front wheel and at least two rear wheels, and the cleaning unit is receivable on an open platform.

In some embodiments, the wheeled base may have an absence of operating components.

It will be appreciated by a person skilled in the art that a surface cleaning apparatus may embody any one or more of the features contained herein and that the features may be used in any particular combination or sub-combination.

BRIEF DESCRIPTION OF THE DRAWINGS

The drawings included herewith are for illustrating various examples of articles, methods, and apparatuses of the teaching of the present specification and are not intended to limit the scope of what is taught in any way.

In the drawings:

FIG. 1 is a perspective view of an embodiment of a surface cleaning apparatus of the present invention;

FIG. 2 is a front view of the embodiment of FIG. 1;

FIG. 3 is a side view of the embodiment of FIG. 1;

FIG. 4 is a top view of the embodiment of FIG. 1;

FIG. 5 is a perspective view of the embodiment of FIG. 1, showing a surface cleaning unit removed from a wheeled base;

FIG. 6 is a side view of the embodiment of FIG. 1, showing a surface cleaning unit removed from a wheeled base;

FIGS. 7-9 are cross-sections taken along line 7-7 in FIG. 1, showing alternate configurations of a cleaning unit;

FIG. 10a is a perspective illustration of an alternate embodiment of a surface cleaning apparatus of the present invention, showing a lid in an open position;

FIG. 10b is a perspective illustration of the surface cleaning apparatus of FIG. 10a, showing the lid in the open position with a filter assembly and cylindrical housing removed;

FIG. 11 is a perspective view of another embodiment of a surface cleaning apparatus;

FIG. 12 is another perspective view of the surface cleaning apparatus of FIG. 11;

FIG. 13 is a perspective view of the surface cleaning apparatus of FIG. 11 with a surface cleaning unit detached;

FIG. 14 is another perspective view of the surface cleaning apparatus of FIG. 11 with a surface cleaning unit detached;

FIG. 15 is a schematic representation of another embodiment of a surface cleaning apparatus;

FIG. 16 is a schematic representation of the surface cleaning apparatus of FIG. 15 with a surface cleaning unit detached;

FIG. 17 is a schematic representation of another embodiment of a surface cleaning apparatus;

FIG. 18 is a perspective view of another embodiment of a surface cleaning apparatus;

FIG. 19 is another perspective view of the surface cleaning apparatus of FIG. 18 with a cyclone bin assembly removed;

FIG. 20 is a perspective view of the surface cleaning apparatus of FIG. 18 with a surface cleaning unit detached and a cyclone bin assembly removed from the surface cleaning unit; and,

FIG. 21 is a bottom perspective view of the cyclone bin assembly of the surface cleaning apparatus of FIG. 18 in the open position.

DESCRIPTION OF VARIOUS EMBODIMENTS

Various apparatuses or processes will be described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may cover processes or apparatuses that differ from those described below. The claimed inventions are not limited to apparatuses or processes having all of the features of any one apparatus or process described below or to features common to multiple or all of the apparatuses described below. It is possible that an apparatus or process described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus or process described below that is not claimed in this document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicants, inventors or owners do not intend to abandon, disclaim or dedicate to the public any such invention by its disclosure in this document.

Portable Cleaning Unit Construction

The following is a description of portable cleaning unit constructions that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring to FIGS. 1-4, an embodiment of a surface cleaning apparatus 10 of the present invention is shown. Surface cleaning apparatus 10 may be a canister type vacuum cleaner, a Shop-Vac™ type vacuum cleaner, or another type of vacuum cleaner that may be mounted to a wheeled base. Surface cleaning apparatus 10 comprises a dirty fluid inlet 12, a clean air outlet 14, and a fluid flow path extending therebetween. A portable cleaning unit 16 is provided in the fluid flow path. Cleaning unit 16 comprises at least one cyclonic separation stage 18 for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit 16 further comprises a suction motor 20 for drawing fluid from the dirty fluid inlet 12 to the clean air outlet 14.

Dirty fluid inlet 12 is provided in a member 34. In the embodiment shown in FIGS. 1-6, member 34 is a hose. In the embodiment shown in FIGS. 7-10, member 34 is a nozzle. In other embodiment, member 34 may be, for example, a surface cleaning head. It will be appreciated that

a flexible hose, a rigid wand or other attachment may be affixed or removably affixed to portable cleaning unit 16.

Referring to the exemplified embodiments of FIGS. 7-9, from dirty fluid inlet 12, fluid is directed to cleaning unit 16. Cleaning unit 16 may be of a variety of configurations. In the embodiment of FIGS. 7 and 8, cleaning unit 16 comprises a single cyclonic cleaning stage 18 preferably comprising a single cyclone housed in a first housing 44, and a filter assembly 38 and motor 20 housed in a second housing 46 adjacent the first housing. Accordingly, in this embodiment, the suction motor 20 is positioned laterally adjacent and laterally spaced from the cyclonic cleaning stage 18. In the embodiment of FIG. 9, cleaning unit 16 comprises first 18 and second 48 cleaning stages housed in first housing 44, and filter assembly 38 and motor 20 housed in second housing 46 laterally adjacent the first housing. In this embodiment, motor 20 is positioned laterally spaced from and laterally adjacent both of first 18 and second 48 cleaning stages. It will be appreciated that portable cleaning unit may utilize one or more cyclonic cleaning stages, each of which may comprise a single cyclone or a plurality of cyclones in parallel. In any embodiment, one or more additional cleaning stages may be used such as one or more filters.

For example, in the embodiments exemplified, cyclonic cleaning stage 18 includes a single cyclone chamber 22. Cyclone chamber 22 comprises a dirty air inlet 24, a separated or dirty material outlet 26, and a clean air outlet 28. A dirty or separated material collection chamber 30 is mounted below dirty material outlet 26, for collecting material removed from the air in cyclone chamber 22. In the embodiment shown, a divider plate 32 is associated with dirty material outlet 26. Divider plate 32 is positioned below the dirty material outlet 26, within the material collection chamber 30. It will be appreciated that a divider plate may be used any one or more of the cyclones and it may be of any configuration and located at any position known in the art. Alternately, a divider plate may not be used and the cyclone chambers may be of any design.

Material collection chamber 30 may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIGS. 7 and 8, material collection chamber 30 has a bottom 31 that is openable by pivoting about a pivot pin 33. In this embodiment, material collection chamber further comprises a latch 35, for locking bottom 31 in place, and a button 37 for releasing the latch. In other embodiments, material collection chamber 30 may be emptied in another manner. For example, material collection chamber 30 may be movable or removable from surface cleaning apparatus 10, such that it may be emptied, or may have another portion that opens. It may be removable from portable cleaning unit with the associated cyclone or cyclones as a sealed unit. See for example the embodiments of FIGS. 14 and 19.

In some embodiments, a filter or a screen may be associated with clean air outlet 28. For example, as shown in FIG. 8, a cylindrical housing 53 may be mounted on clean air outlet 28 and may have a plurality of openings 55 which are provided with a screen (e.g. a wire mesh). Cylindrical housing 53 may be slidably mounted in outlet 28 such that when lid 45 is open, as shown in FIG. 10a, cylindrical housing 53 may be pulled upwardly for removal and cleaning (see FIG. 10b). Any such screen or filter known in the art may be used.

In the embodiment of FIGS. 7 and 8, air is directed from cyclone chamber 22 out of clean air outlet 28, and into an airflow passage 36, which extends between first housing 44 and second housing 46. From airflow passage 36, air is

directed through a filter assembly 38, which, in the embodiments exemplified, comprises a pre-motor foam filter 40, and a screen filter 42. In some examples, as shown in FIG. 10b, filter assembly 38 may also include a removable filter housing 57 that can be removably mounted in second housing 46. The filters 40 and 42 can be removably mounted in filter housing 57. From filter assembly 38, air is drawn past motor 20, and out of clean air outlet 14.

In the exemplified embodiment of FIG. 9, from cyclone chamber 22, air is directed out of clean air outlet 28 and into second cyclonic cleaning stage 48. Second cyclonic cleaning stage 48 comprises a plurality of second stage cyclones 50 in parallel. Each second stage cyclone comprises an inlet (not shown) in fluid communication with clean air outlet 28, and an outlet 52 in fluid communication with airflow passage 36. Each second stage cyclone comprises a cyclonic cleaning region 54, and a dirt collection region 56. From outlets 28, air is directed into airflow passage 36, and into filter assembly 38. From filter assembly 38, air is drawn past motor 20, and out of clean air outlet 14.

In other embodiments, cleaning unit 16 may be otherwise configured. For example, cleaning unit 16 may not comprise a filter assembly, or may comprise a plurality of filter assemblies. Additionally, cleaning unit 16 may comprise additional cleaning stages, which may be positioned laterally adjacent each other or above each other.

In the embodiments shown, the first 44 and second 46 housings are integrally molded. In other embodiments, the first 44 and second 46 housings may be separately manufactured and then secured together, such as by a common base or by gluing, welding or mechanically securing the two housings together. In some embodiments, first 44 and/or second 46 housing may be provided with an openable lid 45, as shown in FIG. 10. When a user opens lid 45, the user may have access to components housed in first 44 and/or second housing 46. For example, as shown in FIG. 10, lid 45 may be provided with a plurality of flanges 47, which are mounted on flanges 49 provided on housings 44 and/or 46. Flanges 47 are pivotally connected together by pivot pins 51. Accordingly, lid 45 may be pivoted from the closed position, as shown in FIGS. 1-9, to the opened position, as shown in FIG. 10.

Referring to FIG. 11, another embodiment of a surface cleaning apparatus 110 is shown. Surface cleaning apparatus 110 is generally similar to surface cleaning apparatus 10, and analogous features are identified using like reference characters indexed by 100.

Surface cleaning apparatus 110 comprises a dirty fluid inlet 112, a clean air outlet 114, and a fluid flow path extending therebetween. A portable cleaning unit 116 is provided in the fluid flow path. Cleaning unit 116 comprises at least one cyclonic separation stage 118 for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit 116 further comprises a suction motor 120 for drawing fluid from the dirty fluid inlet 112 to the clean air outlet 114. Dirty fluid inlet 112 is provided in a member 134, which in this embodiment is a surface cleaning head.

In this embodiment the cleaning unit 116 is mounted to a wheeled base 158. Wheeled base 158 comprises a plurality of wheels 160, and a cradle 162, which receives cleaning unit 116. The portable cleaning unit 116 can be operated while seated in the cradle 162 (FIGS. 11 and 12) and can be lifted out of the cradle 162 and used as a hand carryable apparatus (FIG. 13).

Referring to FIG. 14, in this embodiment the cyclone cleaning stage 118 includes a cyclone chamber 122. Cyclone chamber 122 comprises a dirty air inlet 124, a separated or

11

dirty material outlet **126**, and a clean air outlet **128** (FIG. **14**). A dirty or separated material collection chamber **130** is beside the cyclone chamber **122** and in communication with the dirty material outlet **126**, for collecting material removed from the air in cyclone chamber **122**.

Material collection chamber **130** may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIG. **14**, material collection chamber **130** has a bottom **131** that is openable by pivoting about a pivot pin **133**. In this embodiment, material collection chamber further comprises a latch **135**, for locking bottom **131** in place, and a button **137** for releasing the latch. In this embodiment the material collection chamber **130** may be movable or removable from surface cleaning apparatus **110** and from the portable cleaning unit **116**, such that it may be emptied, and is removable from portable cleaning unit **116** with the associated cyclone **118** or cyclones as a sealed unit.

Referring to FIGS. **18-21**, another embodiment of a surface cleaning apparatus **510** is shown. Apparatus **510** is generally similar to surface cleaning apparatus **10**, and analogous features are identified using like reference characters indexed by **500**.

Referring to FIG. **18**, surface cleaning apparatus **510** comprises a dirty fluid inlet **512**, a clean air outlet **514**, and a fluid flow path extending therebetween. A portable cleaning unit **516** is provided in the fluid flow path. Cleaning unit **516** comprises at least one cyclonic separation stage **518** (FIG. **21**) for removing dirt from air, or for removing liquid from air or to pick up liquid. Cleaning unit **516** further comprises a suction motor **520** (FIG. **20**) for drawing fluid from the dirty fluid inlet **512** to the clean air outlet **514**. Dirty fluid inlet **512** is provided in a member **534**, which in this embodiment is a surface cleaning head.

In this embodiment the cleaning unit **516** is mounted to a wheeled base **558**. Wheeled base **558** comprises a plurality of wheels **560**, and a cradle **562** (FIG. **20**), which receives cleaning unit **516**. The portable cleaning unit **516** can be operated while seated in the cradle **562** (FIG. **18**) and can be lifted out of the cradle **562** and used as a hand carryable apparatus (FIG. **20**).

Referring to FIG. **21**, in this embodiment the cyclone cleaning stage **518** includes a cyclone chamber **522**. Cyclone chamber **522** comprises a dirty air inlet **524** (FIG. **19**), a separated or dirty material outlet **526**, and a clean air outlet **528**. A dirty or separated material collection chamber **530** is beside the cyclone chamber **522** and in communication with the dirty material outlet **526**, for collecting material removed from the air in cyclone chamber **522**.

Material collection chamber **530** may be of any configuration and may be emptied by a user in any manner known in the art. In the embodiment shown in FIG. **21**, material collection chamber **530** has a bottom **531** that is openable by pivoting about a pivot pin **533**. In this embodiment, material collection chamber further comprises a latch **535**, for locking bottom **531** in place, and a button **537** for releasing the latch.

Wheeled Base Construction

The following is a description of a wheeled base construction that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring again to FIGS. **1-4**, portable cleaning unit **16** is mounted to a wheeled base **58**. Wheeled base **58** comprises a plurality of wheels **60**, and a cradle **62**, which receives cleaning unit **16**.

12

In some embodiments, cleaning unit **16** may be permanently mounted to wheeled base **58**, for example via one or more bolts. In other embodiments, cleaning unit **16** may be removably mounted to wheeled base **58**. For example, a user may remove cleaning unit **16** from wheeled base in order to maneuver cleaning unit **16**, or to empty material collection chamber **30**. In such embodiments, cleaning unit **16** is portable. For example, as shown in FIGS. **5** and **6**, cleaning unit **16** may be removed from wheeled base **58** by lifting cleaning unit **16** off of wheeled base **58**.

In any embodiment, surface cleaning apparatus **10** may comprise a handle **64**, and/or a shoulder strap **65** (shown in FIG. **8**) for maneuvering cleaning unit **16** when it is removed from wheeled base **58**. In some embodiments, handle **64** may be integrally formed with one or both of first **44** and second **46** housings.

Surface cleaning apparatus **10** may further comprise a locking member (not shown), such that cleaning unit **16** may be lockably received on wheeled base **58**. The locking member may comprise any suitable locking member known in the art, such as, for example, a quick release latch, a friction or snap fit, a set screw, a tie down strap (e.g., a strap which may be wrapped around cleaning unit **16**) or the like. The lock may be actuatable by a foot pedal. Alternately wheeled base **58** may have side wall extending up around cradle **62** within which portable cleaning unit **16** is received. It will be appreciated that cradle **64** may be any member on which portable cleaning unit **16** may be received or secured, such as a flat base with or without side walls.

In the embodiments exemplified, wheeled base **58** comprises a front wheel **66**, and two rear wheels **68a**, **68b**. Accordingly, cradle **62** is a platform that is generally polygonal and, preferably, generally triangular in configuration. This configuration may provide increased maneuverability to surface cleaning apparatus **10**. In other embodiments, wheeled base **58** may comprise another number of wheels. For example, in some embodiments, wheeled base **58** may comprise two front wheels and two rear wheels. It will be appreciated that, as exemplified, housings **44**, **46** may be oriented on cradle **62** with the suction motor at the rearward end of portable cleaning unit **16** and the inlet to portable cleaning unit **16** at the forward end of the front housing. In alternate configurations, housings **44**, **46** may be positioned side by side. Further, if more than two housings **44**, **46** are provided, then the housings may be arranged linearly, in a triangular configuration or any other desired configuration.

In some embodiments, front wheel **66** is rotatably mounted about a vertical axis to cradle **62** (e.g., is a caster wheel), and rear wheels are non-rotatably mounted about a vertical axis. Accordingly, front wheel **66** may be steerable. In other embodiments, all of front wheel **66** and rear wheels **68** may be caster wheels, or may be non-rotatably mounted wheels.

In some embodiments, wheeled base **58** has a length greater than its width. That is, the distance **L** between front wheel **66** and axis **67** extending between rear wheels **68a**, **68b**, is greater than the distance **W** between rear wheels **68a**, **68b**, along axis **67**. In other embodiments, wheeled base **58** may have a width **W** greater than its length **L**, or may have width **W** equal to its length **L**.

In the embodiments shown, front wheel **66** is of a smaller diameter than rear wheels **68a**, **68b**. Alternately, rear wheels **68a**, **68b** may be smaller than front wheel **66**. Preferably, both the front and rear wheels are each relatively large. For example, in some embodiments, front wheel(s) may have a diameter of between about 0.5-4 inches, preferably 1-3 inches and more preferably 1.5-2.5 inches. In some embodi-

ments, rear wheels may have a diameter of between about 0.5-4 inches, preferably 1-3 inches and more preferably 1.5-2.5 inches. In one particular embodiment, both front wheel(s) 66 and rear wheels 68a, 68b have a diameter in the same range. Such embodiments may be advantageous to provide surface cleaning apparatus 10 with increased maneuverability and with increased stability.

In the embodiments shown, wheeled base 58 is configured such that, when cleaning unit 16 is mounted on cradle 62, rear wheels 58 are positioned outwardly of cleaning unit 16. That is, rear wheels 58 are separated by a distance W that is greater than the width W' of cleaning unit 16. Such embodiments may provide surface cleaning apparatus 10 with a wider stance, and accordingly with increased stability. Additionally, because rear wheels 68 are positioned outwardly of cleaning unit 16, rear wheels 68 may be provided with an increased diameter, as previously mentioned, without increasing the distance between cleaning unit 16 and a surface such as a floor. Accordingly, the center of mass of cleaning unit 16 may remain low, which further increases the stability of surface cleaning apparatus 10.

In some embodiments, wheeled base 58 may comprise operating components of surface cleaning apparatus 10, such as a suction motor (see FIG. 17). For example, wheeled base may comprise a portion that is provided in the fluid flow path, and includes a filter assembly (not shown). In other embodiments, as exemplified, wheeled base 58 may not comprise any operating components (i.e. wheeled base has an absence of operating components).

In the embodiments shown, cleaning unit 16 is oriented such that dirty fluid inlet 12 is provided at a front end 70 of surface cleaning apparatus 10, adjacent front wheel 66, and suction motor 20 is provided at a rear end 72 of surface cleaning apparatus 10, adjacent rear wheels 68. In other embodiments, cleaning unit 16 may be otherwise oriented. For example, suction motor 20 may be provided at front end 70, and dirty fluid inlet 12 may be provided at rear end 72. Alternatively, cleaning unit 16 may be oriented such that suction motor 20 and dirty fluid inlet 12 are equally spaced from front wheel 66 and rear wheels 68. That is, cleaning unit 16 may be positioned substantially sideways in wheeled base 58.

In some embodiments, portable cleaning unit 16 may be connected to a remote surface cleaning head by connected in air flow communication with the wheeled base, wherein the remote surface cleaning head may be connected or removably connected in air flow communication with the wheeled base. Accordingly, when portable cleaning unit 16 is placed on the wheeled base, it may be automatically connected in air flow communication with the wheeled base (see for example FIGS. 15, 17 and 19) or the user may have to connect portable cleaning unit 16 in air flow communication with the wheeled base, such as by connecting a hose of portable cleaning unit 16 in air flow communication with an air outlet of the wheeled base (see for example FIGS. 5 and 6).

As exemplified in FIGS. 5 and 6, wheeled base 62 may comprise a floor cleaning mount 82 coupled to cradle 62. A first end 84 of mount 82 is configured for receiving member 34, which, in the embodiments exemplified in FIGS. 1-6, is a hose. A second end 86 of mount 82 is configured for receiving another member, for example a remote surface cleaning head that is preferably at the distal end of a wand and a flexible hose extends between the wand and mount 82 (not shown). It will be appreciated that portable cleaning unit 16 may be designed such that the inlet of the portable cleaning unit automatically is connected in flow communi-

cation with mount 82 when portable cleaning unit 16 is positioned on wheeled base 58, such as by use of an inlet port aligned with first end 84 or a rigid pipe that is fittable thereon. Alternately, as exemplified, a flexible hose 34 that is manually insertable may be used. An advantage of this design is that the attachment member for a wand or the like is provided on the platform and not the portable cleaning unit. Therefore, the wand may be used to pull wheeled base 58 without risk of pulling portable cleaning unit 16 off of wheeled base 58. Further, preferably the attachment point is close to the floor, preferably at the level of cradle 62, thereby lowering the point at which wheeled base 58 may be pulled and increasing the stability of wheeled base 58 when it is being pulled.

It will be appreciated that in the portable mode, a wand or flexible hose and wand, or other member known in the art may be attached to hose 34 or hose 34 may be removed and the wand or flexible hose and wand, or other member known in the art may be attached directly to the inlet to housing 44.

In some embodiments, one or more accessories, such as cleaning brush 74 and wand extension 76 may be secured to the upper surface of lid 45, such as by means of mounts 78. Accordingly, extension 76 may be configured to function as a handle (e.g. central section 76 may be arcuate in shape or be spaced from lid 45), to define an opening 80 between the upper surface of lid 34 such that extension 76 of brush 74 may be a carry handle 64 for the vacuum cleaner. Alternately, extension 76 may be configured to seat on handle 64 and permit handle 64 to be used when brush 74 is mounted on portable cleaning unit 16. In other embodiments, one or more accessories may be provided in a recess in the lower surface of portable cleaning unit 16 or in an upper surface of wheeled base 58.

Removable Dirt Chamber

The following is a description of a portable cleaning unit having a removable dirt chamber that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

As exemplified in FIG. 14, the cyclone chamber 118 and material collection chamber 130 may be constructed as a one piece assembly and are referred to collectively as a cyclone bin assembly 188. In accordance with this aspect, cyclone bin assembly 188 may be removed from the portable surface cleaning unit 116 when the portable surface cleaning unit 116 is seated on the base 158 (FIGS. 14 and 19) and when the portable surface cleaning unit 116 is separated from the base 158 (FIG. 13). This may allow a user to remove only the cyclone bin assembly 188, for example for emptying, regardless of whether the surface cleaning unit 116 is docked on the base 158.

As exemplified in FIGS. 18-21, the material collection chamber 530 may be movable or removable from surface cleaning apparatus 510 and from the portable cleaning unit 516, such that it may be emptied, and is removable from portable cleaning unit 516 with the associated cyclone 518 or cyclones as a sealed unit.

In the illustrated embodiment, the cyclone chamber 518 and material collection chamber 530, referred to collectively as a cyclone bin assembly 588, can be removed from the portable surface cleaning unit 516 when the portable surface cleaning unit 516 is seated on the base 558 (FIG. 19) and when the portable surface cleaning unit 516 is separated from the base 558 (FIG. 20). This may allow a user to remove only the cyclone bin assembly 588, for example for emptying, regardless of whether the surface cleaning unit 516 is docked on the base 558.

15

Referring to FIG. 18, in the illustrated embodiment, when the surface cleaning unit 516 is mounted on the base 558 the air flow path between the surface cleaning head 534 and the suction motor in the surface cleaning unit 516 includes a rigid conduit 589, a flexible hose 590a.

In this embodiment, the first hose 190a is connected to the surface cleaning unit 516 and extends between a downstream end 592a (with reference to the direction of airflow through the hose 590a) that is connected to the surface cleaning unit 516 and the rigid conduit 589. In this configuration, when the surface cleaning unit 516 is removed from the base 558 the hose 590a comes with the surface cleaning unit 516 (FIG. 20).

It will be appreciated that, in alternate embodiments, material collection chamber 130 may be a separate unit and may be removable without the cyclone chamber. Alternatively, or in addition, material collection chamber 130 may be removed with the handle of the portable cleaning unit. An advantage of this design is that the handle of the portable cleaning unit may be useable to manipulate the material collection chamber 130 or cyclone bin assembly when removed for emptying.

Automatic Portable Cleaning Unit Hose Connection

The following is a description of automatically connecting a hose of the portable cleaning unit in air flow communication with the base when the portable cleaning unit is placed on the base that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Referring to FIG. 12, in the illustrated embodiment, when the surface cleaning unit 116 is mounted on the base 158, the air flow path between the remote surface cleaning head 134 and the suction motor in the surface cleaning unit 116 includes a rigid conduit or wand 189, a first flexible hose 190a and a second flexible hose 190b (see also FIG. 14) positioned downstream from the first hose 190a.

The first hose 190a extends from its upstream that is connected to rigid conduit 189 to its downstream end 192a (with reference to the direction of airflow through the hose 190a) that is connected to the base 158. The first hose 190a has a diameter 191a. While the first hose 190a may be removably connectable to the base 158, first hose 109a remains attached to the base 158 regardless of the position of the surface cleaning unit 116 (FIGS. 12 and 14).

Referring to FIG. 13, the second hose 190b is attached to and is removable with the surface cleaning unit 116. A downstream end 192b of the hose 190b is attached to the air inlet 124 of the cyclone chamber 118 and the upstream end 193b is removably connectable in air flow communication with the air outlet of the base 158 (e.g., opening 195 of coupling 194). When the surface cleaning unit 116 is removed from the base 158, the upstream or inlet end 193b of the hose 190b can be used as a second or auxiliary dirty air inlet for drawing fluid and debris into the air flow path. Optionally, auxiliary cleaning tools may be attached to the inlet end 193b of the hose 190b. In this configuration, the first hose 190a does not form part of the airflow path to the surface cleaning unit 116.

The second hose 190b is shown in a wrapped or storage position in FIG. 13 in which it is wrapped around part of the surface cleaning unit 116. When the surface cleaning unit 116 is in use as a portable cleaning unit the second hose 190b can be unwound and extended. Preferably, the second hose 190b is extensible to increase its cleaning range. The second hose 190b has a diameter 191b, which optionally may be smaller than diameter 191a. This may help reduce the overall size of the surface cleaning unit 116 and may help it

16

nest on the base 158. However, it is preferred that they have the same or similar diameters so as to provide an air flow path that has a generally constant diameter. The hoses 190a and 190b may be generally similar. Alternatively, they may have different properties. For example, the first hose 190a may be non-extensible and relatively stiff (to allow a user to pull the hose 190a to advance the base 158 across the surface) and the second hose 190b may be extensible and less stiff.

Referring to FIG. 12, when the surface cleaning unit 116 is seated on the base 158, the inlet end 193b of the second hose 190b is connected in air flow communication with the downstream end 192a of the first hose 190a, using coupling 194, thereby re-establishing air flow communication between the cleaning head 134 and the surface cleaning unit 116.

Referring to FIG. 13, the coupling 194 may be any suitable connector, and in the example illustrated, is an elbow-type connector with a downstream opening 195 surrounded by a sealing face 196. The surface cleaning unit 116 may be configured such that the upstream end 193b of the second hose 190b is aligned with the opening 195 and seals against seal face 196 to establish the air flow path when the surface cleaning unit 116 is placed on base 158. Accordingly, sealing face 196 is sealed by the inlet end 193b automatically when the surface cleaning unit 116 is inserted vertically onto the base 158.

In order to provide a seal, one or both of base 158 and surface cleaning unit 116 may be configured to provide sufficient abutment therebetween so that an air tight seal is created. As exemplified in FIG. 13, the rear face of coupling 194 is angled and a mating angled surface may be provided on portable cleaning unit 116. Accordingly, when portable cleaning unit is placed on base 158, portable cleaning unit is urged rearwardly and the rear end of portable cleaning unit 116 may abut the rear wall of base 158 thereby pressing the upstream end 193b of the second hose 190b against the opening 195 and optionally compressing a gasket or the like to create an air tight seal.

If the cyclone bin assembly is removable, then the remaining body of portable cleaning unit 116 may also or alternately be angled to press the cyclone inlet 524 against opening 195 (see for example FIG. 19).

Valve to Switch Between Hoses

The following is a description of alternate air flow paths that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

In accordance with this aspect, the portable cleaning unit may incorporate a hose which is different to first hose 190a. For example, it may have a smaller diameter. Accordingly, it may be preferred not to use such a hose in the air flow path when portable cleaning unit 116 is mounted on the base since the smaller diameter hose would reduce air flow and increase the back pressure. However, the smaller diameter hose may be lighter and easier to use in a portable mode (i.e., when surface cleaning unit 116 is removed from base 158). In such a case, a valve may be provided to selective connect the cyclone air inlet with the different hoses or air flow paths. The valve may be manually operable or automatically operable. For example, the valve may be actuated automatically when the surface cleaning unit 116 is removed from the base or when the smaller diameter hose is deployed from a storage position for use.

Accordingly, if second hose 190b has a smaller diameter into the air flow path when the surface cleaning unit 116 is docked, a user may optionally detach the downstream end

192b of the second hose **190a** from the air inlet **124** (thereby removing the second hose **190b** from the air flow circuit) and can reposition the downstream end **192a** of the hose **190a** to be connected directly to the inlet **124**. Alternately, inlet **124** could be automatically connected in air flow communication with opening **195** when surface cleaning unit **116** is placed on base **158**.

Optionally, instead requiring a user to reconfigure a hose, the surface cleaning apparatus may include a valve positioned in the air flow path that allows the air flow to be switched between the first and second hoses. In this configuration, both hoses can remain attached to their respective components, and the air flow path to the surface cleaning unit **116** can include either of the first and second hoses. Optionally, one of the hoses may be detachable and connectable to the other of the hoses, such that one large hose is created and forms the air flow path to the surface cleaning unit.

Referring to FIGS. **15** and **16**, a schematic representation of another embodiment of a surface cleaning apparatus **210** is illustrated. Surface cleaning apparatus **210** is generally similar to apparatus **10**, and analogous features are identified using like reference characters indexed by **200**.

In this embodiment, the surface cleaning unit **216** includes a valve **297** provided in the air flow path, upstream from the air inlet of the cyclone chamber **218**. The valve is connected to the downstream end **292b** of the second hose **290b**, and the valve **297** and second hose **290b** are removable with the surface cleaning unit **216** (FIG. **16**). When the surface cleaning unit **216** is seated on base **258**, the valve can connect to coupling **294** automatically or manually. An actuating lever **298** allows a user to change to position of the valve **297** so that, when the surface cleaning unit **216** is docked, the first hose **290a** is connected in air flow communication with the surface cleaning unit **216** and the second hose **290b** is sealed (but remains attached and does not require re-configuration). Optionally, the valve **297** can be automatically actuated when the surface cleaning unit **216** is placed on or removed from the base **258** to adjust the air flow path accordingly.

Use of Dual Suction Motors

The following is a description of the use of dual suction motors that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Optionally, the base of the surface cleaning apparatus may include some operating components of the surface cleaning apparatus, including, for example a suction motor, the power cord and a cord reel. Providing components in the base may help reduce the weight and/or overall size of the portable surface cleaning unit.

Referring to FIG. **17**, a schematic representation of another embodiment of a surface cleaning apparatus **310** is shown. The surface cleaning apparatus **310** is generally similar to surface cleaning apparatus **10**, and analogous features are identified using like reference characters indexed by **300**.

In the illustrated embodiment, the surface cleaning apparatus **310** includes a base **358** and a surface cleaning unit **316** that can be mounted on the base **358** (as illustrated), and can be detached to be used separately from the base **358**.

The surface cleaning unit **316** includes a cyclone bin assembly **388** that has a cyclone chamber **318** and a dirt collection chamber **330**. The cyclone chamber **318** has an air inlet **324** and an air outlet **328**. A dirt outlet in the form of a slot **326** provides communication between the cyclone chamber **318** and the dirt collection chamber **330**.

A first suction motor **320a** is provided in the surface cleaning unit **316**. An air flow conduit **400** provides an air flow path between the air outlet of the pre-motor filter housing and the suction motor **320a**. Accordingly, a pre-motor filter **338** is provided in the air flow path between the air outlet **328** of the cyclone chamber **318** and the motor **320a**.

In the illustrated embodiment the electrical cord **401** is wound around a cord reel **402** that is provided in the base **358**. In addition, a second suction motor **320b** is provided in the base **358** and is in electrical communication with the power cord **401** such that the second suction motor **358** can be powered by an external power supply (e.g. a wall socket). A base conduit **403** provides air flow communication between the second suction motor **320b** and a port **404** on the upper surface of the base **358**.

When the surface cleaning unit **316** is mounted on the base **358**, a mating port **406** on the surface cleaning unit **316** may connect to and seal the port **404**. Preferably, a valve **407** (e.g. any suitable valve such as a two position valve and a ball valve) is provided, e.g., in the air flow path between the filter **338** and the motor **320a**. The valve **407** is also in air flow communication with the port **406**, and is operable to selectively connect either port **406** or conduit **400** in air flow communication with the cyclone bin assembly **388**. When conduit **400** is connected, suction motor **320a** may be used draw air through the surface cleaning unit **316** (and preferably motor **320b** is not). When port **406** is connected, suction motor **320b** may be used to draw air through the surface cleaning unit **316** (and preferably motor **320a** is not). Preferably, the valve **407** is configured (for example via a biasing member or linkage member) so that when the surface cleaning unit **316** is lifted off the base **358** the valve **407** automatically seals port **406** and connects conduit **400**.

It will be appreciated that valve may be actuatable by other means, such as a member that is drivingly connected to the valve and the member is operable as the surface cleaning unit is paced and or removed from base **358**. It will be appreciated that motor **320b** may be connected in air flow communication at an alternate location. For example, it could be downstream of motor **320a**. Alternately, it could be a dirty air motor and located upstream of cyclone chamber **318**.

Because the electrical cord **401** is provided in the base **358**, when the surface cleaning unit **316** is detached from the base **358**, it may no longer be connected to the external power source (e.g. wall socket). To provide power to the surface cleaning unit **316** when it is detached, the surface cleaning unit **316** includes an on-board energy storage member, e.g., one or more batteries **405**. Alternatively, any other suitable energy storage member or power source can be used (fuel cell, combustion engine, solar cells, etc.). In the illustrated example, the batteries **405** provide DC power. In this configuration, when the surface cleaning unit **316** is detached from base **358**, the suction motor **320a** may operate using DC power, and may operate solely on the power supplied by batteries **405**.

Optionally, when the surface cleaning unit **316** is re-attached to the base **358**, power from the base **358** can be transferred to the surface cleaning unit **316**, for example via detachable electrical connector **408**. Preferably, if an electrical connector **408** is provided the power received from the base **358** can be used to charge the batteries **405** to help ensure the batteries **405** are charged when the surface cleaning unit **316** is removed.

Alternatively, there need not be an electrical connection between the base **358** and the surface cleaning unit **316**. In

such a configuration the batteries **405** may be charged via an alternate power source, or may be replaced with fresh batteries as needed. For example, the surface cleaning unit **116** may be provided with its own power cord, or the power cord **401** may be removable from base **358** and may be plugged into surface cleaning unit **116**.

Optionally, the suction motor **320a** may be smaller and/or less powerful than the suction motor **320b**. Making the suction motor **320a** smaller and lighter than suction motor **320b** may help reduce the overall size and weight of the surface cleaning unit **316**. For example, the suction motor **320b** may be a **1000** watt motor, and the suction motor **320a** may be a **600** watt motor. Reducing the power consumption of the suction motor **320a** may also help prolong the amount of cleaning time that can be achieved using the batteries **405**, before they need to be replaced and/or recharged.

In the illustrated embodiment, because suction motor **320b** is in the base **358** with the electrical cord, it may be an AC motor that can run on AC power received from a wall socket. Motor **320a** may be operated on DC power supplied by the batteries **405**.

In this configuration, a user may be able to select which suction motor **320a** or **320b** is to be used when the surface cleaning unit **316** is docked. For example, if performing a small job or if it is desirable to keep the noise level low a user may activate the smaller suction motor **320a**. Alternatively, if performing a large job a user may select to use the suction motor **320b** by activating the motor **320b** and positioning the valve **407** as appropriate.

Dual Operational Mode for a Portable Surface Cleaning Unit

The following is a description of the use of a dual operational mode for a portable surface cleaning unit that may be used by itself in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features disclosed herein.

Alternately, or in addition to providing a motor **320b** in the base **358**, the suction motor **320a** in the surface cleaning unit may be operable on current supplied by an on board energy storage member (e.g., batteries **405**) when removed from base **358** and may be operable on current supplied from base **358** when mounted thereon.

Accordingly, when removed from the base **358**, motor **320a** may be operable on DC current supplied from batteries **405**. However, when mounted on the base **358** and electrical code **401** is plugged into an electrical outlet, current may be supplied from base **358** to motor **320a**. The current may be AC, in which case, motor **320a** may be operable on both AC and DC current (e.g., it has dual windings) or the AC current may be converted to DC current (such as by providing a power supply in one or both of the base **358** and the surface cleaning unit **116**).

Accordingly, for example, as shown in FIG. **17**, an electrical connector **408** may be used to power the suction motor **320a** when the surface cleaning apparatus is docked on the base **358**. In this configuration the suction motor **320a** may be configured to also run on AC power or a power supply or converter module **409** may be provided to convert the incoming AC power to DC power. Optionally, the convertor module **409** may be in the base **358** so that the connector **408** is provided with DC power.

It will be appreciated that the suction motor of the portable cleaning unit may be operable on different power levels. It may be operable on a first or higher power level when mounted to the base and operable on power supplied from the base (which may be AC or DC). It may be operable on a lower power level when removed from the base.

It will be appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments or separate aspects, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment or aspect, may also be provided separately or in any suitable sub-combination.

What has been described above has been intended to be illustrative of the invention and non-limiting and it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

The invention claimed is:

1. A surface cleaning apparatus having wheels, the surface cleaning apparatus comprising:

- (a) an air flow passage extending from a dirty air inlet to a clean air outlet;
- (b) a portable cleaning unit removably mounted to a remainder of the surface cleaning apparatus, the portable cleaning unit comprising a cyclone bin assembly positioned in the air flow passage and having a longitudinal axis defining a longitudinal direction, a top end and a longitudinally spaced apart openable bottom end, the cyclone bin assembly comprising a cyclone chamber and a separated material collection chamber, a divider plate is located at a lower end of the cyclone chamber at a location of a dirty material outlet of the cyclone chamber;
- (c) a screen positioned in the air flow passage, the screen having an upper end and a bottom;
- (d) a suction motor positioned in the air flow passage downstream from the screen; and,
- (e) an openable lid provided on an upper end of the surface cleaning apparatus,

wherein, subsequent to the lid being moved to an open position, the screen is removable upwardly from the cyclone bin assembly while the portable cleaning unit is mounted to the remainder of the surface cleaning apparatus, and,

wherein, when positioned in the cyclone bin assembly, the screen is suspended in the cyclone bin assembly from a fixed wall of the cyclone bin assembly and the bottom of the screen is spaced from the divider plate such that a volume defined between a central portion of the bottom of the screen and the divider plate is contiguous with a remainder of the cyclone chamber.

2. The surface cleaning apparatus of claim **1** wherein the fixed wall has an opening and the screen is slidably receivable in the opening.

3. The surface cleaning apparatus of claim **2** wherein the screen comprises a rim which seats on an upper surface of a wall defining the opening.

4. The surface cleaning apparatus of claim **1** wherein the cyclone bin assembly comprises a cyclone chamber and a dirt collection chamber, and the apparatus further comprises an openable bottom end that comprises a floor of the dirt collection chamber.

5. A surface cleaning apparatus having wheels, the surface cleaning apparatus comprising:

- (a) an air flow passage extending from a dirty air inlet to a clean air outlet;
- (b) a portable cleaning unit removably mounted to a remainder of the surface cleaning apparatus, the portable cleaning unit comprising a cyclone bin assembly

positioned in the air flow passage and having a longitudinal axis defining a longitudinal direction, a top end and a longitudinally spaced apart openable bottom end, the cyclone bin assembly comprising a cyclone chamber and a separated material collection chamber, a divider plate is located at a lower end of the cyclone chamber at a location of a dirty material outlet of the cyclone chamber;

(c) a physical filtration member positioned in the air flow passage; and,

(d) a suction motor positioned in the air flow passage downstream from the physical filtration member; and,

(e) an openable lid provided on an upper end of the surface cleaning apparatus,

wherein, subsequent to the lid being moved to an open position, the physical filtration member is removable upwardly from the cyclone bin assembly while the portable cleaning unit is mounted to the remainder of the surface cleaning apparatus, and,

wherein, when positioned in the cyclone bin assembly, the physical filtration member is suspended in the cyclone bin assembly from the top end of the cyclone bin assembly and the bottom of the physical filtration member is spaced from the divider plate such that a volume defined between a central portion of the bottom of the physical filtration member and the divider plate is contiguous with a remainder of the cyclone chamber.

6. The surface cleaning apparatus of claim 5 wherein the top end has an opening and the physical filtration member is slidably receivable in the opening.

7. The surface cleaning apparatus of claim 6 wherein the physical filtration member comprises a rim which seats on an upper surface of a wall defining the opening.

8. The surface cleaning apparatus of claim 5 wherein the cyclone bin assembly comprises a cyclone chamber and a dirt collection chamber, and the apparatus further comprises an openable bottom end that comprises a floor of the dirt collection chamber.

* * * * *