

US011192122B2

(12) **United States Patent**
Conrad

(10) **Patent No.:** **US 11,192,122 B2**
(45) **Date of Patent:** **Dec. 7, 2021**

(54) **CYCLONIC AIR TREATMENT MEMBER AND SURFACE CLEANING APPARATUS INCLUDING THE SAME**

(71) Applicant: **Omachron Intellectual Property Inc., Hampton (CA)**

(72) Inventor: **Wayne Ernest Conrad, Hampton (CA)**

(73) Assignee: **Omachron Intellectual Property Inc., Hampton (CA)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 307 days.

(21) Appl. No.: **16/529,406**

(22) Filed: **Aug. 1, 2019**

(65) **Prior Publication Data**
US 2020/0047192 A1 Feb. 13, 2020

Related U.S. Application Data
(63) Continuation-in-part of application No. 16/101,770, filed on Aug. 13, 2018, now Pat. No. 11,013,384.

(51) **Int. Cl.**
B04C 5/185 (2006.01)
A47L 9/16 (2006.01)
B04C 5/04 (2006.01)
B04C 9/00 (2006.01)

(52) **U.S. Cl.**
CPC **B04C 5/185** (2013.01); **A47L 9/1608** (2013.01); **A47L 9/1666** (2013.01); **A47L 9/1683** (2013.01); **B04C 5/04** (2013.01); **B04C 9/00** (2013.01); **B04C 2009/004** (2013.01)

(58) **Field of Classification Search**
CPC A47L 9/1608; A47L 9/1666; A47L 9/1683; A47L 9/2884; B04C 2009/004; B04C 3/06; B04C 5/04; B04C 5/185; B04C 9/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

911,258 A 2/1909 Neumann
1,505,741 A * 8/1924 Stebbins B07B 7/08
209/135

1,600,762 A 9/1926 Hawley
1,797,812 A 3/1931 Waring
1,898,608 A 2/1933 William
1,937,765 A 12/1933 Ward

(Continued)

FOREIGN PATENT DOCUMENTS

AU 112778 4/1940
CA 1077412 A1 5/1980

(Continued)

OTHER PUBLICATIONS

English machine translation of CN101095604A published on Jan. 2, 2008.

(Continued)


Primary Examiner — Marc Carlson

(74) *Attorney, Agent, or Firm* — Philip C. Mendes da Costa; Bereskin & Parr LLP/S.E.N.C.R.L, s.r.l.

(57) **ABSTRACT**

A cyclonic air treatment member comprises a cyclone and a dirt collection chamber external to the cyclone chamber. The cyclone chamber extends longitudinally in an axial direction between a cyclone first end and a cyclone second end. The cyclone chamber includes an axially extending dirt outlet. A removable dirt outlet insert member may be removably receivable by a portion of the dirt outlet.

20 Claims, 49 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,015,464 A	9/1935	Saint	5,254,019 A	10/1993	Noschese
2,152,114 A	3/1939	Van Tongeren	5,267,371 A	12/1993	Soler et al.
2,542,634 A	2/1951	Davis et al.	5,287,591 A	2/1994	Rench et al.
2,678,110 A	5/1954	Madsen	5,307,538 A	5/1994	Rench et al.
2,731,102 A	1/1956	James	5,309,600 A	5/1994	Weaver et al.
2,811,219 A	10/1957	Josef	5,309,601 A	5/1994	Hampton et al.
2,846,024 A	8/1958	Theodor	5,347,679 A	9/1994	Saunders et al.
2,913,111 A	11/1959	Rogers	5,363,535 A	11/1994	Rench et al.
2,917,131 A	12/1959	Evans	5,481,780 A	1/1996	Daneshvar
2,937,713 A	5/1960	Stephenson et al.	5,515,573 A	5/1996	Frey
2,942,691 A	6/1960	Dillon	5,599,365 A	2/1997	Alday et al.
2,942,692 A	6/1960	August	D380,033 S	6/1997	Masterton et al.
2,946,451 A	7/1960	Culleton	5,709,007 A	1/1998	Chiang
2,952,330 A	9/1960	Winslow	5,755,096 A	5/1998	Holleyman
2,981,369 A	4/1961	Yellott et al.	5,815,878 A	10/1998	Murakami et al.
3,002,215 A	10/1961	MacFarland	5,815,881 A	10/1998	Sjoegreen
3,032,954 A	5/1962	Racklyeft	5,858,038 A	1/1999	Dyson et al.
3,085,221 A	4/1963	Kelly	5,858,043 A	1/1999	Geise
3,130,157 A	4/1964	Kelsall et al.	5,893,938 A	4/1999	Dyson et al.
3,200,568 A	8/1965	McNeil	5,935,279 A	8/1999	Kilstrom
3,204,772 A	9/1965	Ruxton	5,950,274 A	9/1999	Kilstrom
3,217,469 A	11/1965	Eckert	5,970,572 A	10/1999	Thomas
3,269,097 A	8/1966	German	6,058,559 A	5/2000	Yoshimi et al.
3,320,727 A	5/1967	Farley et al.	6,071,095 A	6/2000	Verkaar
3,372,532 A	3/1968	Langdon	6,071,321 A	6/2000	Trapp et al.
3,426,513 A	2/1969	Bauer	6,080,022 A	6/2000	Shaberman et al.
3,518,815 A	7/1970	Peterson et al.	6,122,796 A	9/2000	Downham et al.
3,530,649 A	9/1970	Porsch et al.	6,171,356 B1	1/2001	Twerdun
3,543,325 A	12/1970	Hamrick et al.	6,210,469 B1	4/2001	Tokar
3,561,824 A	2/1971	Homan	6,221,134 B1	4/2001	Conrad et al.
3,582,616 A	6/1971	Wrob	6,228,260 B1	5/2001	Conrad et al.
3,675,401 A	7/1972	Cordes	6,231,645 B1	5/2001	Conrad et al.
3,684,093 A	8/1972	Kono	6,251,296 B1	6/2001	Conrad et al.
3,766,558 A	10/1973	Kuechken	6,260,234 B1	7/2001	Wright et al.
3,822,533 A	7/1974	Oranje	6,345,408 B1	2/2002	Nagai et al.
3,870,486 A	3/1975	Eriksson et al.	6,406,505 B1	6/2002	Oh et al.
3,877,902 A	4/1975	Eriksson et al.	6,434,785 B1	8/2002	Vandenbelt et al.
3,898,068 A	8/1975	McNeil et al.	6,440,197 B1	8/2002	Conrad et al.
3,933,450 A	1/1976	Percevaut	6,502,278 B2	1/2003	Oh et al.
3,988,132 A	10/1976	Oranje	6,519,810 B2	2/2003	Kim
3,988,133 A	10/1976	Schady	6,531,066 B1	3/2003	Saunders et al.
4,097,381 A	6/1978	Ritzler	6,553,612 B1	4/2003	Dyson et al.
4,187,088 A	2/1980	Hodgson	6,553,613 B2	4/2003	Onishi et al.
4,218,805 A	8/1980	Brazier	6,560,818 B1	5/2003	Hasko
4,236,903 A	12/1980	Malmsten	6,572,668 B1	6/2003	An et al.
4,307,485 A	12/1981	Dessig	6,581,239 B1	6/2003	Dyson et al.
4,373,228 A	2/1983	Dyson	6,599,338 B2	7/2003	Oh et al.
4,382,804 A	5/1983	Mellor	6,599,350 B1	7/2003	Rockwell et al.
4,383,917 A *	5/1983	Wells B04C 1/00 209/723	6,613,316 B2	7/2003	Rockwell et al.
4,409,008 A	10/1983	Solymes	6,623,539 B2	9/2003	Sun et al.
4,486,207 A	12/1984	Baillie	6,625,845 B2	9/2003	Lee et al.
4,494,270 A	1/1985	Ritzau et al.	6,640,385 B2	9/2003	Matsumoto et al.
4,523,936 A	6/1985	Disanza, Jr.	6,648,934 B2	11/2003	Oh et al.
4,678,588 A *	7/1987	Shortt B01D 45/16 209/459	6,648,934 B2	11/2003	Choi et al.
4,700,429 A	10/1987	Martin et al.	6,712,868 B2	3/2004	Murphy et al.
4,744,958 A	5/1988	Pircon	6,732,403 B2	5/2004	Moore et al.
4,778,494 A	10/1988	Patterson	6,746,500 B1	6/2004	Park et al.
4,803,753 A	2/1989	Palmer	6,782,583 B2	8/2004	Oh
4,826,515 A	5/1989	Dyson	6,782,585 B1	8/2004	Conrad et al.
D303,173 S	8/1989	Masakata et al.	6,810,558 B2	11/2004	Lee
4,853,008 A	8/1989	Dyson	6,818,036 B1	11/2004	Seaman
4,853,011 A	8/1989	James	6,833,015 B2	12/2004	Oh et al.
4,853,111 A	8/1989	MacArthur et al.	6,868,578 B1	3/2005	Kasper
4,905,342 A	3/1990	Ataka	6,874,197 B1	4/2005	Conrad
4,944,780 A	7/1990	Usmani	6,896,719 B2	5/2005	Coates et al.
4,980,945 A	1/1991	Bewley	6,929,516 B2	8/2005	Brochu et al.
5,054,157 A	10/1991	Werner et al.	6,968,596 B2	11/2005	Oh et al.
5,078,761 A	1/1992	Dyson	6,976,885 B2	12/2005	Lord
5,080,697 A	1/1992	Finke	7,065,826 B1 *	6/2006	Arnold A47L 9/1608 15/353
5,090,976 A	2/1992	Dyson	7,105,035 B2	9/2006	Oh et al.
5,129,125 A	7/1992	Gamou et al.	7,113,847 B2	9/2006	Chumura et al.
5,224,238 A	7/1993	Bartlett	7,128,770 B2	10/2006	Oh et al.
5,230,722 A	7/1993	Yonkers	7,160,346 B2	1/2007	Park
			7,162,770 B2	1/2007	Davidshofer
			7,175,682 B2	2/2007	Nakai et al.
			7,198,656 B2	4/2007	Takemoto et al.
			7,210,195 B2	5/2007	Howie et al.
			7,222,393 B2	5/2007	Kaffenberger et al.
			7,272,872 B2	9/2007	Choi

(56)

References Cited

U.S. PATENT DOCUMENTS

7,278,181 B2	10/2007	Harris et al.	2002/0134059 A1	9/2002	Oh
7,341,611 B2	3/2008	Greene et al.	2002/0134238 A1	9/2002	Conrad et al.
7,354,468 B2	4/2008	Arnold et al.	2002/0178535 A1	12/2002	Oh et al.
7,370,387 B2	5/2008	Walker et al.	2002/0178698 A1	12/2002	Oh et al.
7,377,007 B2	5/2008	Best	2002/0178699 A1	12/2002	Oh
7,377,953 B2	5/2008	Oh	2003/0037403 A1	2/2003	Lang
7,386,915 B2	6/2008	Blocker et al.	2003/0046910 A1	3/2003	Lee
7,395,579 B2	7/2008	Oh	2003/0066273 A1	4/2003	Choi et al.
7,426,768 B2	9/2008	Peterson et al.	2003/0106180 A1	6/2003	Tsen
7,429,284 B2	9/2008	Oh	2003/0159238 A1	8/2003	Oh
7,448,363 B1	11/2008	Rasmussen et al.	2003/0159411 A1	8/2003	Hansen et al.
7,449,040 B2	11/2008	Conrad et al.	2003/0200736 A1	10/2003	Ni
7,485,164 B2	2/2009	Jeong et al.	2004/0010885 A1	1/2004	Hitzelberger et al.
7,488,363 B2	2/2009	Jeong et al.	2004/0025285 A1	2/2004	McCormick et al.
7,547,337 B2	6/2009	Oh	2004/0045126 A1	3/2004	Parker et al.
7,547,338 B2	6/2009	Kim et al.	2004/0088816 A1	5/2004	Shimizu et al.
7,563,298 B2	7/2009	Oh	2004/0103495 A1	6/2004	Oh
7,565,853 B2	7/2009	Arnold et al.	2004/0211025 A1	10/2004	Jung et al.
7,588,616 B2	9/2009	Conrad et al.	2004/0216264 A1	11/2004	Shaver et al.
7,597,730 B2	10/2009	Yoo et al.	2004/0237482 A1	12/2004	Lim et al.
7,601,188 B2	10/2009	Hwang et al.	2005/0081321 A1	4/2005	Milligan et al.
7,628,831 B2	12/2009	Gomiciaga-Pereda et al.	2005/0115409 A1	6/2005	Conrad
7,632,324 B2	12/2009	Makarov et al.	2005/0132528 A1	6/2005	Yau
7,691,161 B2	4/2010	Oh et al.	2005/0138763 A1	6/2005	Tanner et al.
7,717,973 B2	5/2010	Oh et al.	2005/0198769 A1	9/2005	Lee et al.
7,740,676 B2	6/2010	Burnham et al.	2005/0198770 A1	9/2005	Jung et al.
7,770,256 B1	8/2010	Fester	2005/0252179 A1	11/2005	Oh et al.
7,774,898 B2	8/2010	Hong et al.	2005/0252180 A1	11/2005	Oh et al.
7,776,120 B2	8/2010	Conrad	2006/0037172 A1	2/2006	Choi
7,779,506 B2	8/2010	Kang et al.	2006/0042206 A1	3/2006	Arnold et al.
7,803,207 B2	9/2010	Conrad	2006/0090290 A1	5/2006	Lau
7,805,804 B2	10/2010	Loebig	2006/0104349 A1	5/2006	Joch et al.
7,811,349 B2	10/2010	Nguyen	2006/0123590 A1	6/2006	Fester et al.
7,867,308 B2	1/2011	Conrad	2006/0137304 A1	6/2006	Jeong et al.
7,882,593 B2	2/2011	Beskow et al.	2006/0137306 A1	6/2006	Jeong et al.
7,922,794 B2	4/2011	Morphey	2006/0137309 A1	6/2006	Jeong et al.
7,931,716 B2	4/2011	Oakham	2006/0137314 A1	6/2006	Conrad et al.
7,934,286 B2	5/2011	Yoo et al.	2006/0156508 A1	7/2006	Khalil
7,938,871 B2	5/2011	Lloyd	2006/0162298 A1*	7/2006	Oh A47L 7/0004 55/337
7,958,598 B2	6/2011	Yun et al.	2006/0162299 A1	7/2006	North
7,979,959 B2	7/2011	Courtney	2006/0168922 A1	8/2006	Oh
7,996,956 B2	8/2011	Wood et al.	2006/0168923 A1	8/2006	Lee et al.
8,021,453 B2	9/2011	Howes	2006/0207055 A1	9/2006	Ivarsson et al.
8,062,398 B2	11/2011	Luo et al.	2006/0207231 A1	9/2006	Arnold
8,100,999 B2	1/2012	Ashbee et al.	2006/0230715 A1	10/2006	Oh et al.
8,101,001 B2	1/2012	Qian	2006/0230723 A1	10/2006	Kim et al.
8,117,712 B2	2/2012	Dyson et al.	2006/0230724 A1	10/2006	Han et al.
8,146,201 B2	4/2012	Conrad	2006/0236663 A1	10/2006	Oh
8,151,407 B2	4/2012	Conrad	2006/0254226 A1	11/2006	Jeon
8,152,877 B2	4/2012	Greene	2006/0278081 A1	12/2006	Han et al.
8,156,609 B2	4/2012	Milne et al.	2006/0288516 A1	12/2006	Sawalski
8,161,599 B2*	4/2012	Griffith B01D 45/16 15/353	2007/0067944 A1	3/2007	Kitamura
8,225,456 B2	7/2012	Håkan et al.	2007/0077810 A1	4/2007	Gogel
8,296,900 B2	10/2012	Conrad	2007/0079473 A1	4/2007	Min
8,484,799 B2*	7/2013	Conrad A47L 9/1608 15/353	2007/0079585 A1	4/2007	Oh et al.
8,578,555 B2	11/2013	Conrad	2007/0095028 A1	5/2007	Kim
8,601,641 B2	12/2013	Conrad	2007/0095029 A1	5/2007	Min
8,646,149 B2	2/2014	Conrad	2007/0136984 A1	6/2007	Hsu
8,673,487 B2	3/2014	Churchill	2007/0209334 A1	9/2007	Conrad
8,677,558 B2	3/2014	Conrad	2007/0209335 A1	9/2007	Conrad
8,813,305 B2	8/2014	Conrad	2007/0271724 A1	11/2007	Hakan et al.
8,869,344 B2	10/2014	Conrad	2007/0289089 A1	12/2007	Yacobi
8,978,198 B2	3/2015	Conrad	2007/0289266 A1*	12/2007	Oh A47L 9/1608 55/337
9,027,198 B2	5/2015	Conrad	2008/0040883 A1	2/2008	Beskow et al.
9,192,269 B2	11/2015	Conrad	2008/0047091 A1	2/2008	Nguyen
9,369,718 B2	6/2016	Lim et al.	2008/0063051 A1	3/2008	Kwon et al.
9,675,218 B2	6/2017	Kim et al.	2008/0134460 A1	6/2008	Conrad
2001/0015132 A1	8/2001	Rohn et al.	2008/0134462 A1	6/2008	Jansen et al.
2002/0011050 A1	1/2002	Hansen et al.	2008/0172821 A1	7/2008	Kang et al.
2002/0011053 A1	1/2002	Oh	2008/0178416 A1	7/2008	Conrad
2002/0062531 A1	5/2002	Oh	2008/0178418 A1	7/2008	Conrad
2002/0088208 A1	7/2002	Lukac et al.	2008/0178420 A1	7/2008	Conrad
2002/0112315 A1	8/2002	Conrad	2008/0190080 A1	8/2008	Oh et al.
			2008/0196194 A1	8/2008	Conrad
			2008/0196196 A1	8/2008	Conrad
			2008/0196745 A1	8/2008	Conrad
			2008/0216282 A1	9/2008	Conrad

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0289139 A1 11/2008 Makarov et al.
 2008/0301903 A1 12/2008 Cunningham et al.
 2009/0044372 A1 2/2009 Knopow et al.
 2009/0056060 A1 3/2009 Han et al.
 2009/0100633 A1 4/2009 Bates et al.
 2009/0113659 A1 5/2009 Jeon
 2009/0144932 A1 6/2009 Yoo
 2009/0165431 A1 7/2009 Oh
 2009/0173365 A1 7/2009 Conrad
 2009/0205160 A1 8/2009 Conrad
 2009/0205161 A1 8/2009 Conrad
 2009/0205298 A1* 8/2009 Hyun A47L 9/165
 55/343
 2009/0209666 A1 8/2009 Hellberg et al.
 2009/0265877 A1 10/2009 Dyson et al.
 2009/0282639 A1 11/2009 Dyson et al.
 2009/0300874 A1 12/2009 Tran et al.
 2009/0300875 A1 12/2009 Inge et al.
 2009/0305862 A1 12/2009 Yoo
 2009/0307564 A1 12/2009 Vedantham et al.
 2009/0307863 A1 12/2009 Milne et al.
 2009/0307864 A1 12/2009 Dyson
 2009/0308254 A1 12/2009 Oakham
 2009/0313958 A1 12/2009 Gomiciaga-Pereda et al.
 2009/0313959 A1 12/2009 Gomiciaga-Pereda et al.
 2010/0017997 A1 1/2010 Beskow et al.
 2010/0083459 A1 4/2010 Beskow et al.
 2010/0132319 A1 6/2010 Ashbee et al.
 2010/0154150 A1 6/2010 McLeod
 2010/0175217 A1 7/2010 Conrad
 2010/0212104 A1 8/2010 Conrad
 2010/0224073 A1* 9/2010 Oh A47L 9/1666
 96/416
 2010/0229321 A1 9/2010 Dyson et al.
 2010/0229328 A1 9/2010 Conrad
 2010/0242210 A1 9/2010 Conrad
 2010/0243158 A1 9/2010 Conrad
 2010/0293745 A1 11/2010 Coburn
 2010/0299865 A1 12/2010 Conrad
 2010/0299866 A1 12/2010 Conrad
 2011/0023261 A1 2/2011 Proffitt, II et al.
 2011/0096829 A1 4/2011 Han et al.
 2011/0146024 A1 6/2011 Conrad
 2011/0168332 A1 7/2011 Bowe et al.
 2011/0219572 A1 9/2011 Conrad
 2011/0219574 A1 9/2011 Conrad
 2011/0219576 A1* 9/2011 Conrad A47L 9/1683
 15/347
 2011/0289719 A1 12/2011 Han et al.
 2012/0000030 A1 1/2012 Conrad
 2012/0023701 A1 2/2012 Lenkiewicz et al.
 2012/0030896 A1 2/2012 Crouch et al.
 2012/0060322 A1 3/2012 Simonelli et al.
 2012/0079671 A1 4/2012 Stickney et al.
 2012/0177109 A1 7/2012 Ye et al.
 2012/0189049 A1 7/2012 Coban et al.
 2012/0216361 A1 8/2012 Millington et al.
 2012/0222245 A1 9/2012 Conrad
 2012/0222260 A1 9/2012 Conrad
 2012/0222262 A1 9/2012 Conrad
 2013/0058417 A1 3/2013 Ikai
 2013/0091662 A1 4/2013 Smith
 2013/0160232 A1 6/2013 Peace
 2013/0227813 A1* 9/2013 Conrad B01D 46/00
 15/353
 2014/0137362 A1 5/2014 Smith
 2014/0137363 A1 5/2014 Wilson
 2014/0137364 A1 5/2014 Stickney et al.
 2014/0182080 A1 7/2014 Lee et al.
 2014/0208538 A1 7/2014 Visel et al.
 2014/0237758 A1 8/2014 Conrad
 2014/0237759 A1* 8/2014 Conrad A47L 5/32
 15/344
 2014/0237956 A1 8/2014 Conrad

2015/0135474 A1 5/2015 Gidwell
 2015/0230677 A1* 8/2015 Andrikanish A47L 9/102
 15/353
 2015/0297050 A1 10/2015 Marsh et al.
 2018/0177353 A1* 6/2018 Conrad A47L 9/1608
 2018/0353032 A1* 12/2018 Conrad A47L 9/165
 2020/0046190 A1* 2/2020 Conrad A47L 9/2884
 2020/0047192 A1* 2/2020 Conrad A47L 9/1683
 2020/0077854 A1* 3/2020 Conrad A47L 5/24
 2020/0122161 A1* 4/2020 Conrad A47L 9/1625
 2020/0163508 A1* 5/2020 Percy-Raine A47L 9/149
 2020/0305668 A1* 10/2020 Conrad A47L 9/165

FOREIGN PATENT DOCUMENTS

CA 1218962 A 3/1987
 CA 2450450 A1 12/2004
 CA 2484587 A1 4/2005
 CA 2438079 C 8/2009
 CA 2658014 A1 9/2010
 CA 2659212 A1 9/2010
 CA 2593950 C 1/2013
 CN 1336154 A 2/2002
 CN 1434688 A 8/2003
 CN 1493244 A 5/2004
 CN 2657570 Y 11/2004
 CN 1626025 A 6/2005
 CN 1875846 A 12/2006
 CN 1875855 A 12/2006
 CN 1887437 A 1/2007
 CN 1895148 A 1/2007
 CN 101061932 A 10/2007
 CN 101095604 A 1/2008
 CN 101108081 A 1/2008
 CN 101108106 A 1/2008
 CN 101108110 A 1/2008
 CN 101489461 A 2/2009
 CN 201223346 Y 4/2009
 CN 101448447 A 6/2009
 CN 101489453 A 7/2009
 CN 101489455 A 7/2009
 CN 101489457 A 7/2009
 CN 201290642 Y 8/2009
 CN 101822506 A 9/2010
 CN 201683850 U 12/2010
 CN 102188208 A 9/2011
 CN 102256523 A 11/2011
 CN 102587312 A* 7/2012
 CN 202932850 U 5/2013
 CN 203724037 U 7/2014
 DE 875134 C 4/1953
 DE 9017798 U1 3/1992
 DE 9216071.9 U1 2/1993
 DE 4232382 C1 3/1994
 DE 10056935 C2 1/2003
 DE 69907201 T2 2/2004
 DE 60201666 T2 6/2006
 DE 60211663 T2 5/2007
 DE 102007011457 A1 10/2007
 DE 112010001135 T5 8/2012
 DE 202010018047 U1 11/2013
 DE 102012211246 A1 1/2014
 DE 202010018084 U1 2/2014
 DE 202010018085 U1 2/2014
 EP 0489489 A1 6/1992
 EP 493950 B1 7/1992
 EP 1031310 A2 8/2000
 EP 1200196 B1 6/2005
 EP 1779761 A2 5/2007
 EP 1815777 A1 8/2007
 EP 1594386 B1 4/2009
 EP 1676516 B1 1/2010
 EP 2308360 A2 4/2011
 EP 1674017 B1 7/2011
 EP 1535560 B1 3/2013
 EP 1629758 A3 10/2013
 EP 2848173 A1 3/2015
 FR 2812531 B1 11/2004
 GB 700791 A 12/1953

(56)

References Cited

FOREIGN PATENT DOCUMENTS

GB	1029943	A	5/1966	
GB	1111074	A	4/1968	
GB	2035787	B	10/1982	
GB	2163703	B	1/1988	
GB	2268875	A	1/1994	
GB	2307849	A	6/1997	
GB	2282979	B	10/1997	
GB	2365324	B	7/2002	
GB	2372431	B	9/2004	
GB	2465781	A	6/2010	
GB	2441962	B	3/2011	
GB	2466290	B	10/2012	
GB	2508035		5/2014	
JP	61131720	A	6/1986	
JP	2000140533	A	5/2000	
JP	2003135335	A	5/2003	
JP	2003180579	A	7/2003	
JP	2005040246	A	2/2005	
JP	2009261501	A	11/2009	
JP	2010081968	A	4/2010	
JP	2010178773	A	8/2010	
JP	2010220632	A	10/2010	
JP	2011189132	A	9/2011	
JP	2011189133	A	9/2011	
KR	1020010045598	A	6/2001	
KR	1020020067489	A	8/2002	
KR	1020020085478	A	11/2002	
KR	1020040050174	A	6/2004	
KR	1020060008365	A	1/2006	
KR	1020060118795	A	11/2006	
KR	1020060118800	A	11/2006	
KR	1020060118802	A	11/2006	
KR	1020060118803	A	11/2006	
WO	1980002561	A1	11/1980	
WO	9627446	A1	9/1996	
WO	97/20492	A1	6/1997	
WO	9809121	A1	3/1998	
WO	9843721	A1	10/1998	
WO	01/07168	A1	2/2001	
WO	0112050	A1	2/2001	
WO	2002017766	A3	3/2002	
WO	2004069021	A1	8/2004	
WO	2004093631	A1	11/2004	
WO	2006026414	A3	8/2007	
WO	WO-2007093123	A1 *	8/2007 B01D 45/16
WO	2007104238	A1	9/2007	
WO	2008009883	A1	1/2008	
WO	2008009888	A1	1/2008	
WO	2008009890	A1	1/2008	
WO	2008009891	A1	1/2008	
WO	2008070962	A1	6/2008	
WO	2008088278	A2	7/2008	
WO	2009026709	A1	3/2009	
WO	2010102396	A1	9/2010	
WO	2010142968	A1	12/2010	
WO	2010142969	A1	12/2010	
WO	2010142970	A1	12/2010	
WO	2010142971	A1	12/2010	
WO	2011054106	A1	5/2011	
WO	2012042240	A1	4/2012	
WO	2012117231	A1	9/2012	

OTHER PUBLICATIONS

English machine translation of CN101108081A published on Jan. 23, 2008.
 English machine translation of CN101108110A published on Jan. 23, 2008.
 English machine translation of CN101448447A published on Jun. 3, 2009.
 English machine translation of CN101489453A published on Jul. 22, 2009.
 English machine translation of CN101489455A published on Jul. 22, 2009.

English machine translation of CN101489457A published on Jul. 22, 2009.
 English machine translation of CN101108106A published on Jan. 23, 2008.
 English machine translation of CN101489461A published on Feb. 22, 2009.
 English machine translation of CN101822506A published on Sep. 8, 2010.
 English machine translation of CN102188208A published on Sep. 21, 2011.
 English machine translation of CN102256523A published on Nov. 23, 2011.
 English machine translation of CN1336154A published on Feb. 20, 2002.
 English machine translation of CN1434688A published on Aug. 6, 2003.
 English machine translation of CN1626025A published on Jun. 15, 2005.
 English machine translation of CN1875846A published on Dec. 13, 2006.
 English machine translation of CN1875855A published on Dec. 13, 2006.
 English machine translation of CN1895148A published on Jan. 17, 2007.
 English machine translation of CN201290642Y published on Aug. 19, 2009.
 English machine translation of CN201683850U published on Dec. 29, 2010.
 English machine translation of CN203724037U published on Jul. 23, 2014.
 English machine translation of DE10056935C2 published on Jan. 16, 2003.
 English machine translation of DE102007011457A1 published on Oct. 25, 2007.
 English machine translation of DE102012211246A1 published on Jan. 2, 2014.
 English machine translation of DE112010001135T5 published on Aug. 2, 2012.
 English machine translation of DE202010018047U1 published on Nov. 14, 2013.
 English machine translation of DE202010018084U1 published on Feb. 27, 2014.
 English machine translation of DE202010018085U published on Feb. 27, 2014.
 English machine translation of DE60201666T2 published on Jun. 1, 2006.
 English machine translation of DE60211663T2 published on May 10, 2007.
 English machine translation of DE69907201T2 published on Feb. 5, 2004.
 English machine translation of JP2003135335A published on May 13, 2003.
 English machine translation of JP2005040246A published on Feb. 17, 2005.
 English machine translation of JP2009261501A published on Nov. 12, 2009.
 English machine translation of JP2010081968A published on Apr. 15, 2010.
 English machine translation of KR1020010045598A published on Jun. 5, 2001.
 English machine translation of KR1020020067489A published on Aug. 2, 2002.
 English machine translation of KR1020020085478A published on Nov. 16, 2002.
 English machine translation of KR1020040050174A published on Jun. 16, 2004.
 English machine translation of KR1020060008365A published on Jan. 26, 2006.
 English machine translation of KR1020060118795A published on Nov. 24, 2006.
 English machine translation of KR1020060118800A published on Nov. 24, 2006.

(56)

References Cited

OTHER PUBLICATIONS

English machine translation of KR1020060118802A published on Nov. 24, 2006.
English machine translation of KR1020060118803A published on Nov. 24, 2006.
Euro-Pro Shark Cordless Hand Vac Owner's Manual, published in 2002.
Handbook of Air Pollution Prevention and Control, pp. 397-404, 2002.
Instructions manual: Makita Cordless Cleaner, Makita 4071D, Handy Vac II, Instructions Manual, dated at least as early as 1993.
Makita BCL180 User Manual, specification according to EPTA Procedure, dated at least as early as Jan. 2003.
English machine translation of JP2011189133, published on Sep. 29, 2011.
English machine translation of JP2010220632, published on Oct. 7, 2010.
English machine translation of JP2010178773, published on Aug. 19, 2010.
English machine translation of JP2000140533, published on May 23, 2000.
English machine translation of JP61131720, published on Jun. 19, 1986.
English machine translation of DE4232382, published on Mar. 24, 1994.

English machine translation of FR2812531, published on Nov. 5, 2004.
English machine translation of DE875134, published on Apr. 30, 1953.
English machine translation of DE921607U1; published on Feb. 25, 1993.
English machine translation of CN1493244, published on May 5, 2004.
English machine translation of CN 1887437, published on Jan. 3, 2007.
English machine translation of JP2011189132, published on Sep. 29, 2011.
English machine translation of WO2004093631, published on Nov. 4, 2004.
English machine translation of the Abstract of 2003180579, published on Jul. 2, 2003.
English machine translation of CN2012233346, published on Apr. 22, 2009.
English machine translation of DE9017798, published on Mar. 19, 1992.
English machine translation of CN2657570, published on Nov. 24, 2004.
English machine translation of WO0112050, published on Feb. 22, 2001.
English machine translation of CN101061932, published on Oct. 31, 2007.

* cited by examiner




FIG. 1

116




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

116




FIG. 20




FIG. 21





FIG. 22

FIG. 23






FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71

1

**CYCLONIC AIR TREATMENT MEMBER
AND SURFACE CLEANING APPARATUS
INCLUDING THE SAME**

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a continuation-in-part of application Ser. No. 16/101,770, filed Aug. 13, 2018.

FIELD

This application relates to the field of cyclonic air treatment members and surface cleaning apparatus including the same.

INTRODUCTION

The following is not an admission that anything discussed below is part of the prior art or part of the common general knowledge of a person skilled in the art.

Various types of surface cleaning apparatus are known, including upright surface cleaning apparatus, canister surface cleaning apparatus, stick surface cleaning apparatus, central vacuum systems, and hand carryable surface cleaning apparatus such as hand vacuums. Further, various designs for cyclonic hand vacuum cleaners, including battery operated cyclonic hand vacuum cleaners, are known in the art.

Surface cleaning apparatus are known which utilize one or more cyclones. A cyclone has a dirt collection region. The dirt collection region may be internal of the cyclone chamber (e.g., the dirt collection region may be a lower end of the cyclone chamber. Alternately, the dirt collection region may be a separate dirt collection chamber that is external to the cyclone chamber and in communication with the cyclone chamber via a dirt outlet. The dirt out may be a slot formed in the sidewall of a cyclone chamber or a gap provided between the end of the cyclone wall and an end of the cyclone chamber.

SUMMARY

In accordance with one aspect of this disclosure, a cyclone chamber is provided with a dirt collection chamber that is in communication with the cyclone chamber by an axially extending dirt outlet. The dirt outlet may have a length dimension in the axial longitudinal direction of the cyclone chamber that is greater than its width dimension in the circumferential direction of the cyclone chamber. For example, the length of the dirt outlet may be 2, 4, 6, 8 or 10 times or more the width of the dirt outlet (i.e., the width in the direction around the perimeter of the cyclone sidewall in a plane transverse to the cyclone axis). An advantage of this design is that, as the air rotates in the cyclone chamber and dirt is disentrained, the disentrained dirt may be deposited into a dirt collection chamber without the disentrained dirt having to be conveyed along the cyclone sidewall to a dirt outlet at an axial end of the cyclone chamber. Accordingly, the tendency of dirt to be re-entrained in the air rotating in the cyclone chamber may be reduced.

In accordance with this aspect, there is provided a surface cleaning apparatus comprising an air flow path extending from a dirty air inlet to a clean air outlet with a cyclone and a suction motor positioned in the air flow path, the cyclone comprising:

- (a) a cyclone chamber having a cyclone sidewall, a longitudinally extending cyclone axis of rotation, a

2

cyclone first end, an cyclone second end spaced apart in a longitudinal axial direction from the cyclone first end, a cyclone air inlet proximate the cyclone first end, a cyclone air outlet located at the cyclone second end and a dirt outlet, wherein the dirt outlet has a length in the axial direction and a width in a circumferential direction and the length is greater than the width; and, (b) a dirt collection chamber external to the cyclone chamber and in communication with the cyclone chamber via the dirt outlet.

In any embodiment, the length may be at least twice as long as the width.

In any embodiment, the length may be at least four times as long as the width.

In any embodiment, the dirt outlet may extend from a position proximate the cyclone first end towards the cyclone second end.

In any embodiment, the dirt outlet may extend to a position proximate the cyclone second end.

In any embodiment, the cyclone air inlet may be a tangential air inlet terminating at an inlet port provided on the cyclone chamber sidewall.

In any embodiment, the cyclone front end may be openable wherein, when the cyclone front end is moved to an open position, the cyclone chamber and the dirt collection chamber may each be opened.

In any embodiment, the surface cleaning apparatus may further comprise a dirt outlet insert member which is removably receivable in a portion of the dirt outlet adjacent the cyclone first end and the dirt outlet insert member may be opened when the cyclone front end is moved to an open position.

In any embodiment, the surface cleaning apparatus may further comprise a screen member having an outlet end located at the cyclone second end and the screen member may extend to distal screen end located adjacent the cyclone first end.

In any embodiment, the distal end of the screen member may terminate 0.01-0.75 inches from the cyclone first end.

In any embodiment, the distal end of the screen member may terminate 0.05-0.375 inches from the cyclone first end.

In any embodiment, the cyclone air inlet may be a tangential inlet having a conduit portion interior the cyclone chamber and the dirt outlet may extend from a position proximate an axially inner side of the inlet conduit towards the cyclone second end.

In any embodiment, the dirt outlet may extend to a position proximate the cyclone second end.

In any embodiment, the dirt outlet may extend from a position 0.01-0.2 inches axially inwardly from the axially inner side of the inlet conduit towards the cyclone second end.

In any embodiment, the cyclone front end may be openable wherein, when the cyclone front end is moved to an open position, the cyclone chamber and the dirt collection chamber may each be opened.

In any embodiment, the surface cleaning apparatus may further comprise a screen member having an outlet end located at the cyclone second end and the screen member may extend to distal screen end located adjacent the axially inner side of the inlet conduit.

In any embodiment, the surface cleaning apparatus may further comprise a dirt outlet insert member which is removably receivable in a portion of the dirt outlet adjacent the cyclone first end and the dirt outlet insert member may be opened when the cyclone front end is moved to an open position.

In accordance with another aspect of this disclosure, a cyclone chamber is provided with a dirt collection chamber that is in communication with the cyclone chamber by two or more dirt outlet regions. The two dirt outlet regions may be discrete outlets (i.e., each dirt outlet region may be a dirt outlet that is surrounded by, e.g., a portion of the sidewall of the cyclone chamber or a portion of the sidewall of the cyclone chamber and a portion of an end wall of the cyclone chamber) or they may be contiguous (e.g., they may be connected by a gap or slot formed in the cyclone chamber sidewall so as to form a single dirt outlet opening in, e.g., the cyclone chamber sidewall).

An advantage of this design is that dirt which is separated from the air swirling in the cyclone chamber prior to the swirling air reaching an end of the cyclone chamber opposed to the cyclone air inlet end (e.g., after the air has turned, for example, 1 or 2 times in the cyclone chamber) may be removed from the cyclone chamber by a first dirt outlet region and the remainder of the dirt may be separated in a second dirt outlet region that is located closer to or at the end of the cyclone chamber opposed to the cyclone air inlet end.

In accordance with this aspect, there is provided a cyclonic air treatment member comprising:

- (a) a cyclone having a cyclone sidewall, a cyclone first end, an opposed cyclone second end, a cyclone air inlet proximate the cyclone first end, a cyclone air outlet and a cyclone longitudinal axis extending from the cyclone first end to the cyclone second end, wherein a cyclone chamber is located between the cyclone first and second ends and the cyclone chamber has an outer perimeter which comprises the cyclone sidewall, wherein an air flow path extends from the cyclone air inlet to the cyclone air outlet: and,
- (b) a dirt collection chamber external to the cyclone chamber, the dirt collection chamber having first and second dirt outlet regions, each dirt outlet region extending around a portion of the perimeter of the cyclone chamber, wherein the second dirt outlet region is positioned proximate the cyclone second end, and the first dirt outlet region is positioned toward the cyclone first end relative to the second dirt outlet region.

In any embodiment, the first dirt outlet region may be longitudinally spaced apart from and discrete from the second dirt outlet region.

In any embodiment, the second dirt outlet region may be longitudinally spaced apart from and contiguous with the first dirt outlet region.

In any embodiment, the first dirt outlet region may be angularly offset about the outer perimeter of the cyclone chamber as compared to the second dirt outlet region.

In any embodiment, at least one of the first and second dirt outlet regions may comprise a slot extending angularly around a portion of the perimeter of the cyclone chamber.

In any embodiment, at least one of the first and second dirt outlet regions may comprise an array of 4 or more (e.g., 4, 5, 6, 7, 8, 9 or 10) apertures formed in the cyclone sidewall.

In any embodiment, the first dirt outlet region may comprise a slot formed in the cyclone sidewall, and the second dirt outlet region comprises an array of 4 or more (e.g., 4, 5, 6, 7, 8, 9 or 10) apertures formed in the cyclone sidewall and positioned adjacent the first dirt outlet region between the cyclone first end and the first dirt outlet region.

In any embodiment, each of the first and second dirt outlet regions may have a long dimension, and the long dimension of the first dirt outlet region is oriented generally transverse to the long dimension of the second dirt outlet region.

In any embodiment, the air flow path may include a cyclonic path portion that extends cyclonically from the cyclone air inlet toward the cyclone second end, and at least one of the dirt outlet regions may have a long dimension that is aligned with the cyclonic path portion. At least 75% of the first dirt outlet region may extend along a portion of the cyclonic path portion. Alternately, the first dirt outlet region may extend along the cyclonic path from an upstream outlet end of the first dirt outlet region to a downstream outlet end of the first dirt outlet region.

In any embodiment, the downstream outlet end of the first dirt outlet region may be positioned towards the cyclone second end relative to the upstream outlet end of the first dirt outlet region.

In any embodiment, both of the upstream outlet end of the first dirt outlet region and the downstream outlet end of the first dirt outlet region may be located along a portion of the cyclonic path portion.

In any embodiment, the second dirt outlet region may have a long dimension having a radial projection that is aligned perpendicularly to the cyclone axis. Alternately or in addition, the first dirt outlet region may have a long dimension having a radial projection that is aligned parallel to the cyclone axis.

In any embodiment, the second dirt outlet region may be bordered by the cyclone second end.

In any embodiment, the cyclone may further comprise a third dirt outlet region to the dirt collection chamber, the third dirt outlet region is formed in the cyclone sidewall, and is oriented transverse to the first and second dirt outlet regions. The first, second, and third dirt outlet regions may be contiguous. Alternately, one, two or all three may be discrete or one may be discrete and two may be contiguous.

In any embodiment, the cyclone air outlet may be at the cyclone second end. Alternately, the cyclone air outlet may be at the cyclone first end.

In accordance with another embodiment, a plurality of discrete dirt outlet regions (slots) are provided. The discrete outlet regions may provide enhanced dirt separation by the cyclone without increasing the back pressure in the cyclone chamber.

In accordance with this aspect, there is provided a cyclonic air treatment member comprising:

- (a) a cyclone having a cyclone sidewall, a cyclone first end, an opposed cyclone second end, a cyclone air inlet proximate the cyclone first end, a cyclone air outlet, a dirt outlet and a cyclone longitudinal axis extending from the cyclone first end to the cyclone second end, wherein a cyclone chamber is located between the cyclone first and second ends and the cyclone chamber has an outer perimeter which comprises the cyclone sidewall: and,
- (b) a dirt collection chamber external to the cyclone chamber and in communication with the cyclone chamber via the dirt outlet, wherein the dirt outlet comprises a plurality of discrete dirt outlet regions, each of which extends at an angle to the cyclone longitudinal axis.

In any embodiment, the plurality of dirt outlet regions may extend perpendicular ± 15 , 20, 25 or 30° to the cyclone longitudinal axis.

In any embodiment, the plurality of dirt outlet regions may extend generally perpendicular to the cyclone longitudinal axis.

5

In any embodiment, the plurality of dirt outlet regions may comprise a plurality of outlet slots that are arranged side by side along at least a portion of an axial length of the cyclone.

In any embodiment, a first dirt outlet region may be positioned proximate the cyclone second end, and a remainder of the plurality of dirt outlet regions may be positioned axially inward of the first dirt outlet region towards the cyclone first end.

In any embodiment, the cyclone air outlet may be located at the cyclone second end.

In any embodiment, the cyclone air outlet may comprise a solid portion at the cyclone second end and an air permeable portion axially inward thereof and the dirt outlet regions may be positioned only in a portion of the cyclone sidewall that is radially outward of the solid conduit.

In any embodiment, the cyclone air outlet may comprise a solid conduit portion at the cyclone second end and an air permeable portion axially inward thereof and the dirt outlet regions may be positioned in a portion of the cyclone sidewall that is radially outward of the solid conduit portion and air permeable portion.

In any embodiment, the dirt outlet may comprise at least three, five, seven or nine dirt outlet regions.

In any embodiment, the dirt outlet regions may be axially spaced apart from each other.

In any embodiment, the cyclone air inlet may be a tangential inlet having a conduit portion interior the cyclone chamber and the plurality of dirt outlet regions may extend from the cyclone second end to a position axially inwards of an axially inner side of the inlet conduit. Optionally, the plurality of dirt outlet regions may extend to a position proximate the axially inner side of the inlet conduit towards the cyclone second end.

In any embodiment, the cyclone air inlet may terminate at an inlet port provided on the cyclone chamber sidewall and the plurality of dirt outlet regions may extend from the cyclone second end towards the cyclone first end. Optionally, the plurality of dirt outlet regions may extend to a position proximate the cyclone first end.

In any embodiment, at least one of the dirt outlet regions may have first and second axially spaced apart sides wherein at least one of the sides is convex or concave.

In any embodiment, at least some of the dirt outlet regions may be axially evenly spaced apart.

In any embodiment, at least some of the dirt outlet regions may be axially spaced apart by varying amounts.

In any embodiment, the dirt outlet regions may have an axial dirt outlet width and the axial dirt outlet width of the dirt outlet regions may decrease from a forward location of the cyclone at which the dirt outlet regions commence to a rear location of the cyclone at which the dirt outlet regions terminate.

In any embodiment, the dirt outlet regions may be spaced apart by an axial distance and the axial distance may decrease from a forward location of the cyclone at which the dirt outlet regions commence to a rear location of the cyclone at which the dirt outlet regions terminate.

In accordance with this aspect, there is also provided a surface cleaning apparatus comprising the any embodiment of the cyclonic air treatment member disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the described embodiments and to show more clearly how they may be carried into

6

effect, reference will now be made, by way of example, to the accompanying drawings in which:

FIG. 1 is a perspective view of a surface cleaning apparatus in accordance with an embodiment;

FIG. 2 is a cross-sectional view taken along line 2-2 in FIG. 1, in accordance with an embodiment;

FIG. 3 is a perspective view of an air treatment member of the apparatus of FIG. 1 with a front wall and air outlet passage omitted, in accordance with an embodiment;

FIG. 4 is a perspective view of the air treatment member of the apparatus of FIG. 1, sectioned along line 2-2 in FIG. 1, and with the front wall and air outlet passage omitted, in accordance with the embodiment of FIG. 3;

FIG. 5 is a perspective view of the air treatment member of the apparatus of FIG. 1, sectioned along line 5-5 in FIG. 1, and with the front wall and air outlet passage omitted, in accordance with the embodiment of FIG. 3;

FIG. 6 is a perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 1 with the front wall and air outlet passage omitted, in accordance with another embodiment;

FIG. 7 is a perspective view of the alternate air treatment member of FIG. 6, sectioned along line 2-2 in FIG. 1, and with the front wall and air outlet passage omitted, in accordance with the embodiment of FIG. 6;

FIGS. 8-21 are perspective views of the air treatment member of the apparatus of FIG. 1, sectioned along line 5-5 in FIG. 1, and with the front wall and air outlet passage omitted, in accordance with various embodiments;

FIG. 22 is a cross-sectional view taken along line 2-2 in FIG. 1, in accordance with another embodiment;

FIG. 23 is a cross-sectional view taken along line 2-2 in FIG. 1, in accordance with another embodiment;

FIG. 24 is a perspective view of an upright surface cleaning apparatus in accordance with an embodiment;

FIG. 25 is a cross-sectional view taken along line 25-25 in FIG. 24, in accordance with another embodiment;

FIG. 26 is a perspective view of the surface cleaning apparatus of claim 1 sectioned along line 2-2, in accordance with another embodiment;

FIG. 27 is a perspective view of the surface cleaning apparatus of claim 1 sectioned along line 27-27, in accordance with another embodiment;

FIG. 28 is a perspective view of a surface cleaning apparatus in accordance with another embodiment;

FIG. 29 is a perspective view of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28, in accordance with an embodiment;

FIG. 30 is a cross-sectional view of the air treatment member of FIG. 29, sectioned along line 29-29 in FIG. 28, in accordance with the embodiment of FIG. 29;

FIG. 31 is a perspective view of the air treatment member of FIG. 29 with a front wall in an open position, in accordance with the embodiment of FIG. 29;

FIG. 32 is a cross-sectional view of the air treatment member of FIG. 29, sectioned along line 32-32 in FIG. 28, in accordance with the embodiment of FIG. 29;

FIG. 33 is a front view of the air treatment member of FIG. 29 with the front wall in the open position, in accordance with the embodiment of FIG. 29;

FIG. 34 is a perspective view of the air treatment member of FIG. 29 with a front wall in a partially open position, in accordance with the embodiment of FIG. 29;

FIG. 35 is a perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28, in accordance with another embodiment;

FIG. 36 is a cross-sectional view of the alternate air treatment member of FIG. 35, sectioned along line 29-29 in FIG. 28, in accordance with the embodiment of FIG. 35;

FIG. 37 is a perspective view of the alternate air treatment member of FIG. 35, sectioned along line 29-29 in FIG. 28, with a front wall in a first partially open position in accordance with the embodiment of FIG. 35;

FIG. 38 is a perspective view of the alternate air treatment member of FIG. 35, sectioned along line 29-29 in FIG. 28, with a front wall in a second partially open position in accordance with the embodiment of FIG. 35;

FIG. 39 is a perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28, in accordance with another embodiment;

FIG. 40 is a cross-sectional view of the alternate air treatment member of FIG. 39, sectioned along line 29-29 in FIG. 28, in accordance with the embodiment of FIG. 39;

FIG. 41 is a perspective view of the alternate air treatment member of FIG. 39, sectioned along line 41-41 in FIG. 28, in accordance with the embodiment of FIG. 35;

FIG. 42 is a perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 28, sectioned along line 42-42 in FIG. 28, in accordance with an embodiment;

FIG. 43 is a cross-sectional view of the alternate air treatment member of FIG. 42, sectioned along line 42-42 in FIG. 28, in accordance with the embodiment of FIG. 42;

FIG. 44 is a front view of the alternate air treatment member of FIG. 42 with a front wall in an open position, in accordance with the embodiment of FIG. 42;

FIG. 45 is a perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28, in accordance with another embodiment;

FIG. 46 is a cross-sectional view of the alternate air treatment member of FIG. 45, sectioned along line 29-29 in FIG. 28, in accordance with the embodiment of FIG. 45; and

FIG. 47 is a front perspective view of the alternate air treatment member of FIG. 45 with a front wall in an open position, in accordance with the embodiment of FIG. 45;

FIG. 48 is a front perspective view of an alternate embodiment of the air treatment member of the apparatus of FIG. 28, with a front wall in an open position, in accordance with an embodiment;

FIG. 49 is a front view of the alternate air treatment member of FIG. 48 with a front wall in an open position, in accordance with the embodiment of FIG. 48

FIG. 50 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 51 is a cross-sectional view of the air treatment member of FIG. 50, sectioned along line 32-32 in FIG. 28;

FIG. 52 is a perspective view of the air treatment member of FIG. 50, sectioned along line 52-52 in FIG. 28;

FIG. 53 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 54 is a cross-sectional view of the air treatment member of FIG. 53, sectioned along line 32-32 in FIG. 28;

FIG. 55 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 56 is a cross-sectional view of the air treatment member of FIG. 55, sectioned along line 32-32 in FIG. 28;

FIG. 57 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 58 is a cross-sectional view of the air treatment member of FIG. 57, sectioned along line 32-32 in FIG. 28;

FIG. 59 is a perspective view of the air treatment member of FIG. 57, sectioned along line 52-52 in FIG. 28;

FIG. 60 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 61 is a cross-sectional view of the air treatment member of FIG. 60, sectioned along line 32-32 in FIG. 28;

FIG. 62 is a perspective view of the air treatment member of FIG. 60, sectioned along line 52-52 in FIG. 28;

FIG. 63 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 64 is a cross-sectional view of the air treatment member of FIG. 63, sectioned along line 32-32 in FIG. 28;

FIG. 65 is a perspective view of the air treatment member of FIG. 63, sectioned along line 52-52 in FIG. 28;

FIG. 66 is a perspective view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 29-29 in FIG. 28;

FIG. 67 is a cross-sectional view of the air treatment member of FIG. 66, sectioned along line 32-32 in FIG. 28;

FIG. 68 is a perspective view of the air treatment member of FIG. 66, sectioned along line 52-52 in FIG. 28;

FIG. 69 is a cross-sectional view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 32-32 in FIG. 28;

FIG. 70 is a cross-sectional view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 32-32 in FIG. 28; and,

FIG. 71 is a cross-sectional view of an alternate embodiment of an air treatment member of the apparatus of FIG. 28, sectioned along line 32-32 in FIG. 28.

DESCRIPTION OF EXAMPLE EMBODIMENTS

Numerous embodiments are described in this application, and are presented for illustrative purposes only. The described embodiments are not intended to be limiting in any sense. The invention is widely applicable to numerous embodiments, as is readily apparent from the disclosure herein. Those skilled in the art will recognize that the present invention may be practiced with modification and alteration without departing from the teachings disclosed herein. Although particular features of the present invention may be described with reference to one or more particular embodiments or figures, it should be understood that such features are not limited to usage in the one or more particular embodiments or figures with reference to which they are described.

The terms “an embodiment,” “embodiment,” “embodiments,” “the embodiment,” “the embodiments,” “one or more embodiments,” “some embodiments,” and “one embodiment” mean “one or more (but not all) embodiments of the present invention(s),” unless expressly specified otherwise.

The terms “including,” “comprising” and variations thereof mean “including but not limited to,” unless expressly specified otherwise. A listing of items does not imply that any or all of the items are mutually exclusive, unless expressly specified otherwise. The terms “a,” “an” and “the” mean “one or more,” unless expressly specified otherwise.

As used herein and in the claims, two or more parts are said to be “coupled”, “connected”, “attached”, “joined”, “affixed”, or “fastened” where the parts are joined or operate together either directly or indirectly (i.e., through one or more intermediate parts), so long as a link occurs. As used herein and in the claims, two or more parts are said to be “directly coupled”, “directly connected”, “directly attached”, “directly joined”, “directly affixed”, or “directly fastened” where the parts are connected in physical contact with each other. As used herein, two or more parts are said to be “rigidly coupled”, “rigidly connected”, “rigidly attached”, “rigidly joined”, “rigidly affixed”, or “rigidly fastened” where the parts are coupled so as to move as one while maintaining a constant orientation relative to each other. None of the terms “coupled”, “connected”, “attached”, “joined”, “affixed”, and “fastened” distinguish the manner in which two or more parts are joined together.

Further, although method steps may be described (in the disclosure and/or in the claims) in a sequential order, such methods may be configured to work in alternate orders. In other words, any sequence or order of steps that may be described does not necessarily indicate a requirement that the steps be performed in that order. The steps of methods described herein may be performed in any order that is practical. Further, some steps may be performed simultaneously.

As used herein and in the claims, two elements are said to be “parallel” where those elements are parallel and spaced apart, or where those elements are collinear.

Some elements herein may be identified by a part number, which is composed of a base number followed by an alphabetical or subscript-numerical suffix (e.g. **112a**, or **112₁**). Multiple elements herein may be identified by part numbers that share a base number in common and that differ by their suffixes (e.g. **112₁**, **112₂**, and **112₃**). All elements with a common base number may be referred to collectively or generically using the base number without a suffix (e.g. **112**).

General Description of a Hand Vacuum Cleaner

Referring to FIGS. 1-2, an exemplary embodiment of a surface cleaning apparatus is shown generally as **100**. The following is a general discussion of apparatus **100**, which provides a basis for understanding several of the features that are discussed herein. As discussed subsequently, each of the features may be used individually or in any particular combination or sub-combination in this or in other embodiments disclosed herein.

Embodiments described herein include an improved cyclonic air treatment member **116**, and a surface cleaning apparatus **100** including the same. Surface cleaning apparatus **100** may be any type of surface cleaning apparatus, including for example a hand vacuum cleaner as shown (see also FIG. 28), a stick vacuum cleaner, an upright vacuum cleaner (**100** in FIG. 24), a canister vacuum cleaner, an extractor, or a wet/dry type vacuum cleaner.

In FIGS. 1-2 and 28, surface cleaning apparatus **100** is illustrated as a hand vacuum cleaner, which may also be referred to also as a “handvac” or “hand-held vacuum cleaner”. As used herein, a hand vacuum cleaner is a vacuum cleaner that can be operated to clean a surface generally one-handedly. That is, the entire weight of the vacuum may be held by the same one hand used to direct a dirty air inlet of the vacuum cleaner with respect to a surface to be cleaned. For example, handle **104** and dirty air inlet **108** may be rigidly coupled to each other (directly or indirectly), such

as being integrally formed or separately molded and then non-removably secured together (e.g. adhesive or welding), so as to move as one while maintaining a constant orientation relative to each other. This is to be contrasted with canister and upright vacuum cleaners, whose weight is typically supported by a surface (e.g. a floor) during use. When a canister vacuum cleaner is operated, or when an upright vacuum cleaner is operated in a ‘lift-away’ configuration, a second hand is typically required to direct the dirty air inlet at the end of a flexible hose.

Still referring to FIGS. 1-2 and 28, surface cleaning apparatus **100** includes a main body or a handvac body **112** having an air treatment member **116** (which may be permanently affixed to the main body or may be removable in part or in whole therefrom for emptying), a dirty air inlet **108**, a clean air outlet **120**, and an air flow path **124** extending between the dirty air inlet **108** and the clean air outlet **120**.

Surface cleaning apparatus **100** has a front end **128**, a rear end **132**, an upper end (also referred to as the top) **136**, and a lower end (also referred to as the bottom) **140**. In the embodiment shown, dirty air inlet **108** is at an upper portion of apparatus front end **128** and clean air outlet **120** is at a rearward portion of apparatus **100** at apparatus rear end **132**. It will be appreciated that dirty air inlet **108** and clean air outlet **120** may be positioned in different locations of apparatus **100**.

A suction motor **144** is provided to generate vacuum suction through air flow path **124**, and is positioned within a motor housing **148**. Suction motor **144** may be a fan-motor assembly including an electric motor and impeller blade(s). In the illustrated embodiment, suction motor **144** is positioned in the air flow path **124** downstream of air treatment member **116**. In this configuration, suction motor **144** may be referred to as a “clean air motor”. Alternatively, suction motor **144** may be positioned upstream of air treatment member **116**, and referred to as a “dirty air motor”.

Air treatment member **116** is configured to remove particles of dirt and other debris from the air flow. In the illustrated example, air treatment member **116** includes a cyclone assembly (also referred to as a “cyclone bin assembly”) having a single cyclonic cleaning stage with a single cyclone **152** and a dirt collection chamber **156** (also referred to as a “dirt collection region”, “dirt collection bin”, “dirt bin”, or “dirt chamber”). Cyclone **152** has a cyclone chamber **154**. Dirt collection chamber **156** may be external to the cyclone chamber **154** (i.e. dirt collection chamber **156** may have a discrete volume from that of cyclone chamber **154**). Cyclone **152** and dirt collection chamber **156** may be of any configuration suitable for separating dirt from an air stream and collecting the separated dirt respectively, and may be in communication dirt outlet(s) of the cyclone chamber.

In alternate embodiments, air treatment member **116** may include a cyclone assembly having two or more cyclonic cleaning stages arranged in series with each other. Each cyclonic cleaning stage may include one or more cyclones arranged in parallel with each other and one or more dirt collection chambers, of any suitable configuration. The dirt collection chamber(s) may be external to the cyclone chambers of the cyclones. Each cyclone may have its own dirt collection chamber or two or more cyclones fluidically connected in parallel may have a single common dirt collection chamber.

Referring to FIG. 2, hand vacuum cleaner **100** may include a pre-motor filter **160** provided in the air flow path **124** downstream of air treatment member **116** and upstream of suction motor **144**. Pre-motor filter **160** may be formed from any suitable physical, porous filter media. For

11

example, pre-motor filter **160** may be one or more of a foam filter, felt filter, HEPA filter, or other physical filter media. In some embodiments, pre-motor filter **160** may include an electrostatic filter, or the like. As shown, pre-motor filter **160** may be located in a pre-motor filter housing **164** that is external to the air treatment member **116**.

In the illustrated embodiments, dirty air inlet **108** is the inlet end **168** of an air inlet conduit **172**. Optionally, inlet end **168** of air inlet conduit **172** can be used as a nozzle to directly clean a surface. Alternatively, or in addition to functioning as a nozzle, air inlet conduit **172** may be connected (e.g. directly connected) to the downstream end of any suitable accessory tool such as a rigid air flow conduit (e.g., an above floor cleaning wand), a crevice tool, a mini brush, and the like. As shown, dirty air inlet **108** may be positioned forward of air treatment member **116**, although this need not be the case.

In the embodiment of FIGS. **2** and **28**, the air treatment member **116** comprises a cyclone **152**, the air treatment air inlet is a cyclone air inlet **184**, and the air treatment member air outlet is a cyclone air outlet **188**. Accordingly, in operation, after activating suction motor **144**, dirty air enters apparatus **100** through dirty air inlet **108** and is directed along air inlet conduit **172** to the cyclone air inlet **184**. As shown, cyclone air inlet **184** may direct the dirty air flow to enter cyclone chamber **154** in a tangential direction so as to promote cyclonic action. Dirt particles and other debris may be disentrained (i.e. separated) from the dirty air flow as the dirty air flow travels from cyclone air inlet **184** to cyclone air outlet **188**. The disentrained dirt particles and debris may discharge from cyclone chamber **154** through a dirt outlet **190** into dirt collection chamber **156** external to the cyclone chamber **154**, where the dirt particles and debris may be collected and stored until dirt collection chamber **156** is emptied.

Air exiting cyclone chamber **154** may pass through an outlet passage **192** located upstream of cyclone air outlet **188**. Cyclone chamber outlet passage **192** may also act as a vortex finder to promote cyclonic flow within cyclone chamber **154**. In some embodiments, cyclone outlet passage **192** may include an air permeable portion **197** (which may be referred to as a screen or shroud **197**, e.g. a fine mesh screen) in the air flow path **124** to remove large dirt particles and debris, such as hair, remaining in the exiting air flow. As exemplified in FIG. **50**, the cyclone air outlet **188** may comprise a conduit portion **189** which is solid (air impermeable) and an axially inward screen or shroud **197**.

From cyclone air outlet **188**, the air flow may be directed into pre-motor filter housing **164** at an upstream side **196** of pre-motor filter **160**. The air flow may pass through pre-motor filter **160**, and then exit through pre-motor filter chamber air outlet **198** into motor housing **148**. At motor housing **148**, the clean air flow may be drawn into suction motor **144** and then discharged from apparatus **100** through clean air outlet **120**. Prior to exiting the clean air outlet **120**, the treated air may pass through a post-motor filter **176**, which may be one or more layers of filter media.

Power may be supplied to suction motor **144** and other electrical components of apparatus **100** from an onboard energy storage member, which may include, for example, one or more batteries **180a** or other energy storage device. In the illustrated embodiment, apparatus **100** includes a battery pack **180**. Battery pack **180** may be permanently connected to apparatus **100** and rechargeable in-situ, or removable from apparatus **100**. In the example shown, battery pack **180** is located between handle **104** and air treatment member **116**. Alternatively or in addition to bat-

12

tery pack **180**, power may be supplied to apparatus **100** by an electrical cord (not shown) connected to apparatus **100** that can be electrically connected to mains power by at a standard wall electrical outlet.

Cyclonic Air Treatment Member with Two or More Dirt Outlets Extending Angularly Around the Cyclone Chamber Sidewall

Embodiments herein relate to an improved cyclonic air treatment member that may have two or more dirt outlets, which extend around a portion of the perimeter of the cyclone chamber sidewall. The features in this section may be used by themselves in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features described herein.

Within a cyclone, dirt is disentrained from a dirt laden air flow by directing the air flow along a cyclonic path. The cyclonic flow direction imparts radially outward forces upon dirt particles in the air flow, whereby the dirt particles are separated from the air flow and ultimately, e.g., ride against the cyclone sidewall. Dirt moved against the cyclone sidewall may exit from the cyclone chamber to a dirt collection chamber through a dirt outlet.

The ability of a cyclonic flow to separate dirt particles depends in part on the radial acceleration experienced by the dirt particles as a result of their cyclonic velocity through the cyclone. However, the cyclonic particle velocity may slow between the cyclone air inlet and air outlet. Below a threshold cyclonic particle velocity, the separation efficiency (i.e. the percentage of dirt particles separated from the dirty air flow by the cyclone) may be substantially reduced. When a vacuum cleaner operates at a high air flow rate (e.g. a 'high power mode' in a handvac), the cyclonic particle velocity between the cyclone air inlet and air outlet may remain well above such threshold velocity. However, when a vacuum cleaner operates at a low air flow rate (e.g. a 'low power mode' in a handvac), the cyclonic particle velocity may fall below the threshold velocity at some point between the cyclone air inlet and air outlet. In such a case, some of the dirt particles that have already been disentrained may be reentrained.

Embodiments herein relate to an improved cyclone having a dirt outlet that comprises a plurality of dirt outlet regions. A first dirt outlet region may be positioned closer, along the cyclonic air flow path, to the cyclone air inlet. The dirt outlet may have at least one additional dirt outlet region that may be positioned closer, along the cyclonic air flow path, to the cyclone air inlet. The additional dirt outlet region may be positioned at a location at which the cyclonic particle velocity may still be high enough (e.g. above the threshold velocity) to provide a targeted separation efficiency, even when operating at a lower air flow rate. Thus, the additional dirt outlet may permit the apparatus to optionally operate at a lower air flow rate with less loss of separation efficiency, all else being equal. For a handvac, this may mitigate the loss of separation efficiency when operating in a 'low power mode', which otherwise has an advantage of consuming less power thereby providing a longer run-time on a single charge.

Referring to FIGS. **2-4**, cyclone **152** includes a cyclone sidewall **202** that, as exemplified, extends along a cyclone longitudinal axis **204** between a cyclone first end **206** and a cyclone second end **208**. Accordingly, cyclone chamber **154** is bounded by cyclone sidewall **202** and cyclone first and second ends **206**, **208**. Cyclone **152** includes a tangential air inlet **184**, although any air inlet may be used. As shown, air

13

inlet **184** may be located proximate cyclone first end **206**, although the cyclone air inlet may be provided at other locations. Cyclone also includes an air outlet **188**. Cyclone air outlet **188** may be located proximate cyclone second end **208**, such as in the illustrated uniflow cyclone configuration, or it may be located at cyclone first end **206** (see, for example FIGS. **24-25**). Apparatus air flow path **124** includes a cyclone air flow path **212**, which extends from cyclone air inlet **184** to cyclone air outlet **188**.

Referring to FIGS. **3-4**, cyclone **152** may include first and second dirt outlet regions **190₁** and **190₂**. Second dirt outlet region **190₂** may be located proximate (e.g. at or closer to) cyclone second end **208**. For example, second dirt outlet region **190₂** may be located at the cyclone second end **208** as exemplified in FIGS. **2** and **3**. Second dirt outlet region **190₂** may be of any design known in the vacuum cleaner arts. For example, it may be a slot formed in the cyclone sidewall at the cyclone second end **208** as exemplified or it may be defined by a gap between the cyclone chamber sidewall and the second end wall **208** (e.g., it may be an annular opening at the end of the cyclone sidewall that faces the cyclone second end **208**. First dirt outlet region **190₁** may be located axially or longitudinally towards cyclone first end **206** relative to second dirt outlet region **190₂**.

Referring to FIGS. **4-5**, first dirt outlet region **190₁** may be provided anywhere in cyclone sidewall **202** having a longitudinal position between cyclone first end **206** and second dirt outlet **190₂**. For example, first dirt outlet region **190₁** may be longitudinally positioned between cyclone air inlet **184** and second dirt outlet **190₂**. This may allow dirt that enters cyclone **152** to exit through cyclone dirt outlet region **190₁** while that dirt has sufficient cyclonic velocity and before that dirt would have reached second dirt outlet region **190₂**.

In some embodiments, first dirt outlet region **190₁** may be aligned with a cyclonic portion of cyclone air flow path **212** (see for example FIG. **15**). This allows separated dirt that is sliding on cyclone sidewall **202** as it is carried along a cyclonic portion of air flow path **212** to flow into first dirt outlet region **190₁**, through which the dirt can exit into dirt collection chamber **156**. Accordingly, the alignment of first dirt outlet region **190₁** may permit the dirt outlet region **190₁** to better interact with dirt separated during an upstream portion of the cyclone air flow path **212**. Even when operating at a low air flow rate, the upstream portion of flow path **212** may yet have sufficient dirt particle velocity to provide a high separation efficiency.

It will be appreciated that cyclone **152** may have more than first and second dirt outlet regions **190₁** and **190₂**. For example, as exemplified in FIGS. **50-52**, three dirt outlet regions **190₁**, **190₂** and **190₃** may be provided. As exemplified in FIGS. **53-54**, **57-59**, **60-62** and **63-65** six dirt outlet regions **190₁-190₆** may be provided. As exemplified in FIGS. **55-56**, ten dirt outlet regions **190₁-190₁₀** may be provided. As exemplified, the plurality of dirt outlet regions comprise a plurality of discrete outlet slots that are arranged side by side along a portion of, or all of, an axial length of the cyclone.

As exemplified in FIG. **50**, the dirt outlet regions **190** may be positioned only in the portion of the cyclone chamber sidewall that is radially outward of the solid conduit portion **189** of the air outlet. Alternately, as exemplified in FIG. **53**, the dirt outlet regions **190** may be positioned in the portion of the cyclone chamber sidewall that is radially outward of the solid conduit portion **189** and the screen/shroud **197** of the air outlet.

14

If a plurality of dirt outlet regions are provided, they may extend from the rear end of the cyclone **152** (cyclone second end **208**) towards the front end (cyclone chamber first end **206**) as exemplified in FIGS. **51** and **54**, or to the front end of the cyclone as exemplified in FIG. **56**. If the air inlet is provided internal of the cyclone **152**, as exemplified in FIG. **55**, then the dirt outlet regions **190** may terminate at or rearward of the downstream wall **183** of the air inlet conduit **129**. Accordingly, the portion of the cyclone chamber sidewall extending forwardly of downstream wall **183** of the air inlet conduit **129** (section A in FIG. **55**) may not have any dirt outlet regions **190**.

Optionally, or in addition, if plurality of dirt outlet regions are provided, they may be evenly axially spaced apart as exemplified in FIGS. **51**, **54** and **56**, or they may be spaced apart by different amounts. If the axial length of a cyclone is about 80 mm, then the axial distance between dirt outlet regions **190** may be 1-6 mm, 1.5-4 mm or 2-3 mm. It will be appreciated that, if the axial length and/or diameter of a cyclone increases, then the axial distance between dirt outlet regions **190** may be increased.

Still referring to FIGS. **4-5**, cyclone air flow path **212** may have an axial flow width **216** (i.e. measured parallel to longitudinal axis **204**) approximately equal to an axial width **220** (i.e. measured parallel to longitudinal axis **204**) of cyclone air inlet **184**. Axial flow width **216** may remain generally constant between cyclone air inlet **184** and cyclone second end **208**. Cyclone dirt outlet regions **190** may have any axial width **224** suitable for allowing dirt separated from the air flow to exit cyclone chamber **154** towards dirt collection chamber **156**. Preferably, axial dirt outlet width **224₁** (or axial width **224** of each dirt outlet region **190**) is between 35% and 90% of axial air inlet width **220** (i.e. about 35% to 90% of axial air flow path width **216**). A width **224** within this range may be large enough to permit common dirt particle sizes to exit freely through the cyclone dirt outlet region **190**, and yet may not be so large that a detrimental amount of the air flow is diverted from cyclone chamber **154** through cyclone dirt outlet region **190**.

In other embodiments, axial dirt outlet width **224₁** may be between 15% and 150% of axial air inlet width **220** (i.e. about 15% to 150% of axial air flow path width **216**), between 25% and 125%, between 40% and 75% or between 50% and 60%. The lower portion of this range (e.g., 10% to 50% or 15% to 35% of axial air inlet width **220**) may minimize the amount of the air flow that diverts through cyclone dirt outlet **190** while still permitting at least small dirt particles to exit. The upper portion of this range (e.g., 75% to 150%, 90% to 150% or 100% to 125% of axial air inlet width **220**) may allow very large dirt particles to exit, although a somewhat greater amount of air flow may divert through cyclone dirt outlet region **190**.

Accordingly, if the axial length of a cyclone is about 80 mm, then the axial dirt outlet width **240** may be 1-18 mm, 2-6 mm, 3-5, or 4 mm. It will be appreciated that, if the axial length and/or diameter of a cyclone increases, then the axial outlet width **224** may be increased. Expressed differently, the axial dirt outlet width **224** may be 2-8%, 3-7% or 5% of the axial length of the cyclone.

The axial dirt outlet width **224** and/or axial distance between dirt outlet regions **190** may decrease from the forward location at which the dirt outlet regions **190** commence to the rear end of the location where the dirt outlet regions **190** terminate.

A dirt outlet region **190** may extend around part or all of the cyclone chamber sidewall, optionally in a plane transverse to the cyclone axis of rotation. For example, a dirt

outlet region **190** may extend in an arc that extends 10-180°, 25-120°, 35-90° or 45-75° around the cyclone chamber sidewall. Each dirt outlet may have the same arc or a different arc.

It will be appreciated that the dirt outlet regions **190** may have the same size (e.g. width, length, and/or area) or may be differently sized and/or differently shaped. As exemplified in FIGS. **3**, **9-11**, **51**, **54** and **56**, the dirt outlet regions are rectangular in shape. Alternately, the dirt outlet regions may have rounded angularly spaced apart ends (see FIGS. **57-59**), they may be oblong (see FIGS. **60-62**), they may have concave angularly extending walls (see FIGS. **63-65**), convex angularly extending walls (see FIG. **70**) or both concave and convex angularly extending walls (see FIGS. **67-69**). Alternately, or in addition, as exemplified in FIG. **71**, the axial dirt outlet width **224** of all (or some) of the dirt outlet regions **190** may be different. As exemplified, the axial dirt outlet width **224** may decrease (or decrease continually as exemplified) from the forward most dirt outlet region **190₁** to the rearward most dirt outlet region **190₅**.

Alternatively or in addition, the alignment of first dirt outlet region **190₁** with a cyclonic portion of cyclone air flow path **212** may be such that at least 50%, 60%, 70%, 80%, 90% or more of the area of first dirt outlet region **190₁** is coincident with (e.g., extends continuously along) the cyclone air flow path **212**. This may expose separated dirt particles to first dirt outlet region **190₁** for an extended continuous distance along cyclone air flow path **212**, whereby the dirt particles may be more likely to exit through first dirt outlet **190₁**, all else being equal.

The alignment of first dirt outlet region **190₁** with the cyclone air flow path **212** may be such that both an upstream end **228** of dirt outlet region **190₁** and a downstream end **232** of dirt outlet region **190₁** are each located along a portion of the cyclone air flow path **212**. For example, dirt outlet region **190₁** may extend contiguously along a part of the cyclone air flow path **212** from dirt outlet upstream end **228** to dirt outlet downstream end **232**.

Referring to FIG. **4**, first dirt outlet region **190₁** may have any axial position (i.e. with respect to cyclone longitudinal axis **204**) between cyclone first end **206** and second dirt outlet **190₂**. In some embodiments, first dirt outlet region **190₁** is axially offset from cyclone air inlet **184** by a distance **236** sufficient to permit at least some dirt particles within the air flow to separate (i.e. move outwardly to the cyclone sidewall **202**) as a result of the cyclonic character of air flow path **212**. For example, first dirt outlet region **190₁** may be located at least one turn (i.e., a 360° segment) of cyclone air flow path **212** from cyclone air inlet **184**. In the illustrated example, first dirt outlet region **190₁** is located just under 1.5 turns of cyclone air flow path **212** from cyclone air inlet **184**. Characterized another way, axial distance **236** from cyclone air inlet **184** to dirt outlet upstream end **228**, measured center-to-center may be at least equal to cyclone air inlet width **220** (i.e. at least about cyclone air flow width **216**). More generally, cyclone air inlet **184** may be spaced (center-to-center) from cyclone first end **206** by an axial distance **240** at least equal to cyclone air inlet width **220**.

Cyclone dirt outlet region **190₁** may have any angular (i.e. circumferential) position on cyclone sidewall **202**. In some embodiments, cyclone dirt outlet region **190₁** is angularly located at a bottom end **244** of cyclone sidewall **202** as shown. This allows gravity to assist with moving separated dirt particles through cyclone dirt outlet **190₁**. In other embodiments, cyclone dirt outlet region **190₁** may be angularly offset from sidewall bottom end **244**. Although such positions may not benefit from gravity assistance for dis-

charging separated dirt particles, they may advantageously provide greater flexibility to position cyclone dirt outlet region **190₁** at a distance **252** along cyclone air flow path **212**, at which cyclonic particle velocities and residency time are optimized for separation efficiency (e.g. at the power mode(s) provided by apparatus **100**). As an example, FIGS. **6-7** show cyclone dirt outlet region **190₁** angularly located between sidewall top and bottom ends **248**, **244**. In the example shown, cyclone dirt outlet region **190₁** has a path distance **252** of about one turn (e.g. 360°) from cyclone air inlet **184**.

Referring to FIG. **5**, cyclone dirt outlets **190** may have any orientation that is suitable for allowing dirt particles to exit cyclone chamber **154**. For example, one of cyclone dirt outlets region **190** (or both as shown) may be oriented such that they have a radial projection **256** (i.e. onto a plane **260** that includes cyclone longitudinal axis **204**) wherein the long direction is oriented transverse (e.g. perpendicular) to cyclone longitudinal axis **204**. For example, a cyclone dirt outlet region **190** may have a projected axis **264** that is transverse (e.g. perpendicular) to longitudinal axis **204**. As shown in FIG. **4**, this may permit cyclone dirt outlet(s) region **190** to be oriented in alignment with cyclone air flow path **212**.

FIG. **5** shows an example in which projections **256** (and projected axes **264**) are substantially perpendicular to cyclone longitudinal axis **204**. FIGS. **8-9** show an example in which projections **256** (and projected axes **264**) are not perpendicular. For example, projected axes **264** may be up to 30 or 45° from perpendicular with longitudinal axis **204**.

FIG. **8** shows dirt outlet regions **190** having a helical orientation, which may be aligned with the cyclonic air flow path through cyclone chamber **154**. As shown, each dirt outlet region **190** has an upstream end **228** located towards cyclone first end **206** relative to its downstream end **232**. An advantage of this design is that it can allow a greater portion of the area of dirt outlet region regions **190** to extend continuously along a portion of the cyclonic air flow path in cyclone chamber **154**.

FIG. **9** shows dirt outlet regions **190** having a helical orientation, which may be transverse (e.g. opposed to, misaligned, or counter-aligned) with the cyclonic air flow path through cyclone chamber **154**. For example, if the cyclonic air flow path **212** from cyclone air inlet **184** is counterclockwise when viewed from cyclone first end **206** looking towards cyclone second end **208** as illustrated in FIG. **4**, then one or both of dirt outlet regions **190** may extend clockwise from their outlet upstream end **228** to their outlet downstream end **232** as seen in FIG. **9** (or vice versa). An advantage of a transversely oriented dirt outlet **190** is that it may intersect several turns of the cyclone air flow path, which may expose the dirt outlet **190** to dirt particles having a wider range of residency time and particle velocities in the cyclonic flow. This may allow particles of different sizes sufficient time to separate from the air flow and make contact with cyclone sidewall **202**. This design may also permit the dirt outlet region **190** to provide an effective exit for a wider range of air flow rates. Further, where the air flow path within cyclone **152** reverses direction at cyclone second end **208** to travel towards cyclone air outlet **188** (e.g. through cyclone chamber outlet passage **192**, see FIG. **2**) this design may align the dirt outlet region **190** with the reversed portion of the air flow path (i.e. the 'counter-flow' portion of the air flow path).

FIGS. **10** and **11** illustrate examples in which dirt outlet region **190₁** is oriented differently from dirt outlet region **190₂**. As shown, one of dirt outlet regions **190** may have a

radial projection **256** (and projected axis **264**) that is substantially perpendicular to cyclone longitudinal axis **204**, and one of dirt outlet regions **190** may have a radial projection **256** (and projected axis **264**) that is transverse but not perpendicular to longitudinal axis **204**. The illustrated examples show second dirt outlet region **190₂** having a radial projection **256₂** (and projected axis **264₂**) that is substantially perpendicular to cyclone longitudinal axis **204**, and first dirt outlet region **190₁** having a helical orientation. An advantage of this design is that it allows first dirt outlet region **190₁** to be positioned and oriented to provide an effective dirt outlet for lower air flow rates, while second dirt outlet region **190₂** is bordered by cyclone second end **208** for discharging dirt that passes first dirt outlet region **190₁** and piles against cyclone second end **208**. In FIG. **10**, first dirt outlet region **190₁** is illustrated with a helical orientation aligned with the cyclonic air flow path through cyclone chamber **154**. In FIG. **11**, first dirt outlet region **190₂** is illustrated with a helical orientation that is transverse (e.g. opposed, misaligned, or counter-aligned) to the cyclonic air flow path through cyclone chamber **154**.

Reference is now made to FIG. **12**. In some embodiments, first dirt outlet region **190₁** may have a long direction that may be oriented substantially parallel (e.g. $\pm 15^\circ$ of parallel) with cyclone longitudinal axis **204**. An advantage of this design is that it can allow first dirt outlet region **190₁** to intersect several turns of the cyclone air flow path. This allows dirt outlet region **190₁** to provide an exit for dirt particles that have experienced a wider range of residency time and particle velocities in the cyclonic flow. In turn, this may allow particles of different sizes sufficient time to separate from the air flow and make contact with cyclone sidewall **202**. This design may also permit the dirt outlet region **190** to provide an effective dirt outlet for a wider range of air flow rates. As shown, first dirt outlet region **190₁** may have a radial projection **256₁** (and projected axis **264₁**) that is parallel to cyclone longitudinal axis **204**.

FIG. **13** shows an embodiment in which the long direction of first dirt outlet region **190₁** has an orientation that is between a transverse and a parallel orientation relative to cyclone longitudinal axis **204**. Such an orientation may provide a balance between (i) providing some degree of alignment with the cyclonic air flow path through cyclone chamber **154** in one of the forward direction (i.e. from cyclone first end **206** towards cyclone second end **208**) or the reverse direction (i.e. from cyclone second end **208** towards cyclone first end **206**), and (ii) exposing the dirt outlet **190₂** to several turns of the cyclonic air flow path.

Reference is now made to FIGS. **14-16**. As shown, some embodiments of cyclone **152** may have first dirt outlet region **190₁** contiguous with second dirt outlet **190₂**. Accordingly, as opposed to, e.g., FIG. **13** wherein two discrete outlet slots are provided, a single outlet slot or opening or gap in the sidewall may be provided which comprises two or more dirt outlet regions. An advantage of this design is that it may provide, where the first and second dirt outlet regions **190₁** and **190₂** meet, an outlet region having a large outlet width and length, which can accommodate especially large dirt particles. In the illustrated example, the first and second dirt outlet regions **190₁** and **190₂** have different orientations relative to cyclone longitudinal axis **204**. As shown, first dirt outlet region **190₁** may have a downstream end **232** that is connected to second dirt outlet region **190₂**. Downstream end **232** may be positioned towards cyclone second end **208** relative to cyclone first end **206**. This may provide the combination of dirt outlet regions **190₁** and **190₂** with a “T-shape” configuration. As shown in FIG. **14**, first dirt

outlet region **190₁** may be oriented substantially parallel to cyclone longitudinal axis **204**. As shown in FIGS. **15-16**, first dirt outlet region **190₁** may have a curved shape that is oriented neither parallel nor perpendicular to cyclone longitudinal axis **204**.

Referring to FIGS. **17-19**, cyclone **152** may have three dirt outlet regions **190** in some embodiments. As shown, third dirt outlet region **190₃** may be oriented transverse to first and second dirt outlet regions **190₁** and **190₂**. First and second dirt outlet regions **190₁** and **190₂** may be oriented the same (as shown), or differently from each other. An advantage of this design is that it may permit (i) first dirt outlet region **190₁** to be oriented best to provide an exit for dirt particles when operating at low air flow rates, (ii) second dirt outlet region **190₂** to provide an exit for particles that reach cyclone second end **208**, and (iii) third dirt outlet region **190₃** to interact with several turns of the cyclonic air flow path, which as discussed above may provide an exit for dirt particles that have experienced a wider range of residency time and particle velocities in the cyclonic flow, allow particles of different sizes sufficient time to separate from the air flow and make contact with cyclone sidewall, and/or provide an effective dirt outlet for a wider range of air flow rates.

As shown, the combination of dirt outlet regions **190₁**, **190₂**, **190₃** may have an “H-shape” or “N-shape” configuration. In the illustrated embodiment, third dirt outlet region **190₃** is contiguous with first and second dirt outlets **190₁** and **190₂**. As exemplified, third dirt outlet **190₃** has an upstream end **228₃** connected to first dirt outlet region **190₁**, and a downstream end **232₃** connected to second dirt outlet region **190₂**. In alternative embodiments, third dirt outlet region **190₃** may be spaced apart from (e.g. discontinuous with) one or both of first and second dirt outlet regions **190₁**, **190₂** such that two or 3 discrete outlets are provided. FIG. **17** shows an example in which third dirt outlet region **190₃** is oriented parallel to cyclone longitudinal axis **204**. FIGS. **18-19** show examples in which third dirt outlet region **190₃** is oriented non-parallel to cyclone longitudinal axis **204** (e.g. neither perpendicular nor parallel to cyclone longitudinal axis **204**, as shown).

In other embodiments, first dirt outlet region **190₁** may be spaced apart from (e.g. discontinuous with) second dirt outlet **190₂**, as illustrated in the examples of FIGS. **3-13**.

Referring to FIG. **4**, any or all of dirt outlet regions **190** may be formed in cyclone sidewall **202**. For example, a dirt outlet **190** may include an aperture (e.g. hole or slot) in cyclone sidewall **202** that allows separated dirt particles to exit cyclone chamber **154** towards dirt collection chamber **156**. In the illustrated example, dirt outlet regions **190** are formed in a portion of cyclone sidewall **202** that is common to dirt collection chamber **156**. An advantage of this design is that it provides the shortest travel distance from dirt outlet **190** to dirt collection chamber **156**, which may mitigate dirt particles collecting in an intervening passage. However, in alternative embodiments dirt outlet region **190** may provide an entrance to a passage leading to dirt collection chamber **156**. This may provide greater flexibility in the location of dirt collection chamber **156** relative to cyclone chamber **154**, such as to optimize apparatus **100** for compactness. Embodiments having a dirt outlet passage are discussed below.

FIG. **4** shows an example in which dirt outlet regions **190** are formed as slots in cyclone sidewall **202** (e.g., an open having a long dimension that extends circumferentially around a portion of the sidewall). As shown in FIG. **20**, a dirt outlet region **190** may be formed as an array of 4 or more closely arranged discrete apertures **268** that collectively

define the dirt outlet region **190**. As compared to a slot, an array of apertures **268** may provide many smaller apertures that are discontinuous with each other. This may help to reduce the amount of the air flow which diverts into dirt collection chamber **156**, which in turn may reduce the backpressure and re-entrainment of collected dirt that can result from such divergence. A dirt outlet region **190** may be composed of an array of 4 or more (e.g., 5, 6, 7, 8, 9 or 10) closely arranged apertures **268** organized in any pattern. In the illustrated embodiment, each dirt outlet region **190** is formed as 4 equally sized apertures **268** arranged linearly in a single row. In other embodiment, each dirt outlet region **190** may be formed from more than 4 apertures, which may be the same or differently sized, and which may be arranged in one or many rows (or in a different non-linear pattern). It is expressly contemplated that any embodiment described or shown herein as a slot may also be formed in another embodiment as an array of apertures.

Referring to FIGS. **21-22**, in some embodiments cyclone **152** includes one or more groups **272** of small apertures **274** (e.g. 10 or more apertures **274**) adjacent one or more (or all) of dirt outlet regions **190**. For example, a group **272** may be located towards cyclone first end **206** relative to the adjacent dirt outlet region **190** (e.g. upstream of the adjacent dirt outlet region **190**). Aperture group **272** may provide an exit for small dirt particles which remain open in the event that the adjacent dirt outlet region **190** becomes clogged. As shown, each group **272** may be angularly aligned (e.g. circumferentially aligned) with its respective adjacent dirt outlet region **190**. The illustrated embodiment shows a first group **272₁** of apertures adjacent dirt outlet region **190₁** and located between first dirt outlet region **190₁** and cyclone first end **206**, and a second group **272₂** of apertures adjacent dirt outlet region **190₂** and located between second dirt outlet **190₂** and first dirt outlet **190₁**. As shown, first group **272₁** may be axially spaced from first end **206** and second group **272₂** may be axially spaced from first dirt outlet **190₁**. FIG. **23** shows an alternative embodiment in which second group extends from proximate second dirt outlet region **190₂** to proximate first dirt outlet **190₁**.

Returning to FIG. **21**, each aperture **274** may have a size (e.g. width, length, and/or area) that is substantially smaller than the associated adjacent dirt outlet region **190**. In some embodiments, aperture **274** may have a width **288** of between 0.10 inches to 0.20 inches. This may provide a size that accommodates most small dirt particles collected in domestic (e.g. residential and commercial) environments. More generally, apertures **274** may each have a width **288** of between 0.010 inches and 0.500 inches. Apertures **274** having a width **288** of between 0.010 inches and 0.10 inches may provide exits suitable for very fine particles, and may minimize the amount of the air flow that diverts from the cyclone chamber **154** through apertures **274**. Apertures **274** having a width **288** of between 0.20 inches and 0.50 inches may provide exits suitable for relatively larger particles, although somewhat more of the air flow may divert from cyclone chamber **154** through apertures **274**. This may provide an acceptable trade-off where the dirt particles targeted for collection by apparatus **100** tend to be larger.

Cyclonic Air Treatment Member with One or More Dirt Outlets Extending Axially on the Cyclone Chamber Sidewall

Embodiments herein relate to an improved cyclonic air treatment member that may have one or more dirt outlets which extend in a generally axial direction along at least a

portion of the cyclone chamber sidewall. The features in this section may be used by themselves in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features described herein.

As discussed previously, FIGS. **14-19** exemplify embodiments wherein a portion of the dirt outlet extends axially or generally axially. In accordance with the feature discussed in this section, and as exemplified in FIGS. **28-34**, a cyclone **152** may have one or more dirt outlets **190**, each of which extends axially or generally axially. Accordingly, the dirt outlet may not include a portion that extends angularly around the cyclone chamber sidewall as discussed previously.

As exemplified in FIGS. **29** and **30**, dirt outlet **190** may have a length **224** that extends linearly in the axial direction generally parallel to the cyclone axis **204**. Alternately, similar to outlet **190₁** of FIGS. **15** and **16** and outlet **190₃** of FIGS. **18, 19** the dirt outlet **190** may extend in a direction that is offset or slightly offset from the direction of the longitudinal axis **204**, e.g. by \pm about 20° or $\pm 10^\circ$. The dirt outlet **190** may extend linearly as exemplified in FIGS. **29** and **30** or angularly as similar to outlet **190₁** of FIGS. **15** and **16** and outlet **190₃** of FIGS. **18, 19**.

The dirt outlet **190** has a transverse width **226** that extends in a circumferential direction of the cyclone chamber **154**. As shown in the example of FIG. **32**, the length **224** is greater than the width **226** (e.g., the length **224** may be 5, 10, 15 or 20 times the width **226**). As the air rotates within a cyclone chamber, the air will tend to stay in a band. The band may have an axial length about the axial length of a tangential air inlet. Accordingly, the dirt outlet **190** may have an axial length that is at least as long as the axial length of a tangential cyclone inlet, which may allow the dirt outlet **190** to underlie the axial length of an entire band of air in a turn of the cyclonic air flow path through cyclone chamber **154**. If the axial length of the dirt outlet is longer, then the dirt outlet **190** may underlie more than one turn of the air, e.g., it may underlie 1.5 or 2 turns of the air.

In some embodiments, as exemplified in FIGS. **28-34**, the cyclone dirt outlet may be formed as an opening or gap in the cyclone chamber sidewall **202**. In the illustrated embodiment, dirt outlet **190** is formed as a rectangular aperture in the sidewall **202**. In alternative embodiments, dirt outlet **190** may have other shapes (e.g. elliptical, triangular, irregular shapes) in which the length **224** is greater than the width **226**.

In some embodiments, the dirt outlet **190** is provided at a bottom end **244** of cyclone sidewall **202** as shown. This may help dirt which remains in the cyclone chamber **154** after termination of operation of the vacuum cleaner **100** to fall into the dirt collection chamber **156** when the vacuum cleaner **100** is held with the cyclone **152** extending horizontally (and possibly slightly upwardly).

The dirt outlet extends between dirt outlet first or upstream end **193** and dirt outlet second or downstream end **194**. The dirt outlet upstream end **193** may be located at any location along the axial length of the cyclone **152**. For example, as exemplified in FIG. **31**, the dirt outlet upstream end **193** may be located at the front end of the cyclone **152** (cyclone first end **206**). Alternately, as exemplified in FIG. **47**, the dirt outlet upstream end **193** may be located axially inwardly from the front end of the cyclone **152**. For example, the dirt outlet upstream end **193** may be located at or axially inwardly (rearwardly) from the axially inner extent of the cyclone air inlet (see, e.g., FIG. **46**). As shown in FIGS. **28-34**, the cyclone air inlet **184** includes a conduit **129** that extends into, and is located interior to the cyclone

chamber **154**. The open portion of the dirt outlet **190** may extend from a position located at or, e.g., about 0.01-0.2 inches axially inward from the axially inner side **185** of the air inlet conduit **129** towards the cyclone second end **208**.

Similarly, the dirt outlet downstream end **194** may be located at any location along the axial length of the cyclone **152**. For example, the dirt outlet downstream end **194** may be located at the rear end of the cyclone **152** (cyclone second end **208**). Alternately, as exemplified in FIG. **30**, the dirt outlet downstream end **194** may be located axially inwardly from the rear end of the cyclone **152**. For example, the dirt outlet downstream end **194** may be located at passage second end **276** or axially inwardly (forwardly) from the axially inner extent of the solid portion of the outlet passage **192** (see, e.g., FIG. **30**).

Accordingly, the dirt outlet **190** may be provided by an axially extending slot **191**, which is formed in the sidewall **202**, which extends longitudinally along at least a portion of the cyclone chamber **154** in a direction generally parallel to the cyclone axis **204** between dirt outlet upstream end **193** and dirt outlet downstream end **194**. As exemplified in FIGS. **29-31**, the length **225** of slot **191** may be greater than the open length **224** of the dirt outlet **190**. This may occur if, for example, the slot extends forwardly of the cyclone air inlet. In such a case, an insert member **230** may be provided to limit the forward extent of the slot **191** when the surface cleaning apparatus is in operation (i.e., the length of the slot **191** may be reduced due to insert member **230** to provide a dirt outlet upstream end **193** that is positioned at a selected forward extent of the cyclone **152**).

FIGS. **29-31** exemplify an embodiment wherein the slot **191** extends from a position at the cyclone first end **206** rearward towards the cyclone second end **208**. In this embodiment, the second end **194** of the slot **191** is axially spaced apart from the first end **193** and is located inwardly (forwardly) of the cyclone second end **208**. As shown in FIG. **30**, the slot **191** is positioned under cyclone air inlet **184**. Accordingly, air entering the cyclone **152** at the axial location of the cyclone air inlet **184** (i.e., between the forward and rearward extent of) could enter the slot **191**.

Optionally, as exemplified, an insert member **230** may be provided, and may be removably received in a slot portion **231** of the slot **191** proximate the cyclone first end **206** as shown. When the insert member **230** is received in the slot **191**, the insert member **230** can occupy the slot portion **231** and prevent dirt from exiting the cyclone chamber **154** via slot portion **231**. The open portion of the dirt outlet **190** may thus extend between the second end **194** and an open outlet end **195**. As a result, in operation the open length **224** of the dirt outlet **190** may be less than the overall length **225** of the slot **191**.

The insert member may extend from the front end **206** of the cyclone rearwardly any desired amount. As exemplified in FIGS. **29-31**, the open outlet end **195** may be positioned proximate an axially inner side **185** of the tangential air inlet **184**. Accordingly, the insert member may extend inwardly to a position at the location of the axially inner side **185** and, optionally, rearwardly thereof (see for example FIG. **35**).

As exemplified in FIG. **2**, in some embodiments, first end **280** of passage **192** may be solid (i.e., it may not be porous). In such a case, the insert member **230** may extend to the inner end of the solid portion of screen **197**, and, optionally, rearwardly thereof such that the open outlet end **195** may be spaced axially inwardly (towards cyclone second end **208**) from the axially inner side **185**. Alternately, if the solid portion of screen **197** extends to the front end **206** of the cyclone, then an insert member **230** may not be provided.

Alternately, the passage first end **280** may be positioned longitudinally adjacent to the inner side **185** of the air inlet **184**. If the cyclone air inlet **184** is provided inside the cyclone chamber **154**, then the cyclone outlet passage **192** may extend to a position longitudinally adjacent (e.g., within 0.01, 0.05, 0.1 or 0.125 inches) to the end **185** of the tangential inlet **184** closest to the outlet end of the cyclone chamber **154**.

As shown in FIG. **30**, the passage first end **280** can be axially spaced inwardly from the inner side **185** of air inlet conduit **129**. For example, the first end **280** of the cyclone outlet passage **192** may terminate at about 0.01-0.75 or about 0.05-0.375 inches inwardly from the inner side **185** of the air inlet **184** in some embodiments. Alternately, in some embodiments, the first end **280** of the cyclone outlet passage **192** may abut the downstream wall **183** of the air inlet conduit **129**.

As discussed subsequently, in some embodiments, the cyclone outlet passage **192** may be tapered between the passage second end **276** and the passage first end **280**. As shown in FIG. **30**, the transverse width of the cyclone outlet passage **192** may increase gradually between passage first end **280** and passage second end **276**. This may provide a greater radial distance between the cyclone chamber sidewall **202** and the cyclone outlet passage **192** at the air inlet end of the cyclone chamber **154** thereby inhibiting dirt from contacting the screen **197** as it enters the cyclone chamber **154**.

In some embodiments, the cyclone first end **206** may be openable. As shown in FIG. **31**, the cyclone first end **206** may be defined by an openable front wall **207**. The front wall **207** may be movable between a closed position (shown for example in FIGS. **28-30**) and an open position (shown in FIG. **31**). As illustrated, when the front end **206** is moved to the open position, the cyclone chamber **154** and the dirt collection chamber **156** are each opened. This may facilitate emptying dirt and debris from the cyclone **152**.

Alternately or in addition, the cyclone chamber **154** and dirt collection chamber **156** may be separately openable.

As exemplified in FIG. **31**, if an insert member **230** is provided, then the insert member **230** can be mounted to the front wall **207**. Accordingly, as the cyclone front end **206** is moved to the open position, the insert member can be removed from the dirt outlet portion **231**. This may provide additional access to dirt collection chamber **156** to facilitate emptying.

As shown, the cyclone outlet passage **192** can be tapered. The reduction in width of the passage **192** moving from the second end **176** to the first end **280** may allow the insert member **230** to have a greater axial length while still permitting the insert member **230** to be withdrawn from the dirt outlet slot **191**.

It will be appreciated that, instead of providing an insert member **230** to close part of slot **191**, slot **191** may have the same dimensions as dirt outlet **190**. Such an embodiment is exemplified in FIGS. **45-47**, wherein the cyclone **152** is not provided with an insert member **230**. Rather, as exemplified, the dirt outlet **190** may be defined entirely by a gap/slot **191** in the cyclone chamber sidewall **202**. The cyclone chamber sidewall **202** may include a section **203** that extends from proximate the front end **206** to the dirt outlet first end **193**. A gap **191** in the sidewall **202** extending rearward from the dirt outlet first end **193** (the open outlet end **195**) may then define the dirt outlet **190**. Accordingly, the dirt outlet first end **193** can be positioned at the same location as discussed

with respect to the open outlet end **195**, i.e., it may be positioned proximate to the second end **185** of the tangential air inlet **184**.

FIGS. **35-38** exemplify an embodiment wherein the open portion of the dirt outlet **190** is axially spaced apart (inwardly) from the second end **185** of the air inlet **184** towards the cyclone second end **208**. This may also reduce the re-entrainment of collected dirt from the dirt collection chamber **156**, particularly if outlet passage **192** is not tapered.

In the example shown in FIGS. **35-38**, the insert member **230** extends axially from the cyclone first end **206** towards the cyclone second end **208** for a distance beyond the inner side **185** of the air inlet conduit **129**. As a result, the open outlet end **195** is axially spaced apart from the inner side **185** of the air inlet conduit **129**. In operation, the open length **224** of the dirt outlet **190** is thus much less than the overall length **225** of the slot **191**.

Depending upon the length of the insert member **20**, the diameter of the cyclone chamber **154** and the diameter of the passage **192**, the top side **233** of the insert member **230** may contact the cyclone outlet passage **192** and may brush against the screen **197** when the insert member **230** is removed from the cyclone chamber when the cyclone front end **206** is moved to the open position (see for example FIGS. **37-38**). In such an embodiment, the insert member **230** may thus help dislodge dirt and debris from the screen **197** to facilitate cleaning thereof. To facilitate the removal of the insert member **230** in such an embodiment, the insert member may be flexible or bendable (e.g., it may be made of a resilient material) and/or the outlet passage **192** may be tapered and or shorter.

As exemplified, if the insert member **230** extends past the cyclone inlet, then the cyclone outlet passage **192** can be tapered. The reduction in width of the passage **192** moving from the second end **176** to the first end **280** may allow the insert member **230** to be more easily withdrawn from the dirt outlet slot **191**.

Optionally, the insert **230** may be flexible or bendable. As the front end **206** is opened, the insert member **230** may contact the cyclone outlet passage **192** and press on the screen **197**. As shown in FIGS. **37-38**, insert member **230** can flex in response to pressing against the outlet passage **192** to allow the insert member **230** to be removed without damaging or displacing the outlet passage **192**, while still assisting in cleaning the screen **197**.

In the example shown in FIGS. **35-38**, the insert member **230** has a generally triangular shape. The triangular shape of the insert member **230** may support the insert member **230** and prevent flexing or bending in response to air flow in the cyclone chamber **154**.

Alternately, other shapes of insert member **230** may be used. Referring to FIGS. **39-41**, shown therein is another example of a cyclone **152** with a rectangular insert member **230**. The rectangular insert member **230** shown in FIGS. **39-41** may occupy less space allowing for increased capacity in the dirt collection chamber **156**.

As exemplified in FIGS. **42-44**, in some embodiments the cyclone air inlet **184** may terminate at a cyclone inlet port **187** formed in the sidewall **202** of the cyclone chamber **154**. In the example illustrated, the cyclone inlet port **187** is the terminal end of a tangential inlet and is an opening formed in the longitudinally extending sidewall **202**. The cyclone air inlet **184** extends from a cyclone air inlet upstream end **310** to a cyclone air inlet downstream end **312**. The cyclone air

inlet downstream end **312** may be oriented to direct air substantially tangentially to the inner surface of sidewall **202**.

In the illustrated example of FIGS. **42-44**, cyclone air inlet **184** is formed as a curved passage **315** extending from a cyclone air inlet upstream end **310** to a cyclone air inlet downstream end **312**. The curved passage **315** may provide a gradual change of direction for the air passing through the cyclone air inlet **184**, which may reduce backpressure through the cyclone air inlet **184**.

The cyclone air inlet **184** has an inlet width that extends between a first inlet side **179** and a second inlet side **185**. In the example illustrated, the first inlet side **179** and second inlet side **185** are spaced apart in a longitudinal axial direction generally parallel to the cyclone axis of rotation **204**. The second inlet side **185**, or downstream inlet side, is positioned closer to the cyclone second end **208** than the first inlet side **179**.

As exemplified, where the cyclone air inlet **184** terminates at a port **187** in the cyclone chamber sidewall **202** such as exemplified in FIGS. **42-44**, the first end **208** of the passage **192** may be located at the second inlet side **185** or, alternately, it may be located axially inwardly of the second side **185** of the tangential air inlet **184** (i.e., towards cyclone second end **208**), for example, 0.01, 0.05, 0.1 or 0.125 inches inwardly of second inlet side **185**.

In alternate embodiments, the first end **208** of the cyclone outlet passage **192** may extend to a position at or adjacent (e.g., within 0.01, 0.05, 0.1 or 0.125 inches) of the first end **206** of the cyclone chamber **154**. For example, the passage first end **280** may terminate at about 0.01-0.75 inches or about 0.05-0.375 inches from the cyclone first end **206** in some embodiments. In such a case, the portion of cyclone outlet passage that is axially co-extensive with port **187** may be solid.

As exemplified in FIGS. **48-49**, in some embodiments the cyclone **152** may include a plurality of axially extending dirt outlet **190₁**, **190₂**, and **190₃**. This may allow the dirt outlets to intersect the air flow path through the cyclone chamber **154** at different locations, which may expose the dirt outlets **190₁**, **190₂**, and **190₃** to dirt particles having a wider range of residency time and particle velocities in the cyclonic flow.

Each of dirt outlets **190₁**, **190₂**, and **190₃** may be the same or different. Each dirt outlet **190₁**, **190₂**, and **190₃** may be of any design discussed herein.

In the example illustrated in FIGS. **48** and **49**, the cyclone **152** omits and insert member **230** and a section **203** of the cyclone chamber sidewall **202** extends to the dirt outlets **190₁**, **190₂**, and **190₃**, similar to the embodiment of FIGS. **45-47**, so that the dirt outlets **190₁**, **190₂**, and **190₃** can be positioned proximate the downstream end of the air inlet **184**. Alternately, an insert member may be used to define the extent of the dirt outlets **190₁**, **190₂**, and **190₃**. Alternately, the dirt outlets **190₁**, **190₂**, and **190₃** may extend to the front end of cyclone **152**.

In the example shown in FIGS. **48-49**, each dirt outlet **190₁**, **190₂**, and **190₃** connects the cyclone chamber **154** to a separate dirt collection chamber **156₁**, **156₂**, and **156₃**. This may reduce the amount of the air flow which diverts into each dirt collection chamber **156**, which in turn may reduce the re-entrainment of collected dirt that can result from such divergence.

Alternately, the plurality of dirt outlets **190** may be connected to a single dirt collection chamber **156**. This may provide an increased dirt collection volume and ensure that the entire dirt collection volume can be used instead of

25

having the empty the dirt collection chambers **156₁**, **156₂**, and **156₃** when one becomes filled.

Cyclone Air Outlet

Embodiments herein relate to an improved cyclonic air outlet. The features in this section may be used by themselves in any surface cleaning apparatus or in any combination or sub-combination with any other feature or features described herein.

As exemplified in FIG. 2, cyclone chamber outlet passage **192** may have any shape that can provide an outlet passage for air exiting cyclone chamber **154**. Cyclone chamber outlet passage **192** may extend longitudinally from a passage second end **276** at cyclone second end **208** towards cyclone first end **206** (e.g. in parallel with cyclone longitudinal axis **204**) to a passage first end **280**. As shown, cyclone chamber outlet passage **192** may be spaced apart from cyclone sidewall **202** to define a surrounding annular region between cyclone chamber outlet passage **192** and cyclone sidewall **202** that promotes cyclonic air flow through cyclone chamber **154**.

In the illustrated embodiment, cyclone chamber outlet passage **192** has a transverse width **288** (e.g. diameter) that is substantially constant (e.g. varies by less than 10%) between passage first end **280** and passage second end **276**. Depending on the size and shape of cyclone sidewall **202**, this may provide the air flow path through cyclone chamber **154** with a relatively constant cross-sectional area.

In accordance with this feature, as exemplified in FIG. 22, cyclone chamber outlet passage **192** may have a transverse width **288** that increases between passage first end **280** and passage second end **276** towards passage second end **276**. In other words, cyclone chamber outlet passage **192** may taper in transverse width **288** towards passage first end **280**. Depending on the size and shape of cyclone sidewall **202**, this may provide the air flow path through cyclone chamber **154** with a shrinking cross-sectional area as the air flow travels from cyclone air inlet **184** towards cyclone second end **208**. As a result of the inverse relationship between cross-sectional area and velocity, the progressive reduction in cross-sectional flow area may increase the flow velocity towards cyclone second end **208**. This may mitigate a loss of velocity and cyclonic degradation that may develop towards cyclone second end **208** particularly when operating at low flow rates (e.g. in a lower power mode). Consequently, the tapered cyclone chamber outlet passage **192** may promote greater overall separation efficiency for cyclone **152**.

As shown, transverse width **288** may increase continuously between passage first end **280** and passage second end **276**. In some embodiments, transverse width **288** may increase by at least 10% (e.g. by 10% to 200%, 25% to 175%, 40% to 125% or 60% to 90%) between passage first end **280** and passage second end **276**. In the illustrated embodiment, transverse width **288** increases by about 125% between passage first end **280** and passage second end **276**.

As exemplified, passage first end **280** may be solid and may have an axial length that is at least as long as, or longer than, the axial inward extent of the cyclone air inlet. Accordingly, air that enters the cyclone chamber may not directly enter the outlet passage **192**, as the first end **280** is solid.

Although many of the figures illustrate concepts and embodiments applied to an exemplary handvac, all of the embodiments described herein apply equally to other surface cleaning apparatus (e.g. upright vacuums, canister vacuums, etc.). Further, although many of the figures illustrate a uniflow cyclone that is horizontally oriented, all embodi-

26

ments disclosed here are also applicable to other cyclone configurations and orientations. As an example, FIGS. 24-25 show an upright vacuum **100** having a cyclonic air treatment member **116** with an inverted cyclone **152**. As shown, cyclone **152** has a central longitudinal axis **204** that is vertically oriented, a plurality of dirt outlet regions **190** (which may have any configuration disclosed in any embodiment herein), a cyclone chamber air outlet passage **192** (which may have any configuration disclosed in any embodiment here), and both the cyclone air inlet **184** and outlet **188** are located at cyclone first end **206**.

Reference is now made to FIGS. 26-27. In some embodiments, a dirt outlet region **190** may provide an entryway to a dirt outlet passage **292** leading to dirt collection chamber **156**. This may be the case for the only dirt outlet region **190** of a cyclone **152** as shown, or for one or more (or all) dirt outlet regions **190** of a cyclone **152** having many dirt outlet regions **190** (e.g. as in any embodiment disclosed herein having two or more dirt outlets **190**). An advantage of providing a dirt outlet passage **292** between a dirt outlet region **190** and the dirt collection chamber **156** is that it may reduce the amount of air flow that diverts from the cyclone chamber **154** into the dirt collection chamber **156**. Diverted air flow can produce a pressure drop in the air flow through cyclone **152**, which may result in less suction and possibly lower dirt separation efficiency all else being equal. By mitigating pressure drops, a smaller, lighter, less expensive suction motor may be used to achieve the same suction, or greater suction may be achieved with the same suction motor. Further, diverted air flow may disturb dirt that has collected in dirt collection chamber **156**, which may lead to that dirt re-emerging into the cyclone chamber **154** through the dirt outlet region **190**. A dirt outlet passage **292** may help to mitigate dirt collected in dirt collection chamber **156** from returning to cyclone chamber **154**.

Dirt outlet passage **292** has a length **296** extending from dirt outlet region **190** to passage outlet **304**. Passage outlet **304** may be located inside dirt collection chamber **156** as shown, or may be formed in a sidewall of dirt collection chamber **156** (e.g., the outlet end may be a port provided in a sidewall of the dirt collection chamber **156**). Passage outlet **304** may have any passage length **296** suitable for directing dirt exiting from cyclone chamber **154** at a dirt outlet region **190** to dirt collection chamber **156**. Preferably, passage length **296** is greater than a thickness of cyclone chamber sidewall **202**. For example passage length **296** may be greater than 5 mm (e.g. between 5 mm and 300 mm, 25-250 mm, 50-200 mm or 75-150 mm). A passage length **296** closer to 5 mm may be appropriate where, for example, cyclone chamber **154** and dirt collection chamber **156** share a common dividing wall **202**. A passage length much greater than 5 mm (e.g. 50 mm or more) may be appropriate where, for example, cyclone chamber **154** and dirt collection chamber **156** are spaced apart.

Dirt outlet passage **292** may extend in any direction from dirt outlet region **190** towards dirt collection chamber **156**. In some embodiments, dirt outlet passage **292** is oriented tangential to cyclone chamber **154**. FIG. 26 shows an example in which dirt outlet passage **292** is oriented tangential cyclone chamber **154** in alignment with the direction of cyclone air flow path **212** where cyclone air flow path **212** crosses dirt outlet region **190**. An advantage of this design is that dirt outlet passage **292** may be oriented in the same direction as the direction of dirt particles at dirt outlet **190**. This may increase particle separation efficiency by reducing the number of dirt particles which cross over dirt outlet region **190** without exiting cyclone chamber **154**. However,

such tangential alignment may also lead to a somewhat greater amount of the air flow diverting from cyclone chamber 154 into dirt collection chamber 156. FIG. 27 shows an example in which dirt outlet passage 292 is oriented tangential to cyclone chamber 154 but extending in a direction opposed to the direction of cyclone air flow path 212 where cyclone air flow path 212 crosses dirt outlet 190. An advantage of this design is that it may reduce the amount of air that diverts from cyclone chamber 154 to dirt collection chamber 156, although a somewhat greater number of dirt particles may pass over dirt outlet 190 without exiting.

While the above description provides examples of the embodiments, it will be appreciated that some features and/or functions of the described embodiments are susceptible to modification without departing from the spirit and principles of operation of the described embodiments. Accordingly, what has been described above has been intended to be illustrative of the invention and non-limiting and it will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

The invention claimed is:

1. A surface cleaning apparatus comprising an air flow path extending from a dirty air inlet to a clean air outlet with a cyclone and a suction motor positioned in the air flow path, the cyclone comprising:

- (a) a cyclone chamber having a cyclone sidewall, a longitudinally extending cyclone axis of rotation, a cyclone first end, an cyclone second end spaced apart in a longitudinal axial direction from the cyclone first end, a cyclone air inlet proximate the cyclone first end, a cyclone air outlet located at the cyclone second end and a dirt outlet, wherein the dirt outlet has a length in the axial direction and a width in a circumferential direction and the length is greater than the width; and,
- (b) a dirt collection chamber external to the cyclone chamber and in communication with the cyclone chamber via the dirt outlet.

2. The surface cleaning apparatus of claim 1 wherein the length is at least twice as long as the width.

3. The surface cleaning apparatus of claim 1 wherein the length is at least four times as long as the width.

4. The surface cleaning apparatus of claim 1 wherein the dirt outlet extends from a position proximate the cyclone first end towards the cyclone second end.

5. The surface cleaning apparatus of claim 4 wherein the dirt outlet extends to a position proximate the cyclone second end.

6. The surface cleaning apparatus of claim 4 wherein the cyclone air inlet is a tangential air inlet terminating at an inlet port provided on the cyclone chamber sidewall.

7. The surface cleaning apparatus of claim 4 wherein the cyclone front end is openable wherein, when the cyclone

front end is moved to an open position, the cyclone chamber and the dirt collection chamber are each opened.

8. The surface cleaning apparatus of claim 7 further comprising a dirt outlet insert member which is removably receivable in a portion of the dirt outlet adjacent the cyclone first end and the dirt outlet insert member is opened when the cyclone front end is moved to an open position.

9. The surface cleaning apparatus of claim 6 further comprising a screen member having an outlet end located at the cyclone second end and the screen member extends to distal screen end located adjacent the cyclone first end.

10. The surface cleaning apparatus of claim 9 wherein the distal end of the screen member terminates 0.01-0.75 inches from the cyclone first end.

11. The surface cleaning apparatus of claim 9 wherein the distal end of the screen member terminates 0.05-0.375 inches from the cyclone first end.

12. The surface cleaning apparatus of claim 1 wherein the cyclone air inlet is a tangential inlet having a conduit portion interior the cyclone chamber and the dirt outlet extends from a position proximate an axially inner side of the inlet conduit towards the cyclone second end.

13. The surface cleaning apparatus of claim 12 wherein the dirt outlet extends to a position proximate the cyclone second end.

14. The surface cleaning apparatus of claim 12 wherein the dirt outlet extends from a position 0.01-0.2 inches axially inwardly from the axially inner side of the inlet conduit towards the cyclone second end.

15. The surface cleaning apparatus of claim 12 wherein the cyclone front end is openable wherein, when the cyclone front end is moved to an open position, the cyclone chamber and the dirt collection chamber are each opened.

16. The surface cleaning apparatus of claim 12 further comprising a screen member having an outlet end located at the cyclone second end and the screen member extends to distal screen end located adjacent the axially inner side of the inlet conduit.

17. The surface cleaning apparatus of claim 16 wherein the distal end of the screen member terminates 0.01-0.75 inches from the axially inner side of the inlet conduit.

18. The surface cleaning apparatus of claim 16 wherein the distal end of the screen member terminates 0.05-0.375 inches from the axially inner side of the inlet conduit.

19. The surface cleaning apparatus of claim 1 wherein the cyclone air inlet is a tangential inlet having a conduit portion interior the cyclone chamber and the dirt outlet extends from a position proximate the cyclone first end towards the cyclone second end.

20. The surface cleaning apparatus of claim 19 further comprising a dirt outlet insert member which is removably receivable in a portion of the dirt outlet adjacent the cyclone first end and the dirt outlet insert member is opened when the cyclone front end is moved to an open position.

* * * * *